

APP PK 900

High density protective liquid for spray booths

APP No. 070903

APP PK 900 is a transparent coat that ensures protection of spray booth walls against dust circulation. Easily washable with water. Product may be applied on coated, painted surfaces, glass, rubber, sealants and plastic. If not diluted product may be applied with a brush or roller. After diluting apply with a spray gun.

To ensure optimal paint booth protection we recommend use of **APP F Mask**.

FEATURES:

-  Colourless
-  Odourless
-  High viscosity
-  Non-flammable
-  Dust-absorptive properties



APP PK 900

High density protective liquid for spray booths



Comparative analysis:

Density: g/cm ³ (20°C)
Coverage at dry coat 125µm
Recommended coat qty
Operation time
Compatibility with film
Mixing ratio (with water)
Paint both lighting colour change

PK 700	PK 800	PK 900
1,05	1,079	1,12
12-14 m ² /l	13-15 m ² /l	15-20 m ² /l
2-3	2-3	2
2 months (3 coats)	3 months (3 coats)	3 months (2 coats)
YES	YES	YES
0	max 10%	max 20%
NO	NO	NO

ADVANTAGES

<p>+ THERMAL RESISTANCE: +80°C</p>	<p>+ COLOUR: COLOURLESS – TRANSPARENT – DOES NOT CHANGE PAINT BOOTH LIGHTING COLOUR</p>	<p>+ HIGH DENSITY THAT ENABLES DILUTING UP TO 20% WITH DEMINERALIZED WATER.</p>	<p>+ ANY APPLICATION METHOD OF DENSE PREPARATION</p>
<p>+ UPON APPLICATION IT FORMS A VISCOUS TRANSPARENT PROTECTIVE BARRIER</p>	<p>+ HIGHER SPRAY DUST ABSORPTION COMPARING TO PK 700</p>	<p>+ EASY TO WASH OFF WITH WATER OR WATER AND DETERGENT</p>	<p>+ BIODEGRADABLE PRODUCT</p>

APP No.	Product Description	Volume	Qty
070903	APP PK 900 - High density protective liquid for spray booths	5 L	1