



# NTools PSM50

Pneumatic eccentric grinder

#### APP No 139200N

The **NTools PSM50** is a pneumatic oscillating mini-grinder. Exact and precise, it is perfectly suited for: light grinding, removal of light rust deposits, smoothing of putty fillings, and grinding of old paint. It is excellent for work in difficult to reach areas, such as the engine compartment, hood edges, flaps and doors.

### **FEATURES:**



Max. rotation speed 15000 RPM.



Vibration – rotation motion with **3 mm** stroke

Low air consumption **52,95 I/min.** 

## **APPLICATION:**

- car bodywork and paint shops,
- carpentry workshops and furniture production,
- varnished element production.

APP Sp. z o.o. ul. Przemysłowa 10, 62-300 Września Customer Service Department: Phone +48 61 437 00 20, bok@app.com.pl www.APP.com.pl





24.11.202



## NTools PSM50

Pneumatic eccentric grinder

12

## Design:

1 Tight and sturdy structure - made out of durable, high quality materials resistant to conditions In the workshop.

2 Compact frame - the small size and low weight ensure excellent working comfort and ability

excellent working comfort and ability to reach difficult areas

## **TECHNICAL DATA:**

| Vibration-rotation motion<br>- with stroke | 3 mm        |  |  |
|--|-------------|--|--|
| Air consumption                            | 52,95 l/min |  |  |
| Working pressure                           | 6,3 bar     |  |  |
| Max. rotation speed                        | 15000 RPM   |  |  |

| Weight                      | 0,71 kg       |  |  |
|-----------------------------|---------------|--|--|
| Noise                       | 87/97 dB (A)  |  |  |
| Length                      | 168 mm (6,6") |  |  |
| Work disk (Velcro and glue) | 50 mm (2")    |  |  |



#### 3 On switch lever lock

- secures against accidental activation of the device and guarantees safety during work.

#### 4 Choke valve

- enables smooth working speed adjustment in a range of 0-15000 RPM.



## THE SET INCLUDES:

- NTools PSM50 Pneumatic eccentric grinder,
- Work disk Ø 50 mm on Velcro, 5/16" thread (APP no. 150544N),
- Quick connection socket EURO 1/4", external thread,
- Flat wrench,
- Oil for pneumatic equipment.,
- Operating manual and warranty sheet.

| ADVANTAGES | <b>EXCELLENTLY BALANCED</b><br>with minimal vibrations (exact grinding)        | <b>VIBRATION-ROTATION MOTION</b><br>with 3 mm stroke, increasing grinding efficiency. | low compres | EFFICIENT AND RELIABLE MOTOR<br>low compressed air consumption<br>- only 52,95 I/min           |  |  |
|------------|--|---|-------------|--|--|--|
|            | BACK DISCHARGE OF AIR INTO<br>THE HANDLE<br>does not cause workplace dustiness | WORKING HEAD AT 90° ANGLE   | ensure com  | VELCRO-MOUNTED WORK DISK,<br>ensure compatibility with grinding disks with<br>a 50 mm diameter |  |  |
|            |  |   | DDU         | ci l   |  |  |

| APP No. | Product name   | RPM   | Stroke | Qty   |
|---------|--|-------|--------|-------|
| 139200N | NTools PSM50 - Pneumatic, eccentric angle grinder, d50 | 15000 | 3 mm   | 1 рс. |

#### APP Sp. z o.o.

ul. Przemysłowa 10, 62-300 Września Customer Service Department: Phone +48 61 437 00 20, bok@app.com.pl

www.APP.com.pl

24.11.2023

