SAFETY DATA SHEET According Commission Regulation (EU) 2020/878



Date of issue: 2023-12-22

APP Fiber

Page 1 z 7

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. <u>Product Identifier</u> Trade name: : APP Fiber Trade code: 010210, 010211, 010212

1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Putty with glass fiber Uses advised against: other

1.3. Details of the supplier of the safety data sheet


Company: APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: <u>www.app.com.pl</u>

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. <u>Emergency telephone number:</u> +48 (61) 437 00 00

Date of issue: 2023-12-22

SECTION 2. HAZARDS IDENTIFICATION 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 GHS07 GHS08 Danger FlamLig3: H226 Flammable liquid and vapour. SkinIrrit2: H315 Causes skin irritation. SkinSens1: H317 May cause an allergic skin reaction EveIrrit2: H319 Causes serious eve irritation STOT SE3: H335 May cause respiratory irritation Repr2: H361d Suspected of damaging the unborn child. STOT RE2: H372 Causes damage to organs (hearing organ) through prolonged or repeated exposure (inhalation) 2.2. Label elements Labelling according Regulation (EC) No 1272/2008 Contains: Stvrene Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4 methylphenyl)amino]ethanol Maleic anhydride **Signal word:** Danger **Pictogram:**



VOC/LZO (2004/42/EC, IIb: 250) <25 g/l

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
Styrene REACH 01-2119457861-32	10<20 %	100-42-5	601-026-00-0	202-851-5	GHS02; GHS07; GHS08 Wng Flam.Liq.3: H226 STOT RE1: H372 Repr2: H361d AcuteTox4: H332 SkinIrrit2: H315 EyeIrrit2: H319 AspTox1: H304 STOT SE3: H335 AquaticChronic3: H412
Maleic anhydride REACH: 01-2119472428-31	<0,1%	108-31-6	607-096-00-9	203-571-6	GHS02; GHS07 FlamLiq3: H226 AcuteTox4:H302 SkinCorr1B: H314 EyeDam1: H318 RespSens1: H334 SkinSens1: H317 STOT RE1: H372 EUH071 Specific concentration

APP B AUTO-PLAST PRODUKT	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878							
	Date of issue: 20	023-12-22	APP Fiber			Page 3 z 7		
Reaction mass of 2,2'-[(4- methylphenyl)imino]bisetha and 2-[[2-(2- hydroxyethoxy)ethyl](4 methylphenyl)amino]ethan	nol	-	-	911-490-9	limit 0,001 <skinser GHS05; GHS AcuteTox4: H SkinIrrit2: H3 SkinSens1: H3 EyeDam1: H3 AquatcChron</skinser 	07 302 315 317 18		

Full text of H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious

person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed:

May cause an allergic skin reaction

May cause respiratory irritation

Suspected of damaging the unborn child.

Causes damage to organs (hearing organ) through prolonged or repeated exposure (inhalation)

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES


6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

- Provide adequate ventilation.
- Use appropriate respiratory protection.

See protective measures under point 7 and 8.



According Commission Regulation (EU) 2020/878

APP Fiber

Page 4 z 7

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s) None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin. Eye protection: Wear face visor or goggles in circumstances where eye contact can accidentally occur. Protection for skin/hands: Nitrile gloves. Respiratory protection: Respiratory protection. Thermal Hazards: None Environmental exposure controls: None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance and colour: liquid, color as indicated on the label Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range:145°C Upper/lower flammability or explosive limits: 1,2-8,9%



Date of issue: 2023-12-22

According Commission Regulation (EU) 2020/878

APP Fiber

Page 5 z 7

Vapour density: N.D. Flash point: 31°C Evaporation rate: N.A. Vapour pressure:6,67 kPa Density: 1442 kg/m³ (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: 238°C Decomposition temperature: N.A. Viscosity dyn.: >20,5 mm²/s (40°C) Viscosity kin.: N.D. Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC<2<u>5 g/l</u> SECTION 10. STABILITY AND REACTIVITY 10.1. Reactivity Mixture is not reactive. 10.2. Chemical stability Stable under normal conditions of handling and storage. 10.3. Possibility of hazardous reactions None. 10.4. Conditions to avoid - solar radiation - sparks - flame - heat **10.5.** Incompatible materials - strong acids - oxides and reductors 10.6. Hazardous decomposition products None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects a) acute toxicity: no hazard Styrene LD50 (rat, ingestion) 2650 mg/kg LC50 (rat, inhalation): 11,8 mg/m3/4 h LD50 (rabbit, skin): 2000 mg/kg b) skin corrosion/irritation: skin irritation. c) serious eye damage/irritation: Causes serious eye irritation d) respiratory or skin sensitization: May cause an allergic skin reaction e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard g) reproductive toxicity: Suspected of damaging the unborn child. h) STOT-single exposure: May cause respiratory irritation i) STOT-repeated exposure: Causes damage to organs (hearing organ) through prolonged or repeated exposure (inhalation) j) aspiration hazard: NO hazard 11.2.1. Endocrine disrupting properties - no data 11.2.2. Other information - no data

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity MIxture is not classified as hazardous.

12.2. Persistence and degradability



SAFETY DATA SHEET According Commission Regulation (EU) 2020/878

Date of issue: 2023-12-22

APP Fiber

Page 6 z 7

No data. **12.3. Bioaccumulative potential** No data. **12.4. Mobility in soil** No data **12.5. Results of PBT and vPvB assessment** vPvB Substances: None - PBT Substances: None **12.6. Endocrine disrupting properties** None **12.7. Other adverse effects** None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number 3269 14.2. UN proper shipping name Polyester resin kit. 14.3. Transport hazard class(es) 3 14.4. Packing Group III 14.5. Environmental hazards No 14.6. Special Precautions for User During handling wear personal protection equipment (see Section 8) Avoid heat and flame. 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code N.A. Label: 3

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H312 Harmful in contact with skin

H314 Causes severe skin burns and eye damage

- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage



APP Fiber

Page 7 z 7

H319 Causes serious eye irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation H336 May cause drowsiness or dizziness

H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled

Date of issue: 2023-12-22

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure through prolonged or repeated exposure - hear apparatus.

H400 Very toxic to aquatic life

H412 Harmful to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.