SATEFY DATA SHEET According Commission Regulation (EU) 2020/878



Date of issue: 25.01.2024

APP Vesta

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

1.1. Product Identifier Trade name: APP Vesta Trade code: 010430

1.2. Relevant identified uses of the substance/mixture and uses advised against Filler.


Uses advised against: other

1.3. Details of the supplier of the safety data sheet **Company:** APP Sp. z o. o. ul. Przemysłowa 10, 62 - 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: www.app.com.pl

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. Emergency telephone number: +48 (61) 437 00 00

Date of issue: 25.01.2024



_A DD=	SATEFY DATA SHEET According Commission Regulation (EU) 2020/878				
AUTO-PLAST PRODUKT	Date of issue: 25.01.2024	APP Vesta	Page 2 z 6		
H315 Causes skin irritation	l.				
H317 May cause an allergi	c skin reaction				
H319 Causes serious eye ir	ritation				
H361d Suspected of damage	ging the unborn child.				
H372 Causes damage to or	gans through prolonged or re	epeated exposure through prolonged or repeated e	xposure –		
inhalation					
EUH212 Warning! Hazard	ous respirable dust may be f	formed when used. Do not breathe dust.			
Precautionary statement	nt(s)				
P210 Keep away from heat	, hot surfaces, sparks, open	flames and other ignition sources. No smoking.			
P280 Wear protective glov	es/protective clothing/eye pr	rotection/face protection.			
P303+P361+P353 IF ON water/shower.	SKIN (or hair): Take off im	mediately all contaminated clothing. Rinse skin w	ith		
and easy to do. Continue ri	nsing.	h water for several minutes. Remove contact lense	es, if present		
P308 + P313 IF exposed on	concerned: Get medical adv	vice/attention.			
P403 Store in a well-ventile	ated place.				
P501 Dispose of contents/c	container according to local/	regional/national/international regulations.			

P501 Dispose of contents/container according to local/regional/national/international regulations.

2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006 VOC (2004/42/EC, IIb: 250) <250 g/l

UN: 3269

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.


3.2. Mixtures

Hazardous components within the meaning of CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:	
Styrene	10-<25	100-42-5	601-026-00-0	202-851-5	GHS02; GHS07;	
	%				GHS08	
REACH:					Flam.Liq.3: H226	
01-2119457861-32					STOT RE1: H372	
					Repr2: H361d	
					AspTox1: H304	
					AcuteTox4: H332	
					SkinIrrit2: H315	
					EyeIrrit2: H319	
Ethyl acetate	<2,5%	141-78-6	607-022-00-5	205-500-4	GHS02; GHS07	
REACH: 01-2119475103-46					Flam. Liq. 2; H225	
					Eye Irrit. 2: H319	
					STOT SE 3: H336	
	0,01-	108-31-6	607-096-00-9	203-571-6	GHS02; GHS07	
Maleic anhydrideREACH:	<0,1%				FlamLiq3: H226	
01-2119472428-31					AcuteTox4:H302	
					SkinCorr1B: H314	
					EyeDam1: H318	
					RespSens1: H334	
					SkinSens1: H317	
					STOT RE1: H372	
					EUH071	
					Specific Concentration	
					Limit:	
					Skin Sens. 1A; H317:	
					C ≥ 0,001	
					%	

Full text of H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES



APP Vesta

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious

person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed:

May cause an allergic skin reaction

Suspected of damaging the unborn child.

Causes damage to organs through prolonged or repeated exposure through prolonged or repeated exposure – inhalation

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.



SATEFY DATA SHEET

According Commission Regulation (EU) 2020/878

APP Vesta

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A. **8.2. Exposure controls**

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Date of issue: 25.01.2024

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands: Nitrile gloves.

Respiratory protection:

Respiratory protection.

Thermal Hazards:

None

Environmental exposure controls: None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance and colour: liquid, green Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range:>77.2°C Upper/lower flammability or explosive limits: N.D. Vapour density: N.D. Flash point: 32°C Evaporation rate: N.A. Vapour pressure: 1594 Pa (20°C), >6905 Pa (50°C) Density: $1030 \text{ kg/m}^3 (15^{\circ}\text{C})$ Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: 238°C Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: $>20,5 \text{ mm}^2/\text{s}$ (40°C) Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information



VOC: <250 g/l

SECTION 10. STABILITY AND REACTIVITY

Date of issue: 25.01.2024

10.1. Reactivity
Mixture is not reactive.
10.2. Chemical stability
Stable under normal conditions of handling and storage.
10.3. Possibility of hazardous reactions
None.
10.4. Conditions to avoid
- solar radiation
- sparks
- flame
- heat
10.5. Incompatible materials
- strong acids
- oxides and reductors
10.6. Hazardous decomposition products

None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects a) acute toxicity: no hazard Styrene LD50 (rat, ingestion) 2650 mg/kg LC50 (rat, inhalation): 11,8 mg/m3/4 h LD50 (rabbit, skin): 2000 mg/kg b) skin corrosion/irritation: skin irritation. c) serious eye damage/irritation: Causes serious eye irritation d) respiratory or skin sensitization: May cause an allergic skin reaction e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard g) reproductive toxicity: Suspected of damaging the unborn child. h) STOT-single exposure: no hazard i) STOT-repeated exposure: Causes damage to organs through prolonged or repeated exposure through prolonged or repeated exposure j) aspiration hazard: NO hazard 11.2.1. Endocrine disrupting properties no data 11.2.2. Other information Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Mixture is not classified as hazardous.

12.2. Persistence and degradability

No data.
12.3. Bioaccumulative potential
No data.

12.4. Mobility in soil

No data

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None
12.6. Endocrine disrupting properties

None

12.7. Other adverse effects

None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds,





SATEFY DATA SHEET According Commission Regulation (EU) 2020/878

meno	 c, _•	 	

Date of issue: 25.01.2024

APP Vesta

Page 6 z 6

ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION
14.1. UN number
3269
14.2. UN proper shipping name
Polyester resin kit.
14.3. Transport hazard class(es)
3
14.4. Packing Group
III
14.5. Environmental hazards
No
14.6. Special Precautions for User
During handling wear personal protection equipment (see Section 8)
Avoid heat and flame.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
N.A.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour

H226 Flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H332 Harmful if inhaled

H336 May cause drowsiness or dizziness

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure through prolonged or repeated exposure - hear apparatus.

H400 Very toxic to aquatic life

H412 Harmful to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to

the specific use intended.