

**SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING****1.1. Product Identifier**

Trade name: APP 2K Acryl Klarlack Compact 2:1

Trade code: 020115, 020116, 020117

**1.2. Relevant identified uses of the substance/mixture and uses advised against**  
**Two-Component Acrylic Clear Top Coat****1.3. Details of the supplier of the safety data sheet**

Company: APP Sp. z o. o.  
ul. Przemysłowa 10, 62 – 300 Września  
Tel. +48 (061) 437 00 00  
Fax. +48 (061) 437 91 37  
Mail: [app@app.com.pl](mailto:app@app.com.pl)  
Strona WEB: [www.app.com.pl](http://www.app.com.pl)

Safety Data Sheet e-mail: [dzp@app.com.pl](mailto:dzp@app.com.pl)**1.4. Emergency telephone number:**

+48 (61) 437 00 00

Date of issue: 16.06.2016

**SECTION 2. HAZARDS IDENTIFICATION****2.1. Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008

**GHS02****GHS07****GHS08****Danger****FlamLiq3: H225 Highly flammable liquid and vapour.****Skin Irrit2: H315 Causes skin irritation****EyeIrrit2: H319 Causes serious eye irritation****STOT SE3: H336 May cause drowsiness or dizziness****STOT RE2: H373 May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure if inhaled.****EUH208 Contains: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Hydroxyphenylbenzotriazol derivatives mixture, Bishydroxyphenylbenzotriazol derivatives mixture. May produce an allergic reaction****2.2. Label elements****Labelling according Regulation (EC) No 1272/2008**

Contains:  
n-butyl acetate  
Acetone

**Signal word:**

Warning

**Pictogram:**



GHS02



GHS07



GHS08

**Hazard statement(s)**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

H373 May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure if inhaled.

EUH208 Contains: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Hydroxyphenylbenzotriazol derivatives mixture, Bishydroxyphenylbenzotriazol derivatives mixture. May produce an allergic reaction

**Precautionary statement(s)**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+ P361+ P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370+ P378 In case of fire: Use sand, extinguishing powder or alcohol resistant foam to extinguish.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container according to local/regional/national/international regulations.

**2.3 Other hazards**

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

UN: 1263

VOC (2004/42/EC, IIe: 840) 530 g/l

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**


**3.1. Substances**

N.A.

**3.2. Mixtures**

**Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:**

Name	Conc.	CAS No	Index No	EC No	Classification:
------	-------	--------	----------	-------	-----------------

		SATEFY DATA SHEET			
		Date of issue: 16.06.2016	APP 2K Acryl Klarlack Compact 2:1		Page 3 z 8
Acetone REACH Reg. No: 01-2119471330-49	20-<30%	67-64-1	606-001-00-8	200-662-2	GHS02; GHS07 Dgr Flam. Liq. 2: H225 Eye Irrit. 2: H319 STOT SE 3: H336 EUH066
n-butyl acetate REACH Reg. No 01-2119485492-29-XXXX	15-20%	123-86-4	607-025-00-1	204-658-1	GHS02; GHS04 Wng Flam.Liq.3: H226 STOT SE3: H336 EUH066
Xylene REACH Reg. No: 01-2119488216-32-XXXX	12,20%	1330-20-7	601-022-00-9	215-525-7	GHS02; GHS07 Wng FlamLiq3: H226 AcuteTox4: H312 AcuteTox4: H332 SkinIrrit2: H315
Ethylbenzene REACH Reg. No 01-2119489370-35	1-<10 %	100-41-4	601-023-00-4	202-849-4	GHS02; GHS07 ; GHS08 Dgr Flam. Liq.2: H225 AspTox1: H304 STOT RE2: H373 Acute Tox.4: H332 SkinIrrit2: H315 EyeIrrit2: H319 STOT SE3: H335
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate REACH Reg. No 01-2119491304-40	<0,25%	41556-26-7	Brak	255-437-1	GHS07; GHS09 Wng SkinSens.1: H317 Aquatic Acute 1: H400 Aquatic Chronic 1: H410
Hydroxy phenylbenzotriazol derivatives mixture	<1%	104810-47-1	607-176-00-3	400-830-7	GHS07; GHS09 Wng SkinSens.1: H317 AquaticChronic2:H411
Bishydroxy phenylbenzotriazol derivatives mixture	<1%	104810-48-2	Brak	600-603-4	GHS07; GHS09 Wng SkinSens.1: H317 AquaticChronic2:H411

Full text of R-Phrases and H-Phrases can be found under heading 16

#### SECTION 4. FIRST AID MEASURES

**4.1. Description of first aid measures****In case of skin contact:**

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. In case of irritation, consult a doctor

**In case of eyes contact:**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

**In case of Ingestion:**

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

**In case of Inhalation:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

**4.2. Most important symptoms and effects, both acute and delayed:**

May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure if inhaled.

Contains: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Hydroxyphenylbenzotriazol derivatives mixture, Bishydroxyphenylbenzotriazol derivatives mixture. May produce an allergic reaction

**4.3. Indication of any immediate medical attention and special treatment needed**

In case if ingestion consult a doctor.

**Treatment:**

None

**SECTION 5. FIRE-FIGHTING MEASURES****5.1. Extinguishing media****Suitable extinguishing media:**

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

**Extinguishing media which must not be used for safety reasons:**

Water jet.

**5.2. Special hazards arising from the substance or mixture**

Highly flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

**5.3. Advice for fire-fighters**

Fires in confined spaces should be dealt with by trained personnel wearing approved air supplied breathing apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

**SECTION 6. ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

**6.2. Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

**6.3. Methods and material for containment and cleaning up**

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

**6.4. Reference to other sections**

See Section 8 for information on personal protection equipment.

**SECTION 7. HANDLING AND STORAGE****7.1. Precautions for safe handling**

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

**7.2. Conditions for safe storage, including any incompatibilities**

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

**7.3. Specific end use(s)**

None.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters**

N.A.

**8.2. Exposure controls**

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

Nitrile gloves.

Respiratory protection:

Respiratory protection.

Thermal Hazards:

None

Environmental exposure controls:

None

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

Appearance and colour: liquid, colorless

Odour: characteristic

Odour threshold: N.D.

pH: N.A.

Melting point / freezing point: N.D.

Initial boiling point and boiling range: 56.2°C

Upper/lower flammability or explosive limits: 1.9-10,3 % (v/v)

Vapour density: N.D.

Flash point: -9°C

Evaporation rate: N.A.

Vapour pressure: 100.4 hPa (20°C), 451 hPa (50°C)

Density: 960 kg/m<sup>3</sup> (15°C)

Solubility in water: insoluble

Solubility in organic solvents: soluble in aromatic solvents

Lipid solubility: N.A.

Partition coefficient (n-octanol/water): N.A.

Ignition temperature: 451°C

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Viscosity dyn.: 57 mPas (20°C)

Viscosity kin.: >20.5 mm<sup>2</sup>/s (40°C)

Explosive properties: can form an explosive mixture in air

Oxidizing properties: not oxidizing

**9.2. Other information**

VOC: 486 g/l

**SECTION 10. STABILITY AND REACTIVITY****10.1. Reactivity**

Mixture is not reactive.

**10.2. Chemical stability**

Stable under normal conditions of handling and storage.

**10.3. Possibility of hazardous reactions**

None.

**10.4. Conditions to avoid**

- solar radiation
- sparks
- flame
- heat

**10.5. Incompatible materials**

- strong acids
- oxides and reductors

**10.6. Hazardous decomposition products**

None.

**SECTION 11. TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

Causes skin irritation

Causes serious eye irritation

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure if inhaled.

Contains: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Hydroxyphenylbenzotriazol derivatives mixture,

Bishydroxyphenylbenzotriazol derivatives mixture. May produce an allergic reaction

**a) acute toxicity:** no hazard**b) skin corrosion/irritation:** Causes skin irritation**c) serious eye damage/irritation:** Causes serious eye irritation**d) respiratory or skin sensitization:** Contains: Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Hydroxyphenylbenzotriazol derivatives mixture, Bishydroxyphenylbenzotriazol derivatives mixture. May produce an allergic reaction**e) germ cell mutagenicity:** no hazard**f) carcinogenicity:** no hazard**g) reproductive toxicity:** no hazard**h) STOT-single exposure:** May cause drowsiness or dizziness**i) STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure if inhaled.**j) aspiration hazard:** No hazard.

Acetone

LD50 (rat, ingestion) 5800 mg/kg

LC50 (rat, inhalation): 100.2 mg/m<sup>3</sup>/4 h

LD50 (rabbit, skin): 20000 mg/kg

Xylene

LD50 (rat, ingestion) 4300 mg/kg

LC50 (rat, inhalation): 22080 mg/m<sup>3</sup>/4 h

LD50 (rabbit, skin): 1700 mg/kg

Ethylbenzene

LD50 (rat, ingestion); 3500 mg/kg

LC50 (rat, inhalation): 17400 mg/m<sup>3</sup>/4 h

LD50 (rabbit, skin): 15400 mg/kg

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

LD50 (rat, ingestion); &gt;2000 mg/kg

Hydroxy phenylbenzotriazol derivatives mixture

LD50 (rat, ingestion); &gt;2000 mg/kg

**SECTION 12. ECOLOGICAL INFORMATION****12.1. Toxicity**

Mixture is not classified as hazardous.

**Buthyl acetate**

- fish LC50: 18 mg/dm<sup>3</sup>/96h
- crustacea EC50: 32 mg/dm<sup>3</sup>/48 h
- algae IC50: 675 mg/dm<sup>3</sup>/72 h

**Xylene:**

- fish LC50: 14 mg/dm<sup>3</sup>/96h
- crustacea EC50: 16 mg/dm<sup>3</sup>/48h

**Ethylbenzene:**

- fish LC50: 12 mg/dm<sup>3</sup>/96h
- crustacea EC50: 1,8 mg/dm<sup>3</sup>/48h
- algae IC50: mg/dm<sup>3</sup>/72 h

**12.2. Persistence and degradability**

No data.

**12.3. Bioaccumulative potential**

No data.

**12.4. Mobility in soil**

No data

**12.5. Results of PBT and vPvB assessment**

vPvB Substances: None - PBT Substances: None

**12.6. Other adverse effects**

None

**SECTION 13. DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods**

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

**SECTION 14. TRANSPORT INFORMATION****14.1. UN number**

1263

**14.2. UN proper shipping name**

Paint

**14.3. Transport hazard class(es)**

3

**14.4. Packing Group**

III

**14.5. Environmental hazards**

No

**14.6. Special Precautions for User**

During handling wear personal protection equipment (see Section 8)

Avoid heat and flame.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

N.A.

**SECTION 15. REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

**Where applicable, refer to the following regulatory provisions :**

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

**15.2. Chemical Safety Assessment**

No

**SECTION 16. OTHER INFORMATION**Full text of phrases referred to in Section 3:

H225 – Highly flammable liquid and vapour  
H226 - Flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H312 - Harmful in contact with skin  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
EUH066 Repeated exposure may cause skin dryness or cracking  
H411 - Toxic to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.