

**SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING****1.1. Product Identifier**

Trade name: APP Harter Klarlack Beta 2:1 normal

Trade code: 020390, 020391

**1.2. Relevant identified uses of the substance/mixture and uses advised against****Hardener****1.3. Details of the supplier of the safety data sheet**

Company: APP Sp. z o. o.  
ul. Przemysłowa 10, 62 – 300 Września  
Tel. +48 (061) 437 00 00  
Fax. +48 (061) 437 91 37  
Mail: [app@app.com.pl](mailto:app@app.com.pl)  
Strona WEB: [www.app.com.pl](http://www.app.com.pl)

Safety Data Sheet e-mail: Tomasz Gołda, [t.golda@app.com.pl](mailto:t.golda@app.com.pl)**1.4. Emergency telephone number:****+48 (61) 437 00 00****Date of issue:** 25.01.2024**SECTION 2. HAZARDS IDENTIFICATION****2.1. Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02



GHS07



GHS08

**Warning****FlamLiq3: H226 Flammable liquid and vapour.****SkinIrrit2: H315 Causes skin irritation.****SkinSens1: H317 May cause an allergic skin reaction****EyeIrrit2: H319 Causes serious eye irritation****AxuteTox4: H332 Harmful if inhaled****STOT SE3: H335 May cause respiratory irritation****STOTSE3: H336 May cause drowsiness or dizziness****STOT RE2: H373 May cause damage to organs through prolonged or repeated exposure (inhalation)****AquaticChronic3: H412 Harmful to aquatic life with long lasting effects****EUH204 Contains isocyanates. May produce an allergic reaction.****2.2. Label elements****Labelling according Regulation (EC) No 1272/2008**

Contains:

Xylene

Hexamethylene diisocyanate oligomers

Butyl acetate

C9 hydrocarbons, aromatic

Tosyl isocyanate

**Signal word:**

Danger

**Pictogram:**



**GHS02**



**GHS07**



**GHS08**

**Hazard statement(s)**

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction  
H319 Causes serious eye irritation  
H332 Harmful if inhaled  
H335 May cause respiratory irritation  
H336 May cause drowsiness or dizziness  
H373 May cause damage to organs through prolonged or repeated exposure (inhalation)  
H412 Harmful to aquatic life with long lasting effects  
EUH204 Contains isocyanates. May produce an allergic reaction.

**Precautionary statement(s)**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+ P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403 Store in a well-ventilated place.  
P501 Dispose of contents/container according to local/regional/national/international regulations.

**2.3 Other hazards**

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006  
UN: 1263

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**


**3.1. Substances**

N.A.

**3.2. Mixtures**

**Hazardous components within the meaning of CLP regulation and related classification:**

Name	Conc.	CAS No	Index No	EC No	Classification:
Xylene REACH:01-21194882216-32	25-30%	1330-20-7	601-022-00-9	215-525-7	GHS02; GHS07 FlamLiq3: H226 AcuteTox4: H312 AcuteTox4: H332 SkinIrrit2: H315 EyeIrrit2: H319 STOT RE2: H373 AspTox1: H304 STOTSE3: H335
Oligomers hexamethylene diisocyanate REACH: 01-2119485796-17	30-40 %	28182-81-2	-	500-060-2	GHS07 AcuteTox4: H332 SkinSens1: H317 STOT SE3: H335
Butyl acetate REACH 01-2119485493-29	15-<20 %	123-86-4	607-025-00-1	204-658-1	GHS02; GHS04 Flam.Liq.3: H226 STOT SE3: H336 EUH066
Hydrocarbons C9, aromatic. REACH: 01-	20-25%	-	-	918-668-5	GHS02; GHS07; GHS08 ; GHS09 Flam. Liq. 3, H226

		<b>SAFETY DATA SHEET</b> According Commission Regulation (EU) 2020/878			
		Date of issue: 25.01.2024	APP Harter Klarlack Beta 2:1 normal		Page 3 z 7
2119455851-35					Asp. Tox. 1: H304 AquaticChronic 2: H411 STOT SE 3; H335+H336
Tosyl isocyanate REACH 01- 2119980050-47	<0,25%	4083-64-1	615-012-00-7	223-810-8	GHS07; GHS08 RespSens1: H334 SkinIrrit2: H315 EyeIrrit2: H319 STOT SE3: H335
2,6-di-tert-butyl-p-cresol	<0,25%	128-37-0	-	204-881-4	GHS09 AquaticAcute1: H400 AquaticChronic1: H410

Full text of R-Phrases and H-Phrases can be found under heading 16

## SECTION 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

#### In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. In case of irritation, consult a doctor

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

#### In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

#### In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

### 4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction

Harmful if inhaled

May cause respiratory irritation

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure (inhalation)

Contains isocyanates. May produce an allergic reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

#### Treatment:

None

## SECTION 5. FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

#### Extinguishing media which must not be used for safety reasons:

Water jet.

### 5.2. Special hazards arising from the substance or mixture

Flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

### 5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel wearing approved air supplied breathing apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.



Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

#### **6.2. Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

#### **6.3. Methods and material for containment and cleaning up**

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

#### **6.4. Reference to other sections**

See Section 8 for information on personal protection equipment.

## **SECTION 7. HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

### **7.2. Conditions for safe storage, including any incompatibilities**

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

### **7.3. Specific end use(s)**

None.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **8.1. Control parameters**

N.A.

### **8.2. Exposure controls**

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

#### Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

#### Protection for skin/hands:

Nitrile gloves.

#### Respiratory protection:

Respiratory protection.

#### Thermal Hazards:

None

#### Environmental exposure controls:

None

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

### **9.1. Information on basic physical and chemical properties**

Appearance and colour: liquid, colorless

Odour: characteristic

Odour threshold: N.D.



pH: N.A.  
Melting point / freezing point: N.D.  
Initial boiling point and boiling range: 127°C  
Upper/lower flammability or explosive limits: 0,7-7,0% (v/v)  
Vapour density: N.D.  
Flash point: 23°C  
Evaporation rate: N.A.  
Vapour pressure: 9.5 hPa  
Density: 948kg/m<sup>3</sup> (15°C)  
Solubility in water: insoluble  
Solubility in organic solvents: soluble in aromatic solvents  
Lipid solubility: N.A.  
Partition coefficient (n-octanol/water): N.A.  
Ignition temperature: N.D.  
Auto-ignition temperature: N.A.  
Decomposition temperature: N.A.  
Viscosity: N.D.  
Explosive properties: can form an explosive mixture in air  
Oxidizing properties: not oxidizing

### 9.2. Other information

-

## SECTION 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Mixture is not reactive.

### 10.2. Chemical stability

Stable under normal conditions of handling and storage.

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

- solar radiation
- sparks
- flame
- heat

### 10.5. Incompatible materials

- strong acids
- oxides and reductors

### 10.6. Hazardous decomposition products

None.

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

**a) acute toxicity:** harmful by inhalation

**b) skin corrosion/irritation:** Causes skin irritation.

**c) serious eye damage/irritation:** Causes serious eye irritation

**d) respiratory or skin sensitization:** May cause an allergic skin reaction

Contains isocyanates. May produce an allergic reaction.

**e) germ cell mutagenicity:** no hazard

**f) carcinogenicity:** no hazard

**g) reproductive toxicity:** no hazard

**h) STOT-single exposure:** May cause respiratory irritation, May cause drowsiness or dizziness

**i) STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure.

**j) aspiration hazard:** May be fatal if swallowed and enters airways

### 11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

- no data

11.2.2. Other information

- no data

## SECTION 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity



Harmful to aquatic life with long lasting effects

**12.2. Persistence and degradability**

No data.

**12.3. Bioaccumulative potential**

No data.

**12.4. Mobility in soil**

No data

**12.5. Results of PBT and vPvB assessment**

vPvB Substances: None - PBT Substances: None

**12.6. Endocrine disrupting properties**

None

**12.7. Other adverse effects**

None

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**13.1. Waste treatment methods**

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

---

**SECTION 14. TRANSPORT INFORMATION**

**14.1. UN number**

1263

**14.2. UN proper shipping name**

Paint

**14.3. Transport hazard class(es)**

3

**14.4. Packing Group**

III

**14.5. Environmental hazards**

No

**14.6. Special Precautions for User**

During handling wear personal protection equipment (see Section 8)

Avoid heat and flame.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

N.A.

---

**SECTION 15. REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

**Where applicable, refer to the following regulatory provisions :**

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

**15.2. Chemical Safety Assessment**

No

---

**SECTION 16. OTHER INFORMATION**

Full text of phrases referred to in Section 3:

H226 - Flammable liquid and vapour

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled



**SAFETY DATA SHEET**  
According Commission Regulation (EU) 2020/878

Date of issue: 25.01.2024

**APP Harter Klarlack Beta 2:1 normal**

Page 7 z 7

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness H411 - Toxic to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.