SAFETY DATA SHEET According Commission Regulation (EU) 2020/878



Date of issue: 2024-07-28

APP AcrylFiller Compact 5:1

Page 1 z 7

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. <u>Product Identifier</u> Trade name: **APP AcrylFiller** (

Trade name: APP AcrylFiller Compact 5:1 Trade code: 020444, 020445

1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Two-component acrylic primer f

1.3. <u>Details of the supplier of the safety data sheet</u> Company: APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: <u>www.app.com.pl</u>

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. <u>Emergency telephone number:</u> +48 (61) 437 00 00

Date of issue: 2024-07-28

SECTION 2. HAZARDS IDENTIFICATION 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Danger

FlamLiq3: H226 Flammable liquid and vapour. SkinIrrit2: H315 Causes skin irritation EyeIrrit2: H319 Causes serious eye irritation STOTRE2: H373 May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure (oral) AquaticChronic3: H412 Harmful to aquatic life with long lasting effects 2.2. Label elements Labelling according Regulation (EC) No 1272/2008 Contains: Xylene (mixture of isomers) Ethylbenzene Butyl acetate Signal word: Warning Pictogram:



Date of issue: 2024-07-28

APP AcrylFiller Compact 5:1

Page 2 z 7



Hazard statement(s)

H226 Flammable liquid and vapour.

H315 Causes skin irritation

H319 Causes serious eye irritation

H373 May cause damage to organs through prolonged or repeated exposure (oral)

H412 Harmful to aquatic life with long lasting effects

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

GHS08

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+ P352 IF ON SKIN: Wash with plenty of water

P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370 + P378 In case of fire: use ABC powder extinguisher to extinguish.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container to an authorised waste collection point.

2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

UN: 1263

VOC/LZO (2004/42/EC, IIc: 540) 394,05 g/l (020444, szary)

VOC/LZO (2004/42/EC, IIc: 540) 392,79 g/l (020445, czarny)

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:	
Xylene Reg. No. REACH:	10-25%	1330-20-7	601-022-00-9	215-525-7	GHS02; GHS07	
01-21194882216-32					FlamLiq3: H226	
					AcuteTox4: H312	
					AcuteTox4: H332	
					SkinIrrit2: H315	
					EyeIrrit2: H319	
					STOT SE3:	
					H335STOT RE2: H373	
					AspTox1: H304	
Butyl acetate Reg. No.	5-<10%	123-86-4	607-025-00-1	204-658-1	GHS02; GHS07	
REACH: 01-2119485493-29					Flam.Liq.3: H226	
					STOT SE3: H336	
					EUH066	
Ethylbenzene Reg. No.	2,5-<5%	100-41-4	601-023-00-4	202-849-4	GHS02; GHS07 ;	
REACH: 01-2119489370-35					GHS08	
					Flam. Liq.2: H225	
					AspTox1: H304	
					STOT RE2: H373	
					Acute Tox.4: H332	
					SkinIrrit2: H315	
					EyeIrrit2: H319	
					STOT SE3: H335	
C9 hydrocarbons, aromatic	<2,5%	64742-95-	-	-	GHS02; GHS07;	
		6			GHS08; GHS09	
					Flam. Liq. 3: H226	

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878						
BAUTO-PLAST PRODUKT	Date of issue: 2024-07-28		APP Acr	ylFiller Comp	act 5:1	Page 3 z 7	
1-methoxy-2-propyl aceta 2-methoxy-1-methylethy acetate Reg. No. REACH 01-2119475791-29	1	108-65-6	607-195-00-7	203-603-9	Asp. Tox. STOT SE STOT SE EUH AquaticC H4 GHS02; Uwa FlamLiq. Eye Irrit.	3: H335 3: H336 066 hronic2: 11 GHS07 nga 3: H226	
Amorphous silicon dioxic	le <1 %	7631-86-	9 -	231-545-4	-		
Crystalline silica	<0,1%	14808-60 7		238-878-4	-		

Full text of H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious

person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed:

May cause damage to organs through prolonged or repeated exposure (oral)

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment.



APP AcrylFiller Compact 5:1

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Date of issue: 2024-07-28

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

a) Eye or face protection: in case of frequent exposure, goggles or glasses that fit well to the face (in accordance with EN 166:2002, EN 167:2002, EN 168:2002, EN ISO 4007:2018)

b) Skin protection: protective (working) clothes, protective gloves (in accordance with the standards: EN ISO 374-1:2016+A1:2018, EN 16523-1:2015+A1:2018, EN ISO 21420:2020)

c) Respiratory protection: efficient ventilation; in the case of frequent exposure, a mask with a multi-gas absorber; Mask conforming to EN 405:2002+A1:2010 (Replace when taste or odor occurs

impurities inside the face mask. if contamination comes with warnings it is recommended to use isolation equipment.) Respiratory protection.

- Thermal Hazards:
- None

Environmental exposure controls:

None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, color according to the label





Date of issue: 2024-07-28

APP AcrylFiller Compact 5:1

Page 5 z 7

Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range: 108-2230°C Upper/lower flammability or explosive limits: N.D. Vapour density: N.D. Flash point: 25°C Evaporation rate: N.A. Vapour pressure: 880Pa (20°C), 4541.19 Pa (50°C) Density: 1550 kg/m³ (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: 315°C Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: >20.5 mm²/s Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC (2004/42/EC, IIc: 540) 394,05 g/l (020444) VOC (2004/42/EC, IIc: 540) 392,79 g/l (020445)

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Mixture is not reactive. **10.2. Chemical stability** Stable under normal conditions of handling and storage. **10.3. Possibility of hazardous reactions** None. **10.4. Conditions to avoid** - solar radiation - sparks - flame - heat **10.5. Incompatible materials** - strong acids - strong bases **10.6. Hazardous decomposition products**

None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects a) acute toxicity: no hazard b) skin corrosion/irritation: Causes skin irritation c) serious eye damage/irritation: Causes serious eye irritation d) respiratory or skin sensitization: no hazard e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard g) reproductive toxicity: no hazard h) STOT-single exposure: no hazard i) STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure (oral) j) aspiration hazard: no hazard 11.2. Information on other hazards 11.2.1. Endocrine disrupting properties - no data 11.2.2. Other information Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.



SAFETY DATA SHEET According Commission Regulation (EU) 2020/878

APP AcrylFiller Compact 5:1

Page 6 z 7

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity
Harmful to aquatic life with long lasting effects
12.2. Persistence and degradability
No data.
12.3. Bioaccumulative potential
No data.
12.4. Mobility in soil
No data
12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
12.6. Other adverse effects
None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number
1263
14.2. UN proper shipping name
Paint
14.3. Transport hazard class(es)
3
14.4. Packing Group
III
14.5. Environmental hazards
No
14.6. Special Precautions for User
During handling wear personal protection equipment (see Section 8)
Avoid heat and flame.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
N.A.

Date of issue: 2024-07-28

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive) **15.2. Chemical Safety Assessment**

No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878				
AUTO-PLAST PRODUKT	Date of issue: 2024-07-28	APP AcrylFiller Compact 5:1	Page 7 z 7		

H411 - Toxic to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.