SAFETY DATA SHEET According Commission Regulation (EU) 2020/878



Date of issue: 2022-06-20

APP Harter AcrylFiller Multi 5:1

Page 1 z 7

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: **APP Harter AcrylFiller Multi 5:1** Trade code: **020534**, **020535**, **020536**, **020537**

1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Hardener.

1.3. Details of the supplier of the safety data sheet

Company: APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: <u>www.app.com.pl</u>

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. <u>Emergency telephone number:</u> +48 (61) 437 00 00

Date of issue: 2022-06-20

SECTION 2. HAZARDS IDENTIFICATION 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Danger

FlamLiq3: H226 Flammable liquid and vapour. RespSens: H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled SkinSens1: H317 May cause an allergic skin reaction STOTRE3: H335 May cause respiratory irritation STOT SE3: H336 May cause drowsiness or dizziness AquaticChronic3:H412 Harmful to aquatic life with long lasting effects EUH204 Contains isocyanates. May produce an allergic reaction. 2.2. Label elements Labelling according Regulation (EC) No 1272/2008 Contains: n-butyl acetate Poly(hexamethylene diisocyanate) Hydrocarbons, C9, aromatic Tosyl isocyanate **Signal word:** Danger **Pictogram:**

GHS02 Hazard statement(s) **GHS07**

APP® auto-plast produkt	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878					
	Date of issue: 2022-06-20	APP Harter AcrylFiller Multi 5:1	Page 2 z 7			
H226 Flammable liquid and vapour.						
H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled						

H317 May cause an allergic skin reaction

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H412 Harmful to aquatic life with long lasting effects

EUH204 Contains isocyanates. May produce an allergic reaction.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+ P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342+ P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...

P303+ P361+ P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006 UN: 1263

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
n-butyl acetate REACH Reg. No 01-2119485493-29	40-50 %	123-86-4	607-025-00-1	204-658-1	GHS02; GHS04 Wng Flam.Liq.3: H226 STOT SE3: H336 EUH066
Poly(hexamethylene diisocyanate) REACH Reg. No 01-2119488934-20	40-50 %	28182-81-2	brak	500-060-2	GHS07; Wng AcuteTox4: H332 SkinSens1: H317 STOT SE3: H335

		SAFETY DATA SHEET According Commission Regulation (EU) 2020/878					
BUTO-PLAST PRODUKT	Date of issue	: 2022-06-20	APP Harter A	crylFiller Mu	ılti 5:1	ti 5:1 Page 3 z 7	
Hydrocarbons, C9, aromatic REACH: 01- 2119455851-35	7-10%	brak	brak	918-668-5	GHS08 Flam. Liq. 3, Asp. Tox. 1: AquaticChron STOT SE 3; I	H304 nic 2: H411	
Xylene REACH: 01-2119488216-32	3-5%	1330-20-7	601-022-00-9	215-525-7	GHS02; GHS FlamLiq3: H2 AcuteTox4: H AcuteTox4: H SkinIrrit2: H STOT SE3: H STOT RE2: H AspTox1: H3	226 1312 1332 315 1335 1373	
Tosyl isocyanate	0,25-0,5 %	4083-64-1	615-012-00-7	223-810-8	GHS07; GHS RespSens1: H SkinIrrit2: H EyeIrrit2: H3 STOT SE3: H	334 315 19	
2,6-di-tert-butyl-p-cresol	<0,25%	128-37-0	-	204-881-4	GHS09 AquaticAcute AquaticChro	1: H400 nic1: H410	

Full text of R-Phrases and H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed

APPR AUTO-PLAST PRODUKT	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878				
	Date of issue: 2022-06-20	APP Harter AcrylFiller Multi 5:1	Page 4 z 7		

May cause allergy or asthma symptoms of breathing difficulties if inhaled

May cause an allergic skin reaction

Contains isocyanates. May produce an allergic reaction.

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe



SAFETY DATA SHEET

According Commission Regulation (EU) 2020/878

Date of issue: 2022-06-20

APP Harter AcrylFiller Multi 5:1

handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls
Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.
Eye protection:
Wear face visor or goggles in circumstances where eye contact can accidentally occur.
Protection for skin/hands:
Nitrile gloves.
Respiratory protection:
Respiratory protection.
Thermal Hazards:
None
Environmental exposure controls:
None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, colorless Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range:77,1°C Upper/lower flammability or explosive limits: 1,2-10,8% (v/v) Vapour density: N.D. Flash point: 30°C Evaporation rate: N.A. Vapour pressure: 10,8 mm Hg Density: 1.03kg/m³ (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity: 8,3 mm^{2/s} Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity Mixture is not reactive. 10.2. Chemical stability Stable under normal conditions of handling and storage. 10.3. Possibility of hazardous reactions None. 10.4. Conditions to avoid solar radiation sparks flame heat 10.5. Incompatible materials



SAFETY DATA SHEET According Commission Regulation (EU) 2020/878

Date of issue: 2022-06-20

APP Harter AcrylFiller Multi 5:1

- strong acids

oxides and reductors
 10.6. Hazardous decomposition products

None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

a) acute toxicity: no hazard

b) skin corrosion/irritation: skin irritation.

c) serious eye damage/irritation: no hazard

d) respiratory or skin sensitization: May cause allergy or asthma symptoms of breathing difficulties if inhaled

May cause respiratory irritation

e) germ cell mutagenicity: no hazard

f) carcinogenicity: no hazard

g) reproductive toxicity: no hazard

h) STOT-single exposure: May cause respiratory irritation

May cause drowsiness or dizziness

i) STOT-repeated exposure: no hazard

j) aspiration hazard: no harmful

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

- no data

11.2.2. Other information

- no data

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects
12.2. Persistence and degradability
No data.
12.3. Bioaccumulative potential
No data.
12.4. Mobility in soil
No data
12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
12.6. Endocrine disrupting properties
None
12.7. Other adverse effects
None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number
1263
14.2. UN proper shipping name
Paint
14.3. Transport hazard class(es)
3
14.4. Packing Group
III
14.5. Environmental hazards
No
14.6. Special Precautions for User
During handling wear personal protection equipment (see Section 8)
Avoid heat and flame.



SAFETY DATA SHEET

According Commission Regulation (EU) 2020/878

Date of issue: 2022-06-20

APP Harter AcrylFiller Multi 5:1

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

N.A.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H226 Flammable liquid and vapour
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H331 Toxic if inhaled
- H332 Harmful if inhaled
- H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H411 Toxic to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.