

	SATEFY DATA SHEET According Commission Regulation (EU) 2020/878	
	Date of issue: 2025-06-25	APP AcrylFiller HQ Fast 4:1 grey

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: APP AcrylFiller HQ Fast 4:1 grey

Trade code: 020551, 020554

1.2. Relevant identified uses of the substance/mixture and uses advised against

Two-component acrylic filler

1.3. Details of the supplier of the safety data sheet

Company: APP Sp. z o. o.
ul. Przemysłowa 10, 62 – 300 Września
Tel. +48 (061) 437 00 00
Fax. +48 (061) 437 91 37
Mail: app@app.com.pl
Strona WEB: www.app.com.pl

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. Emergency telephone number:

+48 (61) 437 00 00

Date of issue: 2025-06-25

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02



GHS07

Warning

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness

H412 Harmful to aquatic life with long lasting effects

2.2. Label elements

Labelling according Regulation (EC) No 1272/2008

Contains:

Butyl acetate

2-methoxy-1-methylethyl acetate

Butan-2-one

Signal word:

Warning

Pictogram:



GHS02

Hazard statement(s)

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Dibutyltin dilaurate. May produce an allergic reaction

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

H412 Harmful to aquatic life with long lasting effects

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P370 + P378 In case of fire: use ABC powder extinguisher to extinguish.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+ P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to an authorised waste collection point.

2.3 Other hazards

No information on fulfilling the PBT or vPvB criteria in accordance with Annex XIII of Regulation 1907/2006 (REACH). No studies have been conducted.

The product does not contain ingredients included in the list established in accordance with Article 59 paragraph 1 as having endocrine disrupting properties or ingredients with endocrine disrupting properties in accordance with the criteria set out in Regulation 2017/2100/EU or Regulation 2018/605/EU in a concentration equal to or greater than 0.1%.

VOC (2004/42/EC, IIc: 540) <530 g/l

UN: 1263

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS
3.1. Substances

N.A.

3.2. Mixtures
Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
Butyl acetate REACH: 01-2119485493-29	10-25%	123-86-4	607-025-00-1	204-658-1	GHS02; GHS04 Flam.Liq.3: H226 STOT SE3: H336 EUH066
Xylene REACH: 01-2119488216-32	2,5-5%	1330-20-7	601-022-00-9	215-525-7	GHS02; GHS07 ; GHS08 Flam. Liq.3: H226 AspTox1: H304 STOT RE2: H373 AcuteTox4: H302 Acute Tox.4: H332 SkinIrrit2: H315 EyeIrrit2: H319
2-methoxy-1-methylethyl acetate REACH: 01-2119475791-29	1-<2,5%	108-65-6	607-195-00-7	203-603-9	GHS02; GHS07 FlamLiq3: H226 STOTSE3: H336
Ethylbenzene REACH: 01-2119489370-35	1-<2,5%	100-41-4	601-023-00-4	202-849-4	GHS02; GHS07 ; GHS08 Flam. Liq.2: H225 AspTox1: H304 STOT RE2: H373 Acute Tox.4: H332 SkinIrrit2: H315 EyeIrrit2: H319 STOT SE3: H335
Butan-2-one REACH 01-2119457290-43	<2,5%	78-93-3	606-002-00-3	201-159-0	GHS02; GHS07 FlamLiq2: H225 EyeIrrit2: H319 STOT SE3: H336 EUH066
Acetic acid REACH: 01-2119475328-30	<1%	64-19-7	607-002-00-6	200-580-7	GHS02; GHS05; FlamLiq3: H226 SkinCorr1A: H314 Specific concentration limits: Skin Corr. 1A; H314: C ≥90 % Skin Corr. 1B; H314: 25

		SATEFY DATA SHEET According Commission Regulation (EU) 2020/878			
		Date of issue: 2025-06-25	APP AcrylFiller HQ Fast 4:1 grey		Page 3 z 7
					%≤ C <90 % Skin Irrit. 2; H315: 10 % ≤C <25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 %
Dibutyltin dilaurate REACH: 01-2119496068-27	0,25- <0,3%	77-58-7	-	201-039-8	GHS05; GHS07; GHS08; GHS09 SkinCorr1C: H314 SkinSens1: H317 STOT SE3: H335 Muta2: H341 Rep1B: H360FD STOTSE1: H371 AquaticChronic1: H 410 AcuaticAcute1: H400

Full text of H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems , consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed:

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking.

Contains Dibutyltin dilaurate. May produce an allergic re action

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel wearing approved air supplied breathing apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

	SATEFY DATA SHEET According Commission Regulation (EU) 2020/878		
	Date of issue: 2025-06-25	APP AcrylFiller HQ Fast 4:1 grey	Page 4 z 7

Wear personal protection equipment.
 Wear breathing apparatus if exposed to vapours/dusts/aerosols.
 Provide adequate ventilation.
 Use appropriate respiratory protection.
 See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

a) Eye or face protection: in case of frequent exposure, goggles or glasses that fit well to the face (in accordance with EN 166:2002, EN 167:2002, EN 168:2002, EN ISO 4007:2018)

b) Skin protection: protective (working) clothes, protective gloves (in accordance with the standards: EN ISO 374-1:2016+A1:2018, EN 16523-1:2015+A1:2018, EN ISO 21420:2020)

c) Respiratory protection: efficient ventilation; in the case of frequent exposure, a mask with a multi-gas absorber; Mask conforming to EN 405:2002+A1:2010 (Replace when taste or odor occurs impurities inside the face mask. if contamination comes with warnings it is recommended to use isolation equipment.)

Respiratory protection.

Thermal Hazards:

None

Environmental exposure controls:

None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

**SATEFY DATA SHEET**

According Commission Regulation (EU) 2020/878

Date of issue: 2025-06-25

APP AcrylFiller HQ Fast 4:1 grey

Page 5 z 7

Appearance and colour: liquid, grey
Odour: characteristic
Odour threshold: N.D.
pH: N.A.
Melting point / freezing point: N.D.
Initial boiling point and boiling range: 80-1355C
Upper/lower flammability or explosive limits: N.D.
Vapour density: N.D.
Flash point: 24°C
Evaporation rate: N.A.
Vapour pressure: N.D.
Density: 1420 kg/m³ (15°C)
Solubility in water: insoluble
Solubility in organic solvents: soluble in aromatic solvents
Lipid solubility: N.A.
Partition coefficient (n-octanol/water): N.A.
Ignition temperature: N.D.
Auto-ignition temperature: 315°C
Decomposition temperature: N.A.
Viscosity dyn.: N.D.
Viscosity kin.: >20.5 mm²/s
Explosive properties: can form an explosive mixture in air
Oxidizing properties: not oxidizing

9.2. Other information

VOC: <530 g/l

SECTION 10. STABILITY AND REACTIVITY**10.1. Reactivity**

Mixture is not reactive.

10.2. Chemical stability

Stable under normal conditions of handling and storage.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

- solar radiation
- sparks
- flame
- heat

10.5. Incompatible materials

- strong acids
- strong bases

10.6. Hazardous decomposition products

None.

SECTION 11. TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

- a) **acute toxicity:** no hazard
- b) **skin corrosion/irritation:** no hazard
- c) **serious eye damage/irritation:** no hazard
- d) **respiratory or skin sensitization:** Contains Dibutyltin dilaurate. May produce an allergic reaction
- e) **germ cell mutagenicity:** no hazard
- f) **carcinogenicity:** no hazard
- g) **reproductive toxicity:** no hazard
- h) **STOT-single exposure:** May cause drowsiness or dizziness
- i) **STOT-repeated exposure:** no hazard
- j) **aspiration hazard:** no hazard

11.2. Information on other hazards**11.2.1. Endocrine disrupting properties**

- no data

11.2.2. Other information

Repeated exposure may cause skin dryness or cracking.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

	SATEFY DATA SHEET According Commission Regulation (EU) 2020/878		
	Date of issue: 2025-06-25	APP AcrylFiller HQ Fast 4:1 grey	Page 6 z 7

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects

12.2. Persistence and degradability

No data.

12.3. Bioaccumulative potential

No data.

12.4. Mobility in soil

No data

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

1263

14.2. UN proper shipping name

Paint

14.3. Transport hazard class(es)

3

14.4. Packing Group

III

14.5. Environmental hazards

No

14.6. Special Precautions for User

During handling wear personal protection equipment (see Section 8)

Avoid heat and flame.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

N.A.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

H312 Harmful in contact with skin

H314 Causes severe skin burns and eye damage

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H318 Causes serious eye damage

	SATEFY DATA SHEET According Commission Regulation (EU) 2020/878		
	Date of issue: 2025-06-25	APP AcrylFiller HQ Fast 4:1 grey	Page 7 z 7

H319 Causes serious eye irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H360FD May damage fertility. May damage the unborn child

H371 May cause damage to organs (or state all organs affected, if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H373 May cause damage to organs through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

H411 Toxic to aquatic life with long lasting effects

H412 Harmful to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.