SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier
Trade name: **APP Grund EP Spray**
Trade code: **021205, 021206**

1.2. Relevant identified uses of the substance/mixture and uses advised against
Epoxy primer spray 500 ml

1.3. Details of the supplier of the safety data sheet
Company: **APP Sp. z o. o.**
ul. Przemysłowa 10, 62 – 300 Września
Tel. +48 (061) 437 00 00
Fax. +48 (061) 437 91 37
Mail: app@app.com.pl
Strona WEB: www.app.com.pl

Safety Data Sheet e-mail: **dzp@app.com.pl**

1.4. Emergency telephone number:
+48 (61) 437 00 00

Date of update: 2023-08-23

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008



GHS02



GHS07

Dgr
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness
H412 Harmful to aquatic life with long lasting effects
EUH066 Repeated exposure may cause skin dryness or cracking.

2.2. Label elements
Labelling according Regulation (EC) No 1272/2008
Contains:
Acetone
Propan-2-ol
Signal word:
Danger
Pictogram:



GHS02



GHS07

Hazard statement(s)

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness
H412 Harmful to aquatic life with long lasting effects
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
P260 Do not breathe spray.
P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container according to local/regional/national/international regulations.P501

2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006
UN: 1950
LZO (2004/42/EC, IIc: 780) 683.4 g/l

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances
N.A.
3.2. Mixtures
Hazardous components within the meaning of CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
Dimethyl ether REACH Reg No: 01-2119472128-37	40-50%	115-10-6	603-019-00-8	204-065-8	**GHS02; GHS04 Dgr** **FlamGas1: H220** **PressGas: H280**
Acetone REACH Reg. No: 01-2119471330-49	30-40%	67-64-1	606-001-00-8	200-662-2	**GHS02; GHS07** **Dgr** **Flam. Liq. 2: H225** **Eye Irrit. 2: H319 STOT** **SE 3: H336 EUH066**

Xylene REACH Reg. No 01-2119488216-32	5-10%	1330-20-7	601-022-00-9	215-525-7	**GHS02; GHS07** **Wng** **FlamLiq.3: H226** **AcuteTox.4: H312** **AcuteTox.4: H332** **SkinIrrit.2: H315** **EyeIrrit2: H319** **AspTox1: H304** **STOT RE2: H373**
Propan-2-ol; REACH Reg. No 01-2119457558-25	5-10%	67-63-0	603-117-00-0	200-661-7	**GHS02;GHS07** **Dgr** **FlamLiq2: H225** **EyeIrrit2: H319** **STOT SE3: H336**
2-methylpropan-1-ol; isobutanol REACH Reg. No 01-2119484609-23	1-3%	78-83-1	603-108-00-1	201-148-0	**GHS02; GHS05; GHS07** **Dgr** **Flam. Liq. 3: H226** **STOT SE 3: H335** **Skin Irrit. 2: H315** **Eye Dam. 1: H318** **STOT SE 3: H336**
Titanium dioxide (particles with an aerodynamic diameter ≤ 10 µm) REACH: 01-2119489379-17	1-3 %	13463-67-7	-	236-675-7	**GHS08** **Carc2: H351**
Zinc Oxide	<1 %	1314-13,2	030-013-00-7	215-222-5	**GHS09 Wng** **AquaticChronic1: H410** **AquaticAcute: H400**
phosphoric acid REACH: 01-2119485924-24	<1%	7664-38-2	015-011-00-6	231-633-2	**GHS05** **Skin Corr.1B: H314**
Ethylobenzene REACH: 01-2119489370-35	<1%	100-41-4	601-023-00-4	202-849-4	**GHS02; GHS07 ; GHS08** **Flam. Liq.2: H225** **AspTox1: H304** **STOT RE2: H373** **Acute Tox.4: H332** **SkinIrrit2: H315** **EyeIrrit2: H319** **STOT SE3: H335**
C9 hydrocarbons, aromatic REACH: 01-2119489370-	<0,1 %	128601-23-0	-	918-668-5	**GHS02; GHS07; GHS08;** **Flam.Liq.3: H226** **Asp.Tox1: H304** **STOT SE3: H335; H336** **EUH066** **AquaticChronic2: H411**

35					
Phenol REACH: 01-2119471329-32	<0,1 %	108-95-2	604-001-00-2	203-632-7	**GHS05 ; GHS06; GHS08** **Dgr** **Muta2: H341** **AcuteTox3: H301** **AcuteTox3: H311** **AcuteTox3: H331** **SkinCorr1B: H314** **Limit concentrations:** **Skin Corr. 1B;** **H314: C ≥ 3 %** **Skin Irrit. 2; H315** **1 % ≤ C<3 %** **Eye Irrit. 2;** **H319:1 % ≤C<3 %**

Full text of H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems , consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be

done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile : ≥0.45 mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

Thermal Hazards:

None
Environmental exposure controls:
None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties
Appearance and colour: liquid, grey
Odour: characteristic
Odour threshold: N.D.
pH: N.A.
Melting point / freezing point: N.D.
Initial boiling point and boiling range: <0°C
Upper/lower flammability or explosive limits: 2,6-26,6% (v/v)
Vapour density: N.D.
Flash point: <0ºC
Evaporation rate: N.A.
Vapour pressure: 4000hPa (20ºC)
Density: 851kg/m^3 (15ºC)
Solubility in water: insoluble
Solubility in organic solvents: soluble in aromatic solvents
Lipid solubility: N.A.
Partition coefficient (n-octanol/water): N.A.
Ignition temperature: N.D.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Viscosity dyn.: N.D.
Viscosity kin.: N.D.
Explosive properties: can form an explisive mixture in air
Oxidizing properties: not oxidizing
9.2. Other information
VOC: 683.4 g/l

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity
Mixture is not reactive.
10.2. Chemical stability
Stable under normal conditions of handling and storage.
10.3. Possibility of hazardous reactions
None.
10.4. Conditions to avoid
- solar radiation
- sparks
- flame
- heat

10.5. Incompatible materials
- strong oxidisers
- strong acids

10.6. Hazardous decomposition products
None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects
Toxicological information of components:
a) acute toxicity: no hazard
b) skin corrosion/irritation: no hazard
c) serious eye damage/irritation: Causes serious eye irritation
d) respiratory or skin sensitization: No hazard
e) germ cell mutagenicity: no hazard
f) carcinogenicity: no hazard
g) reproductive toxicity: no hazard
h) STOT-single exposure: may cause drowsiness or dizziness.
i) STOT-repeated exposure: no hazard

j) aspiration hazard: no hazard
11.2.1. Endocrine disrupting properties
- no data
11.2.2. Other information
- no data

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity
Harmful to aquatic life with long lasting effects
12.2. Persistence and degradability
Expected to be biodegradable.
12.3. Bioaccumulative potential
No data.
12.4. Mobility in soil
No data
12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
12.6. Endocrine disrupting properties
None
12.7. Other adverse effects
None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods
Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number or ID number:
1950
14.2. UN proper shipping name
Aerosols, flammable
14.3. Transport hazard class(es)
3
14.4. Packing Group
No
14.5. Environmental hazards
No
14.6. Special Precautions for User
During handling wear personal protection equipment (see Section 8)
Avoid heat and flame.
14.7. Sea transport in bulk in accordance with IMO instruments:
N.A.
Label: 2.1

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.
Where applicable, refer to the following regulatory provisions :
Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.
Regulation (EC) nr 648/2004 (detergents).
1999/13/EC (VOC directive)
15.2. Chemical Safety Assessment
No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H318	Causes serious eye damage
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.
It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.