

Date of issue: 2022-06-25

According Commission Regulation (EU) 2020/878
APP Modular Industrial Line Thinner

Alkyd 30-820 Standard

Page 1 z 7

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: APP Modular Industrial Line Thinner Alkyd 30-820 Standard Trade code: 0278825, 0278826

1.2. Relevant identified uses of the substance/mixture and uses advised against

Thinner.

Uses advised against: Other

1.3. <u>Details of the supplier of the safety data sheet</u> Company: APP Sp. z o. o.

APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: <u>www.app.com.pl</u>

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. <u>Emergency telephone number:</u> +48 (61) 437 00 00

Date of issue: 2022-06-25

SECTION 2. HAZARDS IDENTIFICATION 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 **GHS07** GHS08 Danger H226 Flammable liquid and vapour H304 May be fatal if swallowed and enters airways H312 Harmful in contact with skin H332 Harmful if inhaled H315 Causes skin irritation H319 Causes serious eye irritation H335 May cause respiratory irritation H373 May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure 2.2. Label elements Labelling according Regulation (EC) No 1272/2008 Contains: Reaction mass of ethylbenzene and m-xylene and p-xylene Signal word: Danger **Pictogram:** GHS02 **GHS07** GHS08

Hazard statement(s)

APPF® auto-plast produkt		SATEFY DATA SHEET According Commission Regulation (EU) 2020/878				
		Date of issue: 2022-06-25	APP Modular Industrial Line Thinner Alkyd 30-820 Standard	Page 2 z 7		
H226		quid and vapour				
H304	May be fatal	if swallowed and enters airways				
H312	Harmful in c	contact with skin				
H332	Harmful if in	haled				
H315	Causes skin i	es skin irritation				
H319		erious eye irritation				
H335	•	e respiratory irritation				
H373	May cause da	cause damage to organs through prolonged or repeated exposure through prolonged or repeated				
	exposure					
Precauti	onary statemer	nt(s)				
P210	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.					
P241		sion-proof electrical/ventilating/lighting//equipment.				
P260	Do not breath	athe dust/fume/gas/mist/vapours/spray.				
P280	P280 Wear protective gloves/protective clothing/eye protection/face protection.					
P301+P3		VED: Immediately call a PO	ISON CENTER/doctor			
P331	P331 Do NOT induce vomiting.					
P243						
P303+ P3	361+ P353 IF C water/shower		off immediately all contaminated clothing. R	inse skin with		
2 3 Otha	r hazards					
			XIII 1007/2006			
UN: 1993		PBT and vPvB according	g to annex AIII 1907/2006			

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
m-xylene	<20%	108-38-3	601-022-00-9	203-576-3	GHS02; HS07;
REACH REG NO					Flam. Liq.3: H226
* see below table					Acute Tox.4: H332
					Acute Tox.4: H312
					Skin Irrit.2: H315
p-xylene	<10%	106-42-3	601-022-00-9	203-396-5	GHS02; HS07;
REACH REG NO					Flam. Liq.3: H226
* see below table					Acute Tox.4: H332
					Acute Tox.4: H312
					Skin Irrit.2: H315
ethylbenzene	<8%	100-41-4	601-023-00-4	202-849-4	GHS02; GHS07
REACH REG NO					Flam. Liq.2: H225
* see below table					Acute Tox.4: H332
					STOT RE2: H373
					Asp.Tox.1: H304
o-xylene	<5%	95-47-6	601-022-00-9	202-422-2	
REACH REG NO					
* see below table					GHS02; HS07;
					Flam. Liq.3: H226
					Acute Tox.4: H332
					Acute Tox.4: H312
					Skin Irrit.2: H315

* Reg. No. REACH for the reaction mixture: m-xylene, p-xylene, o-xylene, ethylbenzene: 01-2119555267-33

Full text of R-Phrases and H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty

	SATEFY DATA SHEET According Commission Regulation (EU) 2020/878			
AUTO-PLAST PRODUKT	Date of issue: 2022-06-25	APP Modular Industrial Line Thinner Alkyd 30-820 Standard	Page 3 z 7	

of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious

person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed:

May be fatal if swallowed and enters airways

Harmful in contact with skin

Harmful if inhaled

May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture:

Flammable liquid. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate

regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.



According Commission Regulation (EU) 2020/878

APP Modular Industrial Line Thinner

Alkyd 30-820 Standard

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Date of issue: 2022-06-25

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile : ≥ 0.45 mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

Thermal Hazards: None

Environmental exposure controls: None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, colourless Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range: >129°C Upper/lower flammability or explosive limits: 2.2-11.7% Vapour density: N.D. Flash point: 24-26°C Evaporation rate: N.A. Vapour pressure: N.D. Density:870kg/m³ (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: 550°C Decomposition temperature: N.A. Viscosity dyn.: N.D.



According Commission Regulation (EU) 2020/878

APP Modular Industrial Line Thinner Page 5 z 7 Alkyd 30-820 Standard

Viscosity kin.: N.D. Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information

Date of issue: 2022-06-25

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity Mixture is not reactive. 10.2. Chemical stability Stable under normal conditions of handling and storage. 10.3. Possibility of hazardous reactions None. 10.4. Conditions to avoid - solar radiation - sparks - flame - heat **10.5.** Incompatible materials - strong oxidisers - strong acids 10.6. Hazardous decomposition products

None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects a) acute toxicity: Harmful in contact with skin; Harmful if inhaled b) skin corrosion/irritation: Causes skin irritation c) serious eye damage/irritation: Causes serious eye irritation d) respiratory or skin sensitization: no hazard e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard g) reproductive toxicity: no hazard h) STOT-single exposure: May cause respiratory irritation i) STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure j) aspiration hazard: May be fatal if swallowed and enters airways **Xylene:** LD50 (rat, ingestion): 4300 mg/kg LC50 (rat, inhalation): 22100 mg/m³/4h 11.2. Information on other hazards 11.2.1. Endocrine disrupting properties - no data 11.2.2. Other information - no data

SECTION 12. ECOLOGICAL INFORMATION

dus.	
Pimephales promelas LC50:	16,1 mg/dm ³ /96 h
Salmo gairdneri LC50:	8 mg/dm ³ /96 h
Lepomis macrochirus LC50:	$16,1 \text{ mg/dm}^3/96 \text{ h}$
Carassius auratus LC50:	16,1 mg/dm ³ /96 h
Daphnia magna EC50:	3,82 mg/dm ³ /48 h
	Salmo gairdneri LC50: Lepomis macrochirus LC50: Carassius auratus LC50:

12.2. Persistence and degradability

Expected to be biodegradable. High volatility and fast evaporation. Mixture is not soluble in water. Mixture undergoes photolysis in air.

12.3. Bioaccumulative potential No data.



According Commission Regulation (EU) 2020/878

DR (EU) 2020/8/8

Date of issue: 2022-06-25APP Modular Industrial Line Thinner
Alkyd 30-820 StandardPage 6 z 7

12.4. Mobility in soil No data
12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
12.6. Endocrine disrupting properties None
12.7. Other adverse effects None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

 14.1. UN number

 1993

 14.2. UN proper shipping name

 Flammable liquids, n.o.s.

 14.3. Transport hazard class(es)

 3

 14.4. Packing Group

 III

 14.5. Environmental hazards

 No

 14.6. Special Precautions for User

 During handling wear personal protection equipment (see Section 8)

 Avoid heat and flame.

 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

 N.A.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:			
H225	Highly flammable liquid and vapour		
H226	Flammable liquid and vapour		
H304	May be fatal if swallowed and enters airways		
H312	Harmful in contact with skin		
H332	Harmful if inhaled		
H315	Causes skin irritation		
H319	Causes serious eye irritation		
H335	May cause respiratory irritation		
H336	May cause drowsiness or dizziness		
H373	May cause damage to organs through prolonged or repeated exposure through prolonged or		
	repeated exposure (liver, kidneys, hearing organs).		

	SATEFY DATA SHEET According Commission Regulation (EU) 2020/878		
AUTO-PLAST PRODUKT	Date of issue: 2022-06-25	APP Modular Industrial Line Thinner Alkyd 30-820 Standard	Page 7 z 7

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.