#### SAFETY DATA SHEET According Commission Regulation (EU) 2020/878



Date of issue: 2024-05-26

APP U210 2w1

Page 1 z 6

# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: APP U210 2w1 grey Trade code: 050111

1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Car body surface treatments and sealing compound. Uses advised against: other

#### 1.3. Details of the supplier of the safety data sheet

APP Sp. z o. o.
ul. Przemysłowa 10, 62 – 300 Września
Tel. +48 (061) 437 00 00
Fax. +48 (061) 437 91 37
Mail: <u>app@app.com.pl</u>
Strona WEB: <u>www.app.com.pl</u>

Safety Data Sheet e-mail: dzp@app.com.pl

Date of issue: 2024-05-26

# SECTION 2. HAZARDS IDENTIFICATION

**2.1. Classification of the substance or mixture** Classification according to Regulation (EC) No 1272/2008



Dgr

H225 Highly flammable liquid and vapour

H315 Causes skin irritation

H336 May cause drowsiness or dizziness

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure H412 Harmful to aquatic life with long lasting effects

#### 2.2. Label elements



•

# GHS08

Hazard statement(s)

H225 Highly flammable liquid and vapour

GHS02

- H315 Causes skin irritation
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure

GHS07

- H336 May cause drowsiness or dizziness
- H412 Harmful to aquatic life with long lasting effects

SA	4FE	TYI	)A7	TA S	HEET	
	0		D		(TII) 0000/070	

APP U210 2w1



Date of issue: 2024-05-26

# According Commission Regulation (EU) 2020/878

Page 2 z 6

#### **Precautionary statement(s)**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/eye protection.

P303+ P361+ P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+ P378 In case of fire: Use CO2, extinguishing powder or sand to extinguish.

P405 Store locked up.

P501 Dispose of contents/container according to local/regional/national/international regulations.

#### 2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

VOC (2004/42/EC, IIe: 840) 536.1 g/l UN: 1139

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification

Name	Conc.	CAS No	Index No	EC No	Classification:
<b>Toluene</b> REACH: 01-21194713310-51	25-<50%	108-88-3	601-021-00-3	203-625-9	GHS02; GHS08; GHS07 Flam. Liq. 2: H225 Repr. 2: H361 Asp. Tox. 1: H304 STOT RE 2: H373 Skin Irrit. 2: H315 STOT SE 3: H336 AquaticChronic3: H412
<b>C9 hydrocarbons, aromatic</b> REACH: 01-2119455851-35	1-<3%	-	-	918-668-5	GHS02; GHS07; GHS08; Flam.Liq.3: H226 Asp.Tox1: H304 STOT SE3: H335; H336 EUH066 AquaticChronic2: H411

Full text of H-Phrases can be found under heading 16

#### SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

#### In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

#### In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious

person. Consult a doctor immediately and show him label or Safety Data Sheet.

#### In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878						
AUTO-PLAST PRODUKT	Date of issue: 2024-05-26	APP U210 2w1	Page 3 z 6				

respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

#### 4.2. Most important symptoms and effects, both acute and delayed

Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure through exposure.May cause drowsiness or dizziness

## 4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

#### SECTION 5. FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

#### 5.2. Special hazards arising from the substance or mixture

Highly flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

#### 5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

#### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

#### 6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

#### 6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

#### SECTION 7. HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878					
AUTO-PLAST PRODUKT	Date of issue: 2024-05-26	APP U210 2w1	Page 4 z 6			

product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

#### 7.3. Specific end use(s)

None.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

N.A.

#### 8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin. Eye protection: Wear face visor or goggles in circumstances where eye contact can accidentally occur. Protection for skin/hands: Nitrile gloves. Respiratory protection: Respiratory protection. Thermal Hazards: None Environmental exposure controls: None

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

Appearance and colour: liquid, grey Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range:111°C Upper/lower flammability or explosive limits: 1.2-7.1% Vapour density: N.D. Flash point: 4°C Evaporation rate: N.A. Vapour pressure: 35 hPa Density: 1230 kg/m<sup>3</sup> (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: 450 °C Decomposition temperature: N.A. Viscosity: 270000 cPs (20°C) Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC: 536.1 g/l

#### SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity
Mixture is not reactive.
10.2. Chemical stability
Stable under normal conditions of handling and storage.
10.3. Possibility of hazardous reactions
None.
10.4. Conditions to avoid
solar radiation
sparks
flame

- heat



#### SAFETY DATA SHEET According Commission Regulation (EU) 2020/878

Date of issue: 2024-05-26

APP U210 2w1

Page 5 z 6

**10.5. Incompatible materials** - none

**10.6. Hazardous decomposition products** 

None.

#### SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

a) acute toxicity: no hazard

b) skin corrosion/irritation: Causes skin irritation

c) serious eye damage/irritation: no hazard

d) respiratory or skin sensitization: no hazard

e) germ cell mutagenicity: no hazard

f) carcinogenicity: no hazard

g) reproductive toxicity: Suspected of damaging the unborn child.

h) STOT-single exposure: May cause drowsiness or dizziness

i) STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure through prolonged or repeated exposure

j) aspiration hazard: no hazard

**11.2.1. Endocrine disrupting properties** 

- no data

11.2.2. Other information

- no data

Toluene: LD50 (rat, ingestion): 5580 mg/kg LD50 (rabbit, skin): 12124 mg/kg

LC50 (rat, inhalation): 28100 mg/m3/4h

# SECTION 12. ECOLOGICAL INFORMATION

# 12.1. Toxicity

Harmful to aquatic life with long lasting effects **Toluene:** - fish LC50: 5.5 mg/dm<sup>3</sup>/96h - crustacea EC50: 3.8 mg/dm<sup>3</sup>/96h - algae EC50: 134 mg/dm<sup>3</sup>/96h 12.2. Persistence and degradability No data. 12.3. Bioaccumulative potential No data. 12.4. Mobility in soil No data 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None 12.6. Endocrine disrupting properties None 12.7. Other adverse effects None

#### SECTION 13. DISPOSAL CONSIDERATIONS

## 13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

14.1. UN number

#### 1139 14.2. UN proper shipping name

Coating solution (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining)

#### 14.3. Transport hazard class(es)

3

14.4. Packing Group



SAFETY DATA SHEET According Commission Regulation (EU) 2020/878

APP U210 2w1

II

#### 14.5. Environmental hazards

No 14.6. Special Precautions for User

During handling wear personal protection equipment (see Section 8)

Avoid heat and flame.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Date of issue: 2024-05-26

N.A.

Label: 3

#### SECTION 15. REGULATORY INFORMATION

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive)

**15.2. Chemical Safety Assessment** No

#### **SECTION 16. OTHER INFORMATION**

Full text of phrases referred to in Section 3:

H226 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H315 - Causes skin irritation

H304 - May be fatal if swallowed and enters airways

H314- Causes severe skin burns and eye damage

H315 - Causes skin irritation

H336- May cause drowsiness or dizziness

H361- Suspected of damaging fertility or the unborn child (state route of exposure if it is conclusively

proven that no other routes of exposure cause the hazard)

H373- May cause damage to organs through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H362- May cause harm to breast-fed children

H400- Very toxic to aquatic life

H410- Very toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.