

**SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING****1.1. Product Identifier**Trade name: **W100 WAX anthracite**Trade code: **050501****1.2. Relevant identified uses of the substance/mixture and uses advised against**  
**Wax covering mass.****1.3. Details of the supplier of the safety data sheet**

Company: APP Sp. z o. o.  
ul. Przemysłowa 10, 62 – 300 Września  
Tel. +48 (061) 437 00 00  
Fax. +48 (061) 437 91 37  
Mail: [app@app.com.pl](mailto:app@app.com.pl)  
Strona WEB: [www.app.com.pl](http://www.app.com.pl)

Safety Data Sheet e-mail: **Tomasz Gołda, t.golda@app.com.pl****1.4. Emergency telephone number:****+48 (61) 437 00 00****Date of issue:** 2015-08-19**SECTION 2. HAZARDS IDENTIFICATION****2.1. Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008

**GHS02****GHS07****GHS08****GHS09**

Dgr

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H336 May cause drowsiness or dizziness

H411 Toxic to aquatic life with long lasting effects

Mixture is not classified as corrosive because of the form (dry granulate silica).

Classification according to EU Directives 67/548/EEC or 1999/45/EC



**F+ Extremely flammable**



**Xi Irritant**



**N Dangerous for the environment.**

R12 Produkt skrajnie łatwopalny

R38 Irritating to skin

R67 Vapours may cause drowsiness and dizziness

R12/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

## 2.2. Label elements

### Labelling according Regulation (EC) No 1272/2008

Contains:

Naphtha (petroleum),hydrotreated light

Naphtha (petroleum),hydrodesulfurized heavy

### Signal word:

Danger

### Pictogram:



**GHS02**



**GHS07**



**GHS08**



**GHS09**

### Hazard statement(s)

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H336 May cause drowsiness or dizziness

H411 Toxic to aquatic life with long lasting effects

### Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+ P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P332+ P313 If skin irritation occurs: Get medical advice/attention.

P302+ P352 IF ON SKIN: Wash with plenty of water.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container according to local/regional/national/international regulations.

### 2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

UN: 1950

VOC (2004/42/EC, IIe: 840) 499 g/l

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS


### 3.1. Substances

N.A.

### 3.2. Mixtures

**Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:**

| Nazwa niebezpiecznej substancji  | Zakres stężeń | Numer CAS  | Numer indeksowy | Numer WE                 | Symbole niebezpieczeństwa  |
|--|---------------|------------|-----------------|--------------------------|--|
| <b>Propane</b><br>REACH Reg. No<br>01-2119486944-21  | 25-50 %       | 74-98-6    | 601-003-00-5    | 200-827-9                | F+: R12  |
|  |               |            |                 |                          | GHS02; GHS04<br>Dgr<br>FlamGas1: H220<br>PressGas: H280  |
| <b>Naphtha (petroleum),hydrotreated light notes: H and P</b><br>REACG Reg No<br>01-2119475133-43 | 20-25 %       | 64742-49-0 | 649-328-00-1    | 920-750-0                | F: R11<br>Xn: R65<br>Xi: R38<br>N: R51/53<br>R67<br>Uwagi: H i P   |
|  |               |            |                 |                          | GHS02; GHS07;<br>GHS08; GHS09<br>Dgr<br>Flam.Liq.2: H225<br>Asp.Tox1: H304<br>SkinIrrit2: H315<br>AquaticChronic2:H411<br>STOT SE3: H336<br>Uwagi: H i P |
| <b>Naphtha (petroleum),hydrodesulfurized heavy</b><br>REACH Reg. No.:<br>01-2119458049-33        | 10-<br><15%   | 64742-82-1 | 649-330-00-2    | 265-185-4<br>(919-446-0) | R10<br>Xn: R65<br>R66; R67<br>N: R51/53  |
|  |               |            |                 |                          | GHS02; GHS08;<br>GHS09<br>Dgr<br>Flam.Liq.3: H226<br>Asp.Tox1: H304<br>STOT SE3: H336<br>AquaticChronic2:H411<br>EUH066                                  |

|  |         | SAFETY DATA SHEET         |                     |           |  | Page 4 z 8 |
|--|---------|---------------------------|---------------------|-----------|--|------------|
|  |         | Date of issue: 2015-08-19 | W100 WAX anthracite |           |  |            |
| Sulfonic acids sodium salts  | 1-<2,5% | 68608-26-4                | -                   | -         | Xi: R36  |            |
|  |         |                           |                     |           | Eye Irrit 2: H319  |            |
| 2-Butoxyethanol  | <1%     | 111-76-2                  | 603-014-00-0        | 203-905-0 | Xn: R20/21/22<br>Xi: R36/38  |            |
|  |         |                           |                     |           | GHS07<br>Wng<br>AcuteTox4: H302<br>AcuteTox4: H312<br>AcuteTox4: H332<br>SkinIrrit2: H315<br>EyeIrrit2: H319 |            |
| Ethanol<br>REACH Reg. No:<br>01-2119457610-43                                    | <0,3%   | 64-17-5                   | 603-002-00-5        | 200-578-6 | F: R11   |            |
|  |         |                           |                     |           | GHS02 Dgr<br>Flam.Liq.2: H225  |            |
| Carbon black   | <0,3%   | 1333-86-4                 | -                   | 215-609-9 | -  |            |
|  |         |                           |                     |           | -  |            |

Full text of R-Phrases and H-Phrases can be found under heading 16

## SECTION 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

#### In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

#### In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

#### In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems , consult a doctor immediately and show him label or Safety Data Sheet.

### 4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways. May cause drowsiness or dizziness

### 4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

#### Treatment:

None

## SECTION 5. FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

#### Extinguishing media which must not be used for safety reasons:

Water jet.

### 5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

### 5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel wearing approved air supplied breathing apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

### 6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

### 6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

## SECTION 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling.

Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

### 7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

### 7.3. Specific end use(s)

None.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

N.A.

### 8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile :  $\geq 0.45$  mm, 240 min. ). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

Thermal Hazards:

None

Environmental exposure controls:

None

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance and colour: liquid, aerosol, colour according to the label

Odour: characteristic, like acetone

Odour threshold: N.D.

pH: N.A.

Melting point / freezing point: -44°C

Initial boiling point and boiling range: N.D.

Upper/lower flammability or explosive limits: 0,6-10,9% (v/v)

Vapour density: N.D.

Flash point: -97°C

Evaporation rate: N.A.

Vapour pressure: N.D.

Density: 706 kg/m<sup>3</sup> (15°C)

Solubility in water: insoluble

Solubility in organic solvents: soluble in aromatic solvents

Lipid solubility: N.A.

Partition coefficient (n-octanol/water): N.A.

Ignition temperature: 200°C

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Viscosity dyn.: N.D.

Viscosity kin.: N.D.

Explosive properties: can form an explosive mixture in air

Oxidizing properties: not oxidizing

### 9.2. Other information

VOC: 499 g/l

## SECTION 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Mixture is not reactive.

### 10.2. Chemical stability

Stable under normal conditions of handling and storage.

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

- solar radiation
- sparks
- flame
- heat

### 10.5. Incompatible materials

- strong oxidisers
- strong acids

### 10.6. Hazardous decomposition products

None.

**SECTION 11. TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

May be fatal if swallowed and enters airways

Causes skin irritation

May cause drowsiness or dizziness

**a) acute toxicity:** no hazard

**b) skin corrosion/irritation:** Causes skin irritation

**c) serious eye damage/irritation:** no hazard

**d) respiratory or skin sensitization:** no hazard

**e) germ cell mutagenicity:** no hazard

**f) carcinogenicity:** no hazard

**g) reproductive toxicity:** no hazard

**h) STOT-single exposure:** may cause drowsiness or dizziness.

**i) STOT-repeated exposure:** no hazard

**j) aspiration hazard:** May be fatal if swallowed and enters airways

**Toxicological information of components:****Naphtha (petroleum),hydrodesulfurized heavy**

LD50 (rat, ingestion): >5000mg/kg

LD50 (rabbit, skin): 3160mg/kg

**Naphtha (petroleum),hydrotreated light**

LD50 (rat, ingestion): 5000mg/kg

LC50 (rat, inhalation): >23 mg/m<sup>3</sup>/ 4h

LD50 (rabbit, skin): 2800 mg/kg

**SECTION 12. ECOLOGICAL INFORMATION****12.1. Toxicity**

Toxic to aquatic life with long lasting effects

**Naphtha (petroleum),hydrodesulfurized heavy**

- fish LL50 (*Oncorhynchus mykiss*): 10-30 mg/l/96h
- crustacea EC50 (*Daphnia magna*): 10-22 mg/l/48h
- algae EL50 (*Pseudokirchneriella subcapitata*): 4,6-10 mg/l/72 h
- crustacea LOEC (*Daphnia magna*): 0,203 mg/l/21d
- crustacea NOEC (*Daphnia magna*): 0,097 mg/l/21d
- algae NOERL (*Pseudokirchneriella subcapitata*): 1 mg/l/72h

**Naphtha (petroleum),hydrotreated light**

- fish LL50 (*Oncorhynchus mykiss*): >13,4 mg/l/96 h
- crustacea EC50 (*Daphnia magna*): 3 mg/l/48 h
- algae EL50 (*Pseudokirchneriella subcapitata*): 10-30 mg/l/72 h
- crustacea LOEC (*Daphnia magna*):0,32 mg/l/21d
- crustacea NOEC (*Daphnia magna*): 0,17 mg/l/21d
- algae (*Pseudokirchneriella subcapitata*): 10 mg/l/72h

**12.2. Persistence and degradability**

Expected to be biodegradable.

**12.3. Bioaccumulative potential**

No data.

**12.4. Mobility in soil**

No data

**12.5. Results of PBT and vPvB assessment**

vPvB Substances: None - PBT Substances: None

**12.6. Other adverse effects**

None

**SECTION 13. DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods**

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

**SECTION 14. TRANSPORT INFORMATION****14.1. UN number**



1950

**14.2. UN proper shipping name**

Aerosols, flammable

**14.3. Transport hazard class(es)**

3

**14.4. Packing Group**

No

**14.5. Environmental hazards**

No

**14.6. Special Precautions for User**

During handling wear personal protection equipment (see Section 8)

Avoid heat and flame.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

N.A.

Label: 2.1

**SECTION 15. REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

**Where applicable, refer to the following regulatory provisions :**

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

**15.2. Chemical Safety Assessment**

No

**SECTION 16. OTHER INFORMATION**Full text of phrases referred to in Section 3:

|        |  |
|--------|--|
| R10    | Flammable  |
| R11    | Highly flammable   |
| R12    | Extremely flammable  |
| R20    | Harmful by inhalation  |
| R36    | Irritating to eyes   |
| R43    | May cause sensitisation by skin contact  |
| R67    | Vapours may cause drowsiness and dizziness   |
| R52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment |
| R66    | Repeated exposure may cause skin dryness or cracking   |
| R67    | Vapours may cause drowsiness and dizziness   |
| H220   | Extremely flammable gas  |
| H222   | Extremely flammable aerosol  |
| H225   | Highly flammable liquid and vapour   |
| H226   | Flammable liquid and vapour  |
| H280   | Contains gas under pressure; may explode if heated   |
| H317   | May cause an allergic skin reaction  |
| H319   | Causes serious eye irritation  |
| H336   | May cause drowsiness or dizziness  |
| H412   | Harmful to aquatic life with long lasting effects  |
| EUH066 | Repeated exposure may cause skin dryness or cracking.  |

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.