

Page 1 z 7

According Commission Regulation (EU) 2020/878

Date of issue: 2024-02-28 APP W100 WAX

# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product Identifier

Trade name: APP W100 WAX Spray

Trade code: 050502

## 1.2. Relevant identified uses of the substance/mixture and uses advised against

Wax mass to protect the chassis uses advised against: other

## 1.3. Details of the supplier of the safety data sheet

Company: APP Sp. z o. o.

ul. Przemysłowa 10, 62 – 300 Września

Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: app@app.com.pl WEB: www.app.com.pl

Safety Data Sheet e-mail: dzp@app.com.pl

#### 1.4. Emergency telephone number:

+48 (61) 437 00 00

**Date of issue:** 2024-02-28

## **SECTION 2. HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008





GHS02

GHS07

Dgr

H225 Highly flammable liquid and vapour

H336 May cause drowsiness or dizziness

H319 Causes serious eye irritation

H412 Harmful to aquatic life with long lasting effects

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.2. Label elements

# Labelling according Regulation (EC) No 1272/2008

## **Contains:**

Hydrocarbons C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

C9 hydrocarbons, aromatic

C7 ÷ C9 hydrocarbons; n-alkanes, isoalkanes, cyclics

## Signal word:

Danger

## Pictogram:





GHS02

GHS07

## **Hazard statement(s)**

H225 Highly flammable liquid and vapour



According Commission Regulation (EU) 2020/878

Date of issue: 2024-02-28 APP W100 WAX Page 2 z 7

H319 Causes serious eye irritation H336 May cause drowsiness or dizziness

Harmful to aquatic life with long lasting effects H411 **EUH066** Repeated exposure may cause skin dryness or cracking.

## **Precautionary statement(s)**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection. P280

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+ P235 Store in a well-ventilated place. Keep cool.

Dispose of contents/container according to local/regional/national/international regulations. P501

## 2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

UN: 1139

VOC (2004/42/EC, He: 840) <406 g/l

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substances

N.A.

## 3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:		
Hydrocarbons C9-C11, n-	25-<50	64742-48-9	649-327-00-6	919-857-5	GHS02; GHS07; GHS08;		
alkanes, isoalkanes,	%				Flam.Liq.3: H226		
cycloalkenes, <2%					Asp.Tox1: H304		
aromatics REACH: 01-					STOT SE3: H336		
2119463258-33					EUH066		
2117 100230 00							
C9 hydrocarbons,	2,5-<10	128601-23-0	_	918-668-5	GHS02; GHS07; GHS08;		
aromatic REACH: 01-	%				Flam.Liq.3: H226		
2119455851-35					Asp.Tox1: H304		
2117433031-33					STOT SE3: H335; H336		
					EUH066		
					AquaticChronic2: H411		
C7 ÷ C9 hydrocarbons; n-	2,5-	-	-	920-750-0	GHS02; GHS08; GHS07;		
alkanes, isoalkanes,	<10%				GHS09		
cyclics REACH 01-					Flam. Liq. 2: H225		
2119473851-33-XXXX					Asp. Tox. 1: H304		
					STOT SE 3: H336		
					Aquatic Chronic 2: H411		
	2 1100/	(0(00.26.4		251 501 5	EUH066		
Sulfonic acids, petroleum,	3-<10%	68608-26-4	-	271-781-5	Eye Irrit 2: H319		
sodium salts REACH:							
01-2119527859-22							
2 between the salpe ACH.	<1%	111-76-2	603-014-00-0	203-905-0	GHS07		
2-butoxyethanol REACH:	<1%	111-/0-2	003-014-00-0	203-905-0	AcuteTox4: H302		
01-2119475108-36					AcuteTox4: H312		
					AcuteTox4: H332		
					SkinIrrit2: H315		
					Eyelrrit2: H319		
					ATE LD50 (oral) 1200		
					mg/kg		
Ethanol REACH: 01-	<1%	64-17-5	603-002-00-5	200-578-6	GHS02		
2119457610-43					Flam.Liq.2: H225		
211/10/010 10					EyeIrrit2: H319		
Carbon black REACH:	<1%	1333-86-4	607-025-00-1	215-609-9	-		
01-2119384822-32					_		
01 211/00 1022-02							
Calcium hydroxide	<2,5%	1305-62-0	-	215-137-3	GHS05; GHS07;		



According Commission Regulation (EU) 2020/878

Date of issue: 2024-02-28 APP W100 WAX

Page 3 z 7

REACH:			Skin Irrit.	2, H315;
01-2119475151-45			EyeDam1	l: H318
			STOT SE	3: H335

Full text of H-Phrases can be found under heading 16

#### **SECTION 4. FIRST AID MEASURES**

#### 4.1. Description of first aid measures

#### In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

#### In case of eves contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

#### In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

#### In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness

#### 4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

#### **Treatment:**

None

## **SECTION 5. FIRE-FIGHTING MEASURES**

#### 5.1. Extinguishing media

## Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

## Extinguishing media which must not be used for safety reasons:

Water jet.

## 5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

## 5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

## 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

## 6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until



According Commission Regulation (EU) 2020/878

Date of issue: 2024-02-28 APP W100 WAX

Page 4 z 7

the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

#### 6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

#### **SECTION 7. HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

#### 7.3. Specific end use(s)

None.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

N.A.

## 8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

#### Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile:  $\geq$ 0.45 mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

#### Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

Thermal Hazards:

None

Environmental exposure controls:

None

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance and colour: liquid, color according to the label

Odour: characteristic Odour threshold: N.D.

pH: N.A.

Melting point / freezing point: N.D.

Initial boiling point and boiling range: 165-181°C Upper/lower flammability or explosive limits: 0.6-7,5%

Vapour density: N.D. Flash point: 6°C Evaporation rate: N.A. Vapour pressure: 5 hPa Density: 833-870 kg/m³ (15°C)



According Commission Regulation (EU) 2020/878

Solubility in water: insoluble

Solubility in organic solvents: soluble in aromatic solvents

Lipid solubility: N.A.

Partition coefficient (n-octanol/water): N.A.

Ignition temperature: N.D. Auto-ignition temperature: 475°C Decomposition temperature: N.A. Viscosity dyn.: >20.5 mm²/s, 40°C

Viscosity kin.: N.D.

Explosive properties: can form an explisive mixture in air

Oxidizing properties: not oxidizing

9.2. Other information

VOC: <406

## **SECTION 10. STABILITY AND REACTIVITY**

## 10.1. Reactivity

Mixture is not reactive.

#### 10.2. Chemical stability

Stable under normal conditions of handling and storage.

## 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

- solar radiation
- sparks
- flame
- heat

## 10.5. Incompatible materials

- strong oxidisers
- strong acids

#### 10.6. Hazardous decomposition products

None

## SECTION 11. TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

a) acute toxicity: no hazard

b) skin corrosion/irritation: no hazard

c) serious eye damage/irritation: Causes serious eye irritation

d) respiratory or skin sensitization: no hazard

e) germ cell mutagenicity: no hazard

f) carcinogenicity: no hazard

g) reproductive toxicity: no hazard

h) STOT-single exposure: may cause drowsiness or dizziness

i) STOT-repeated exposure: no hazard

j) aspiration hazard: no hazard

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

- no data

## 11.2.2. Other information

Repeated exposure may cause skin dryness or cracking.

## **SECTION 12. ECOLOGICAL INFORMATION**

## 12.1. Toxicity

Harmful to aquatic life with long lasting effects

## 12.2. Persistence and degradability

No data.

## 12.3. Bioaccumulative potential

No data.

## 12.4. Mobility in soil

No data

#### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

## 12.6. Endocrine disrupting properties



According Commission Regulation (EU) 2020/878

None

#### 12.7. Other adverse effects

None

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

## **SECTION 14. TRANSPORT INFORMATION**

#### 14.1. UN number

1139

#### 14.2. UN proper shipping name

Coating solution (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining)

## 14.3. Transport hazard class(es)

2

## 14.4. Packing Group

III

#### 14.5. Environmental hazards

No

#### 14.6. Special Precautions for User

During handling wear personal protection equipment (see Section 8)

Avoid heat and flame.

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

N.A.

Label: 3

## **SECTION 15. REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

## Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

#### 15.2. Chemical Safety Assessment

No

#### **SECTION 16. OTHER INFORMATION**

Full text of phrases referred to in Section 3:			
H225	Highly flammable liquid and vapour		
H226	Flammable liquid and vapour		
H304	May be fatal if swallowed and enters airways		
H312	Działa szkodliwie w kontakcie ze skórą.		
H315	Działa drażniąco na skórę.		
H319	Działa drażniąco na oczy.		
H332	Działa szkodliwie w następstwie wdychania.		
H335	Może powodować podrażnienie dróg oddechowych.		
H336	Może wywoływać uczucie senności lub zawroty głowy.		
H411	Toxic to aquatic life with long lasting effects		
EUH066	Repeated exposure may cause skin dryness or cracking.		

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to



# SAFETY DATA SHEET According Commission Regulation (EU) 2020/878

Page 7 z 7

Date of issue: 2024-02-28 APP W100 WAX

the specific use intended.