

Date of update: 2025-03-20

APP B200 Autobit Spray

Page 1 z 7

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. <u>Product Identifier</u> Trade name: **APP B200 Autobit Spray** Trade code: **050603**

1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Bituminous preparation for underbody protection

1.3. Details of the supplier of the safety data sheet

Company: APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: <u>www.app.com.pl</u>

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. Emergency telephone number: +48 (61) 437 00 00

Date of update: 2025-03-20

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Dgr

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation

H411 Toxic to aquatic life with long lasting effects

H336 May cause drowsiness or dizziness

2.2. Label elements

Labelling according Regulation (EC) No 1272/2008 Contains:

Hydrocarbons C7 n-alkanes, isoalkanes, cyclics Hydrocarbons C7 ÷ C9; n-alkanes, isoalkanes, cyclic

Signal word:

Danger

Pictogram:



Hazard statement(s)

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H315 Causes skin irritation
- H411 Toxic to aquatic life with long lasting effects
- H336 May cause drowsiness or dizziness

Precautionary statement(s)

ADD		Acco	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878				
AUTO-PL	R AST PRODUKT	Date of update: 2025-03-20	APP B200 Autobit Spray	Page 2 z 7			
P102		of reach of children.					
P210			, open flames and other ignition sources. No	smoking.			
P211		ay on an open flame or other ign	nition source.				
P251		rce or burn, even after use.					
			nperatures exceeding 50 °C/122°F.				
P273		ase to the environment.					
P280		ective gloves/protective clothing					
		N: Wash with plenty of water/					
			and keep comfortable for breathing.				
P305 + P			h water for several minutes. Remove contact	t lenses, if prese			
D 405		o do. Continue rinsing.					
P405	Store lock			DECI			
P501		contents/container according to	local/regional/national/international regulation	ons.P501			
	r hazards	• / • • • • • • • • • • • •	· , ,••• ,•				
		ixtures possible without suffici	ient ventilation.				
UN: 1950	-	940 M 712 A					
	04/42/EC, IIe:		VIII of Download in the	007/2006			
			accordance with Annex XIII of Regulation 19	907/2006			
		we been conducted.					
			list established in accordance with Article 59 th endocrine disrupting properties in accordan				
			on 2018/605/EU in a concentration equal to or				
0.1%.							
SECTIO	N 3 COMPOS	SITION/INFORMATION ON	INCOEDIENTS				

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
Propane REACH: 01- 2119486944-21	10-25%	74-98-6	601-003-00-5	200-827-9	GHS02; GHS04 FlamGas1: H220 PressGas: H280
Izobutane REACH: 01- 2119485395-27	25-50%	75-28-5	601-004-00-0	200-857-2	GHS02; GHS04 FlamGas1: H220 PressGas: H280
Hydrocarbons C7; n- alkanes, isoalkanes, cyclic REACH 01- 2119475515-33-	10-25%	-	-	927-510-4	GHS02; GHS08; GHS07; GHS09 Flam. Liq. 2: H225 Asp. Tox. 1: H304 STOT SE 3: H336 SkinIrrit2: H315 Aquatic Chronic 2: H411
Hydrocarbons C7 ÷ C9; n-alkanes, isoalkanes, cyclic REACH 01-2119473851-33- XXXX	10-25%	-	-	920-750-0	GHS02; GHS08; GHS07; GHS09 Flam. Liq. 2: H225 Asp. Tox. 1: H304 STOT SE 3: H336 Aquatic Chronic 2: H411 EUH066

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878					
AUTO-PLAST PRODUKT	Date of update: 2025-03-20		APP	Spray	Page 3 z 7	
Hydrocarbons C9, aromatic REACH: 01- 2119455851-35	<2,5%	-	-	918-668-5	GHS02; GH GHS08 ; GH Flam. Liq. 3, Asp. Tox. 1: AquaticChro H411 SE 3; H335+ EUH066	S09 H226 H304 onic 2: STOT
propylene carbonate REACH: 01-2119537232- 48	<2,5%	108-32-7	607-194-00-1	203-572-1	GHS07 EyeIrrit2: H3	19
n-hexane	<1%	110-54-3	601-037-00-0	203-777-6	GHS02; GH GHS07 GHS09 Flam. Liq. 22 Repr. 2: H36 Asp. Tox. 1: STOT RE 2: Skin Irrit. 2: STOT SE 3: Aquatic Chr H411	: H225 11 H304 H373 H315 H336

Full text of H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious

person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed

. May cause drowsiness or dizziness

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878				
AUTO-PLAST PRODUKT	Date of update: 2025-03-20	APP B200 Autobit Spray	Page 4 z 7		

source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878			
BAUTO-PLAST PRODUKT	Date of update: 2025-03-20	APP B200 Autobit Spray	Page 5 z 7	

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile : ≥ 0.45 mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water. Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

<u>Thermal Hazards:</u> None <u>Environmental exposure controls:</u> None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, black Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range: N.D. Upper/lower flammability or explosive limits: N.D, Vapour density: N.D. Flash point: -42°C Evaporation rate: N.A. Vapour pressure: N.D. Density: N.D. Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: N.D. Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC: 512 g/l

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity Mixture is not reactive. 10.2. Chemical stability Stable under normal conditions of handling and storage. 10.3. Possibility of hazardous reactions None. 10.4. Conditions to avoid - solar radiation - sparks - flame - heat **10.5.** Incompatible materials - strong oxidisers - strong acids 10.6. Hazardous decomposition products None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects Toxicological information of components:

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878				
AUTO-PLAST PRODUKT	Date of update: 2025-03-20	APP B200 Autobit Spray	Page 6 z 7		
a) acute toxicity: no hazard					
b) skin corrosion/irritation: Causes skin irritation					
c) serious eye damage/irritation: no hazard					
d) respiratory or skin sensitization: no hazard					
e) germ cell mutagenicity: no hazard					

f) carcinogenicity: no hazard

g) reproductive toxicity: no hazard

h) STOT-single exposure: may cause drowsiness or dizziness.

i) STOT-repeated exposure: no hazard

j) aspiration hazard: no hazard

11.2.1. Endocrine disrupting properties

- no data

11.2.2. Other information

- no data

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Toxic to aquatic life with long lasting effects
12.2. Persistence and degradability
Expected to be biodegradable.
12.3. Bioaccumulative potential
No data.
12.4. Mobility in soil
No data
12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
12.6. Endocrine disrupting properties
None
12.7. Other adverse effects
None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number 1950 14.2. UN proper shipping name Aerosols, flammable 14.3. Transport hazard class(es) 3 14.4. Packing Group No 14.5. Environmental hazards Yes 14.6. Special Precautions for User During handling wear personal protection equipment (see Section 8) Avoid heat and flame. 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code N.A. Label: 2.1

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE)

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878			
AUTO-PLAST PRODUKT	Date of update: 2025-03-20	APP B200 Autobit Spray	Page 7 z 7	

n.790/2009. Where applicable, refer to the following regulatory provisions : Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive) 15.2. Chemical Safety Assessment No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:		
H220	Extremely flammable gas	
H222	Extremely flammable aerosol	
H225	Highly flammable liquid and vapour	
H226	Flammable liquid and vapour	
H280	Contains gas under pressure; may explode if heated	
H304	May be fatal if swallowed and enters airways	
H319	Causes serious eye irritation	
H336	May cause drowsiness or dizziness	
H411	Toxic to aquatic life with long lasting effects	
H412	Harmful to aquatic life with long lasting effects	
EUH066	Repeated exposure may cause skin dryness or cracking.	

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.