SAFETY DATA SHEET According Commission Regulation (EU) 2020/878



Date of issue: 2023-03-21

APP Rally Spray Color (silver)

Page 1 z 7

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

1.1. Product Identifier Trade name: APP Rally Spray Color (silver)

Trade code: 210104, 210114

1.2. Relevant identified uses of the substance/mixture and uses advised against Structure paint. uses advised against: other.

1.3. Details of the supplier of the safety data sheet

Company: APP Sp. z o. o. ul. Przemysłowa 10, 62 - 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: app@app.com.pl Strona WEB: www.app.com.pl

Safety Data Sheet e-mail: dzp@app.com.pl

Date of issue: 2023-03-21

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



H229 Pressurised container: May burst if heated.


H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

2.2. Label elements

Labelling according Regulation (EC) No 1272/2008

Contains: Acetone Butyl acetate 2-methoxy-1-methylethyl acetate Signal word: Danger **Pictogram:**



- Causes serious eye irritation H319
- H336 May cause drowsiness or dizziness
- EUH066 Repeated exposure may cause skin dryness or cracking.
- **Precautionary statement(s)**

		SAFETY DATA SHEET According Commission Regulation (EU) 2020/878					
		According Commission Regulation (EU) 2020/076					
AUTO-PLAST PRODUKT		Date of issue: 2023-03-21 APP Rally Spray Color (silver		Page 2 z 7			
P210	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.						
P211	Do not spray	o not spray on an open flame or other ignition source.					
P251	Do not pierce	not pierce or burn, even after use					
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.							
P260	P260 Do not breathe spray.						
P501	P501 Dispose of contents/container according to local/regional/national/international regulations.P501						
2.3 Other hazards							
Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006							
UN: 1950							
VOC (2004/42/FC He· 840) 688 6g/l							

VOC (2004/42/EC, IIe: 840) 688,6g/l

Formation of explosive mixtures is possible in the absence of sufficient ventilation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
Propane REACH Reg. No 01-2119486944-21	10-<12.5 %	74-98-6	601-003-00-5	200-827-9	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280
Butane REACH Reg. No 01-2119474691-32	5-<10 %	106-97-8	601-004-00-0	203-448-7	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280
Isobutane REACH Reg. No 01-2119485395-27	5-<10 %	75-28-5	601-004-00-0	200-857-2	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280
Acetone REACH Reg. No: 01-2119471330-49	25-<50%	67-64-1	606-001-00-8	200-662-2	GHS02; GHS07 Dgr Flam. Liq. 2: H225 Eye Irrit. 2: H319 STOT SE 3: H336 EUH066

A D D=	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878					
AUTO-PLAST PRODUKT	Date of issue: 2023-03-21		APP R	ally Spray Colo	or (silver)	Page 3 z 7
n-buthyl acetate REACH Reg. No 01-2119485493-29	10-<12.5 %	123-86-4	607-025-00-1	204-658-1	GHS02; GHS0 Wng Flam.Liq.3: H2 STOT SE3: H3 EUH066	226
2-methoxy-1-methylethyl acetate REACH Reg. No: 01-2119475791-29-XXXX	5-<10%	108-65-6	607-195-00-7	203-603-9	GHS02; GHS0 Wng FlamLiq3: H22 STOT SE3: H3	26
Nitrocellulose (less than 12.6 nitrogen)	<2,5%	9004-70-0	603-037-01-3	-	GHS08 Exp1: H201	
Aluminum, unstabilized powder REACH01-2119529243-45	<2,5%	7429-90-5	013-001-00-6	231-072-3	GHS02 Flam. Sol. 1: H Water-react. 2:	
Reaction mass of ethylbenzene and xylene REACH: 01-2119488216-32	<2,5%	-	-	905-588-0	GHS02; GHS0 FlamLiq3: H22 AcuteTox4: H3 AcuteTox4: H3 SkinIrrit2: H3 EyeIrrit2: H31 STOT SE3: H3 STOTRE3: H3 AspTox1: H304	26 512 532 15 9 535 73

Full text of R-Phrases and H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878			
AUTO-PLAST PRODUKT	Date of issue: 2023-03-21	APP Rally Spray Color (silver)	Page 4 z 7	

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878				
AUTO-PLAST PRODUKT	Date of issue: 2023-03-21	APP Rally Spray Color (silver)	Page 5 z 7		
	0 111 1 0		1		

equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile : ≥ 0.45 mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

<u>Thermal Hazards:</u> None Environmental exposure controls:

None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance and colour: liquid aerosol, color as indicated on the label Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range: N.D. Upper/lower flammability or explosive limits: 1.7-13.0% (v/v) Vapour density: N.D. Flash point: <0°C Evaporation rate: N.A. Vapour pressure: 3500 hPa (20°C) Density: 700 kg/m³ (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: 333°C Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: N.D. Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC: 688.6 g/l

SECTION 10. STABILITY AND REACTIVITY

10.1. ReactivityMixture is not reactive.10.2. Chemical stabilityStable under normal conditions of handling and storage.



APP Rally Spray Color (silver)

Page 6 z 7

10.3. Possibility of hazardous reactions None.
10.4. Conditions to avoid

solar radiation
sparks
flame
heat

10.5. Incompatible materials

strong oxidisers

 strong acids
 10.6. Hazardous decomposition products None.

SECTION 11. TOXICOLOGICAL INFORMATION

Date of issue: 2023-03-21

11.1. Information on toxicological effects a) acute toxicity: no hazard b) skin corrosion/irritation: no hazard c) serious eve damage/irritation: Causes serious eve irritation d) respiratory or skin sensitization: no hazard e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard g) reproductive toxicity: no hazard h) STOT-single exposure: may cause drowsiness or dizziness. i) STOT-repeated exposure: no hazard j) aspiration hazard: no hazard Repeated exposure may cause skin dryness or cracking. Acetone 5800 mg/kg LD50 (rat, skin): 20000 mg/kg LD50 (rabbit, skin): $39 \text{ mg/m}^{3}/4\text{h}$ LC50 (rat, inhalation): n-buthyl acetate 10770mg/kg LD50 (rat, skin): LD50 (rabbit, skin): >17600 mg/kg LC50 (rat, inhalation): $>21 \text{ mg/m}^{3}/4\text{h}$ 2-methoxy-1-methylethyl acetate LD50 (rat, skin): 85320mg/kg >2920 mg/kg LD50 (rabbit, skin): 35.7 mg/m³/4h LC50 (rat, inhalation): 11.2. Information on other hazards 11.2.1. Endocrine disrupting properties - no data 11.2.2. Other information - no data

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity
Mixture is not classified as hazarodus.

12.2. Persistence and degradability
Expected to be biodegradable.
12.3. Bioaccumulative potential

No data.
12.4. Mobility in soil

No data
12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

None

12.7. Other adverse effects

None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods



SAFETY DATA SHEET According Commission Regulation (EU) 2020/878

ing Commission Regulation (EU) 2020/8/8

Date of issue: 2023-03-21

APP Rally Spray Color (silver)

Page 7 z 7

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number 1950 14.2. UN proper shipping name Aerosols, flammable 14.3. Transport hazard class(es) 3 14.4. Packing Group No 14.5. Environmental hazards No 14.6. Special Precautions for User During handling wear personal protection equipment (see Section 8) Avoid heat and flame. 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code NA Label: 2.1

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:		
H228	Flammable solid	
H261	In contact with water releases flammable gas	
H351	Suspected of causing cancer	
H220	Extremely flammable gas	
H222	Extremely flammable aerosol	
H225	Highly flammable liquid and vapour	
H226	Flammable liquid and vapour	
H280	Contains gas under pressure; may explode if heated	
H315	Causes skin irritation	
H318	Causes serious eye damage	
H319	Causes serious eye irritation	
H332	Harmful if inhaled	
H336	May cause drowsiness or dizziness	
EUH066	Repeated exposure may cause skin dryness or cracking.	

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.