SAFETY DATA SHEET According Commission Regulation (EU) 2020/878



Date of issue: 2024.11.28

APP Rally 400 Color Spray (all colors)

Page 1 z 7

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. <u>Product Identifier</u> Trade name: APP Rally 400 Color Spray (all colors) Trade code: 210121, 210122, 210123, 210124, 210125, 210126 UFI: NUWR-TKMF-J002-DRC8

1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Acrylic clearcoat Uses advised against: other.

1.3. Details of the supplier of the safety data sheet

APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: <u>www.app.com.pl</u>

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. <u>Emergency telephone number:</u> +48 (61) 437 00 00

Date of issue: 2024-11-28

Company:

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Dgr H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation H336 May cause drowsiness or dizziness **2.2. Label elements Labelling according Regulation (EC) No 1272/2008** Contains: Acetone **Signal word:** Danger **Pictogram:**



Hazard statement(s)

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878				
AUTO-PLAST PRODUKT	Date of issue: 2024.11.28	APP Rally 400 Color Spray (all colors)	Page 2 z 7		
Precautionary statement	nt(s)				
P101 If medical advice is n	eeded, have product containe	er or label at hand.			
P102 Keep out of reach of	children.				
P210 Keep away from heat	, hot surfaces, sparks, open fl	ames and other ignition sources. No smoking.			
P211 Do not spray on an o	pen flame or other ignition so	ource.			
P251 Do not pierce or burn	n, even after use.				
P410 + P412 Protect from	sunlight. Do not expose to ter	nperatures exceeding 50 °C/122°F.			

- P412 Protect from sunlight. Do not expose to temperatures exceeding 50 ° P410

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container according to local/regional/national/international regulations.

2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

UN: 1950

VOC (2004/42/EC, IIe: 840) 659.17 g/l

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS


3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
Propane REACH: 01-	10-25%	74-98-6	601-003-00-5	200-827-9	GHS02; GHS04
2119486944					FlamGas1: H220
					PressGas: H280
21 Butane [1] REACH:	5-10%	106-97-8	601-004-00-0	203-448-7 [GHS02; GHS04
01-2119474691-32					FlamGas1: H220
					PressGas: H280
Isobutane [2] REACH:	2,5-5%	75-28-5	601-004-00-0	200-857-2	GHS02; GHS04
01-2119485395-27	,				FlamGas1: H220
					PressGas: H280
Acetone .REACH: 01-	25-50%	67-64-1	606-001-00-8	200-662-2	GHS02; GHS07
2119471330-49					Flam. Liq. 2: H225
					Eye Irrit. 2: H319 STOT
					SE 3: H336 EUH066
Xylene .REACH: 01-	5-<10%	1330-20-7	601-022-00-9	215-525-7	
2119752448-30					GHS02; GHS07; GHS08
					FlamLiq3: H226
					AcuteTox4: H312
					AcuteTox4: H332
					SkinIrrit2: H315
Ethylbenzene REACH:	0,3-0,5%	100-41-4	601-023-00-4	202-849-4	GHS02; GHS07 ; GHS08
01-2119489370-35					Flam. Liq.2: H225
					AspTox1: H304
					STOT RE2: H373
					Acute Tox.4: H332
					SkinIrrit2: H315
					EyeIrrit2: H319
					STOT SE3: H335
2-Butoxyethyl acetate	<0,01%	112-07-2	607-038-00-2	203-933-3	GHS07
REACH 01-2119475112-					AcuteTox4: H302
47					AcuteTox4: H312



Full text of H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878			
BAUTO-PLAST PRODUKT	Date of issue: 2024.11.28	APP Rally 400 Color Spray (all colors)	Page 4 z 7	

the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile : ≥ 0.45 mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

<u>Thermal Hazards:</u> None <u>Environmental exposure controls:</u> None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, aerosol, color as labeled Odour: characteristic Odour threshold: N.D. pH: N.A.
Melting point / freezing point: N.D.
Initial boiling point and boiling range: N.D.
Upper/lower flammability or explosive limits: N.D.
Vapour density: N.D.
Flash point: N.D.
Evaporation rate: N.A.
Vapour pressure: <300 kPa (50°C)
Density: 750-850 kg/m³ (15°C)

_ ^	
AUTO-PLA	R) ST PRODUKT

SAFETY DATA SHEET According Commission Regulation (EU) 2020/878

APP Rally 400 Color Spray (all colors)

Page 5 z 7

Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: 365°C Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: 58 cP (50°C) Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing **9.2. Other information** VOC: 659.17 g/l

Date of issue: 2024.11.28

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity Mixture is not reactive. 10.2. Chemical stability Stable under normal conditions of handling and storage. 10.3. Possibility of hazardous reactions None. 10.4. Conditions to avoid - solar radiation - sparks - flame - heat **10.5.** Incompatible materials - strong oxidisers - strong acids 10.6. Hazardous decomposition products None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects a) acute toxicity: no hazard b) skin corrosion/irritation: no hazard c) serious eye damage/irritation Causes serious eye irritation d) respiratory or skin sensitization: no hazard e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard g) reproductive toxicity: no hazard h) STOT-single exposure: May cause drowsiness or dizziness i) STOT-repeated exposure: no hazard j) aspiration hazard: no hazard 11.2. Information on other hazards 11.2.1. Endocrine disrupting properties - no data 11.2.2. Other information Repeated exposure may cause skin dryness or cracking. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Mixture is not classified as hazardous for the environment.
12.2. Persistence and degradability
No data.
12.3. Bioaccumulative potential
No data.
12.4. Mobility in soil
No data
12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None



SAFETY DATA SHEET

According Commission Regulation (EU) 2020/878

Date of issue: 2024.11.28

APP Rally 400 Color Spray (all colors)

Page 6 z 7

12.6. Endocrine disrupting properties None12.7. Other adverse effects None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number 1950 14.2. UN proper shipping name Aerosols, flammable 14.3. Transport hazard class(es) 2 14.4. Packing Group No 14.5. Environmental hazards No 14.6. Special Precautions for User During handling wear personal protection equipment (see Section 8) Avoid heat and flame. 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code N.A. Label: 2.1

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC

Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive) **15.2. Chemical Safety Assessment** No

SECTION 16. OTHER INFORMATION

the hazard)

 Full text of phrases referred to in Section 3:

 H220 Extremely flammable gas

 H222 Extremely flammable aerosol

 H280 Contains gas under pressure; may explode if heated

 H226 Flammable liquid and vapour

 H302 Harmful if swallowed

 H304 May be fatal if swallowed and enters airways

 H312 Harmful in contact with skin

 H315 Causes skin irritation

 H319 Causes serious eye irritation

 H332 Harmful if inhaled

 H335 May cause respiratory irritation

 H336 May cause drowsiness or dizziness

 H373 May cause damage to organs through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure cause

SAFETY DATA SHEET	
According Commission Regulation (EU) 2020/878	



Date of issue: 2024.11.28

APP Rally 400 Color Spray (all colors)

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

H411 Toxic to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.