

According Commission Regulation (EU) 2020/878

Page 1 z 6

Date of issue: 2025-01-22 APP Bumper Paint Structure Spray

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: APP Bumper Paint Structure Spray

Trade code: 210411

1.2. Relevant identified uses of the substance/mixture and uses advised against

One component structural foundation

Uses advised against: other

1.3. Details of the supplier of the safety data sheet

Company: APP Sp. z o. o.

ul. Przemysłowa 10, 62 – 300 Września

Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: app@app.com.pl

Strona WEB: www.app.com.pl

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. Emergency telephone number:

+48 (61) 437 00 00

Date of issue: 2024-01-22

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008





GHS02

GHS07

Dgr

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

2.2. Label elements

Labelling according Regulation (EC) No 1272/2008

Contains:

Ethyl acetate

Butyl acetate

Butan-2-one

Signal word:

Danger

Pictogram:





GHS02

GHS07

Hazard statement(s)

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

EUH066 Repeated exposure may cause skin dryness or cracking.



According Commission Regulation (EU) 2020/878

Page 2 z 6

Date of issue: 2025-01-22 APP Bumper Paint Structure Spray

Precautionary statement(s)

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P302+ P352 IF ON SKIN: Wash with plenty of water/...

P501 Dispose of contents/container according to local/regional/national/international regulations.

2.3 Other hazards

Buildup of explosive mixtures possible without sufficient ventilation.

UN: 1950

VOC (2004/42/EC, He: 840g/l). 635.2 g/l

No information on fulfilling the PBT or vPvB criteria in accordance with Annex XIII of Regulation 1907/2006 (REACH). No studies have been conducted.

The product does not contain ingredients included in the list established in accordance with Article 59 paragraph 1 as having endocrine disrupting properties or ingredients with endocrine disrupting properties in accordance with the criteria set out in Regulation 2017/2100/EU or Regulation 2018/605/EU in a concentration equal to or gratem than 0.1%.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of CLP regulation and related classification:

Nazwa niebezpiecznej	Zakres	Numer	Numer	Numer	Symbole
substancji	stężeń	CAS	indeksowy	WE	niebezpieczeństwa
Propane REACH: 01-	12,5-20	74-98-6	601-003-00-5	200-827-9	GHS02; GHS04
2119486944-21	%				FlamGas1: H220
					PressGas: H280
Butane REACH: 01-	5-10 %	106-97-8	601-004-00-0	203-448-7	GHS02; GHS04
2119474691-32					FlamGas1: H220
					PressGas: H280
Isobutane REACH: 01-	5-10 %	75-28-5	601-004-00-0	200-857-2	GHS02; GHS04
2119485395-27					FlamGas1: H220
					PressGas: H280
Butyl acetate REACH: 01-	5-10 %	123-86-4	607-025-00-1	204-658-1	GHS02; GHS04
2119485493-29					Flam.Liq.3: H226
					STOT SE3: H336
					EUH066
Ethyl acetate	25-50 %	141-78-6	607-022-00-5	205-500-4	GHS02; GHS07
REACH:					Flam.Liq.2: H225
01-2119475103-46					EyeIrrit2: H319
					STOT SE3: H336
					EUH066
Butan-2-one	5-<10%	78-93-3	606-002-00-3	201-159-0	GHS02; GHS07
REACH:					FlamLiq2: H225
01-2119457290-43					EyeIrrit2: H319
					STOT SE3: H336
Ethanol	<2,5%	64-17-5	603-002-00-5	200-578-6	
REACH:					GHS02; GHS07
01-2119457610-43					FlamLiq2: H225
					EyeIrrit2: H319
					Specific concentration
					limit: H319≥50%

Full text of H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:



According Commission Regulation (EU) 2020/878

Date of issue: 2025-01-22

APP Bumper Paint Structure Spray

Page 3 z 6

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.



According Commission Regulation (EU) 2020/878

Date of issue: 2025-01-22 APP Bumper Paint Structure Spray

Page 4 z 6

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile: \geq 0.45 mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

Thermal Hazards:

None

Environmental exposure controls:

None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance and colour: liquid, aerosol, black

Odour: characteristic, like acetone

Odour threshold: N.D.

pH: N.A.

Melting point / freezing point: N.D.

Initial boiling point and boiling range: N.D.

Linnar/lower flammability or avalogive limits: N.

Upper/lower flammability or explosive limits: N.D.

Vapour density: N.D. Flash point: N.D. Evaporation rate: N.A.

Vapour pressure: 350 hPa (20°C) Density: 800 kg/m³ (15°C) Solubility in water: insoluble

Solubility in organic solvents: soluble in aromatic solvents

Lipid solubility: N.A.

Partition coefficient (n-octanol/water): N.A.

Ignition temperature: N.D. Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity dyn.: N.D.



Page 5 z 6

According Commission Regulation (EU) 2020/878

Date of issue: 2025-01-22 APP Bumper Paint Structure Spray

Viscosity kin.: N.D.

Explosive properties: can form an explisive mixture in air

Oxidizing properties: not oxidizing

9.2. Other information

VOC: 635.2 g/l

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Mixture is not reactive.

10.2. Chemical stability

Stable under normal conditions of handling and storage.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

- solar radiation
- sparks
- flame
- heat

10.5. Incompatible materials

- strong oxidisers
- strong acids

10.6. Hazardous decomposition products

None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

- a) acute toxicity: no hazard
- b) skin corrosion/irritation: no hazard
- c) serious eye damage/irritation: causes serious eye irritation.
- d) respiratory or skin sensitization:no hazard
- e) germ cell mutagenicity: no hazard
- f) carcinogenicity: no hazard
- g) reproductive toxicity: no hazard
- h) STOT-single exposure: may cause drowsiness or dizziness.
- i) STOT-repeated exposure: no hazard
- j) aspiration hazard: no hazard
- 11.2.1. Endocrine disrupting properties
- no data
- 11.2.2. Other information

Repeated exposure may cause skin dryness or cracking.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

The mixture is not classified as hazardous to the environment

12.2. Persistence and degradability

Expected to be biodegradable.

12.3. Bioaccumulative potential

No data.

12.4. Mobility in soil

No data

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

None

12.7. Other adverse effects

None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds,



According Commission Regulation (EU) 2020/878

Date of issue: 2025-01-22

APP Bumper Paint Structure Spray

Page 6 z 6

ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number or ID number

1950

14.2. UN proper shipping name

Aerosols, flammable

14.3. Transport hazard class(es)

14.4. Packing Group

14.5. Environmental hazards

14.6. Special Precautions for User

During handling wear personal protection equipment (see Section 8)

Avoid heat and flame.

14.7. Sea transport in bulk in accordance with IMO instruments:

N.A.

Label: 2.1

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

SECTION 16. OTHER INFORMATION Full text of phrases referred to in Section 3:

1 will tell of pintubes reterious to in Section 5.				
H220	Extremely flammable gas			
H222	Extremely flammable aerosol			
H225	Highly flammable liquid and vapour			
H226	Flammable liquid and vapour			
H280	Contains gas under pressure; may explode if heated			
H319	Causes serious eye irritation			
H336	May cause drowsiness or dizziness			
The information contained herein is based on our state of knowledge at the above-specified date. It				
refers solely to the product indicated and constitutes no guarantee of particular quality.				
Total for Caller and the Caller Calle				

It is the duty of the user to ensure that this information is appropriate and complete with respect to

the specific use intended.