#### SAFETY DATA SHEET According Commission Regulation (EU) 2020/878



Date of issue: 2023-12-22

APP NSK 919 S

Page 1 z 6

# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: : **APP NSK 919 S** Trade code:**220505, 220506** 

1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Filling resin – sachet Uses advised against: other

1.3. Details of the supplier of the safety data sheet

Company: APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: <u>www.app.com.pl</u>

Safety Data Sheet e-mail: dzp@app.com.pl

1.4. <u>Emergency telephone number:</u> +48 (61) 437 00 00

Date of issue: 2023-12-22

# **SECTION 2. HAZARDS IDENTIFICATION 2.1. Classification of the substance or mixture** Classification according to Regulation (EC) No 1272/2008



Warning

SkinIrrit2: H315 Causes skin irritation. SkinSens1: H317 May cause an allergic skin reaction EyeIrrit2: H319 Causes serious eye irritation STOT SE3: H335 May cause respiratory irritation AquaticChronic2: H411 Toxic to aquatic life with long lasting effects 2.2. Label elements Labelling according Regulation (EC) No 1272/2008 Contains: 2-Hydroxyethyl methacrylate Isobornyl acrylate Benzyl methacrylate Signal word: Warning **Pictogram: GHS07** GHS09 Hazard statement(s)

H317 May cause an allergic skin reaction
Precautionary statement(s)
P264 Wash hands thoroughly after handling
P333+ P313 If skin irritation or rash occurs: Get medical advice/attention.

Date of issue: 2023-12-22

APP NSK 919 S

# 2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substances

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	<b>Classification:</b>
2-Hydroxyethyl	15-40 %	868-77-9	607-124-00-X	212-782-9	GHS07
methacrylate REACH: 01-					SkinIrrit2: H315
2119513212-58					SkinSens1: H317
					EyeIrrit2: H319
Isobornyl acrylate REACH:	10-20%	5888-33-5	-	227-561-6	GHS07; GHS09
01-21199557862-0011					Eye Irrit. 2: H319
					SkinSens1: H317
					H317SkinIrrit2: H315
					STOT SE 3: H335
					AquaticAcute1: H400
					AquaticChronic2:
					H410
Benzyl methacrylate	7-<13 %	2495-37-6	-	219-674-4	GHS07
					SkinSens1: H317
	7-<13 %	7534-94-3	-	231-403-1	GHS07
Exo-1,7,7-					SkinIrrit2: H315
trimethylbicyclo[2.2.1]hept-					EyeIrrit2: H319
2-yl methacrylate					STOT SE3: H335
					AquaticChronic3:
					H412
Toluene REACH: 01-	<0,1%	108-88-3	601-021-00-3	203-625-9	GHS02; GHS08;
2119471310-51					GHS07
					Flam. Liq. 2: H225
					<b>Repr. 2: H361d</b>
					Asp. Tox. 1: H304
					STOT RE 2: H373
					Skin Irrit. 2: H315
					STOT SE 3: H336

Full text of H-Phrases can be found under heading 16

# SECTION 4. FIRST AID MEASURES

# 4.1. Description of first aid measures

## In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. In case of irritation, consult a doctor

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

# In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

#### In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

### 4.2. Most important symptoms and effects, both acute and delayed:

May cause an allergic skin reaction

May cause respiratory irritation

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

#### **Treatment:**



Date of issue: 2023-12-22

APP NSK 919 S

None

#### SECTION 5. FIRE-FIGHTING MEASURES

# 5.1. Extinguishing media

# Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

#### 5.2. Special hazards arising from the substance or mixture

Flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

#### 5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

# 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

# 6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

#### **6.4. Reference to other sections**

See Section 8 for information on personal protection equipment.

#### SECTION 7. HANDLING AND STORAGE

# 7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

# 7.3. Specific end use(s)

None.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION



SAFETY DATA SHEET According Commission Regulation (EU) 2020/878

APP NSK 919 S

Page 4 z 6

**8.1.** Control parameters N.A.

#### 8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin. Eye protection: Wear face visor or goggles in circumstances where eye contact can accidentally occur. Protection for skin/hands: Nitrile gloves. Respiratory protection: Respiratory protection. Thermal Hazards: None Environmental exposure controls:

Date of issue: 2023-12-22

None

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, colorless Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range:N.D. Upper/lower flammability or explosive limits: -Vapour density: N.D. Flash point: >93,3°C Evaporation rate: N.A. Vapour pressure:N.D. Density: 1040 kg/m<sup>3</sup> (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: N.D. Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: N.D. Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC<25 g/l SECTION 10. STABILITY AND REACTIVITY 10.1. Reactivity Mixture is not reactive. 10.2. Chemical stability Stable under normal conditions of handling and storage. 10.3. Possibility of hazardous reactions None. 10.4. Conditions to avoid - solar radiation - sparks - flame - heat **10.5.** Incompatible materials - strong acids - oxides and reductors 10.6. Hazardous decomposition products None.

## SECTION 11. TOXICOLOGICAL INFORMATION

AUTO-PLAST PRODUKT	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878					
	Date of issue: 2023-12-22	APP NSK 919 S	Page 5 z 6			
<b>11.1. Information on toxicol</b> <b>a) acute toxicity:</b> no hazard	ogical effects					

a) acute toxicity: no hazard
b) skin corrosion/irritation: skin irritation.
c) serious eye damage/irritation: Causes serious eye irritation
d) respiratory or skin sensitization: May cause an allergic skin reaction
e) germ cell mutagenicity: no hazard
f) carcinogenicity: no hazard
g) reproductive toxicity: no hazard
h) STOT-single exposure: May cause respiratory irritation
i) STOT-repeated exposure: no hazard
j) aspiration hazard: No hazard
11.2.1. Endocrine disrupting properties
no data
11.2.2. Other information
no data

#### SECTION 12. ECOLOGICAL INFORMATION

# 12.1. Toxicity

Toxic to aquatic life with long lasting effects **12.2. Persistence and degradability** No data. **12.3. Bioaccumulative potential** No data. **12.4. Mobility in soil** No data **12.5. Results of PBT and vPvB assessment** vPvB Substances: None - PBT Substances: None **12.6. Endocrine disrupting properties** None **12.7. Other adverse effects** None

#### SECTION 13. DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

#### SECTION 14. TRANSPORT INFORMATION

14.1. UN number 3082 14.2. UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. 14.3. Transport hazard class(es) 9 14.4. Packing Group Ш 14.5. Environmental hazards YES 14.6. Special Precautions for User During handling wear personal protection equipment (see Section 8) Avoid heat and flame. 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code N.A. Label: 3

# SECTION 15. REGULATORY INFORMATION

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture** Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE.

	SAFETY DATA SHEET According Commission Regulation (EU) 2020/878				
AUTO-PLAST PRODUKT	Date of issue: 2023-12-22	APP NSK 919 S	Page 6 z 6		

Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive) 15.2 Chaminal Safety Assessment

15.2. Chemical Safety Assessment

No

# SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

H411 Toxic to aquatic life with long lasting effects

H412 Harmful to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It

refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.