

TECHNICAL INFORMATION

Issue Date:
04.12.2015.



Updating Date:
04.12.2015.

Page 1 from 2

Product Name: Dulling Additive for Acrylic System APP Modular 2K Acryl Line 50-96. APP No.: 0250096.

Special purpose product intended for dulling of APP Modular 2K Acryl Line top coat and other two-component Acrylic top coats. Application of matting additive does not result in discoloration, change of levelling and UV resistance.

Package: Dulling additive APP Modular 2K Acryl Line 50-96 – 1.0L.

Product and additives: Dulling additive APP Modular 2K Acryl Line 50-96.


Viscosity: 100-110 s 4mm DIN/+20°C.

Application Special purpose product intended for dulling of Acrylic top coat from APP Modular 2K Acryl Line system.

Use

Mixing ratio:

Mixing ratio by volume before adding the hardener and thinner to the top coat:



Semi-matt:

30 by volume

Dulling additive 50-96

70 by volume

APP Modular 2K Acryl Line

Matt:

50 by volume

Dulling additive 50-96

50 by volume

APP Modular 2K Acryl Line

Caution!

Before use mix the product well.

Mixing ratio of hardener and thinner for the desired effect shall be according to ratio of top coat.

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.

TECHNICAL INFORMATION

Issue Date:
04.12.2015.




Updating Date:
04.12.2015.

Page 2 from 2

**Product Name: Dulling Additive for Acrylic System
APP Modular 2K Acryl Line 50-96. APP No.: 0250096.**

Drying




Drying time of coat along with dulling additive may longer than specified in the top coat's manufacturer instructions.
Pot life: 6h.

Tool cleaning:

Nitrocellulose thinner.

Storage:



Store in closed, original containers, in dry and well ventilated spaces.
Protect against freezing.

Occupational safety:



Product for professional use only.
See: labels on containers and MSDS.
User shall follow locally and regionally applicable industrial safety regulations.

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.