TECHNICAL INFORMATION

Date drafted: 07.12.2021



Date updated: 07.12.2021

Page 1 of 1

Modular Industrial Line Product name: thickening additive for lacquers and primers APP Thixo Additive 30-920. APP No.: 0279921.

An additive from the APP Modular Industrial Line system intended for increasing the density of primers and topcoats. Allows very thick coatings to be spray-applied without the risk of dripping.

Product and accessories. APP Thixo Additive 30-920.

Colour. Transparent grey-white.

Form: Paste.

Specific weight. 0.9 kg/L at 20°C.

Application. Intended to change the density of APP Modular Industrial Line

system primers and varnishes.

Application

Mixing ratios. Mixing ratios by weight:




100 APP Modular Industrial Line Lack/Primer

max 10 APP Thixo Additive 30-920

After applying the additive, mix very thoroughly, e.g. mechanically, until a homogeneous mixture is obtained.

Equipment cleaning. Nitrocellulose, PUR or acrylic solvent.

Storage



Store in closed original packaging in a dry and well-ventilated room, at +5°C to + 30°C.

Protect from frost and direct sunlight.

OHS regulations



For professional use only.

See text on product labels or SDS.

The user must comply with the OHS regulations in force in the country concerned.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.