

TECHNICAL INFORMATION



Preparation Date:
17.05.2011

Updating Date:
17.05.2011

Page 1 from 1

Product Name: APP 2K Epoxy Verdunnung

Epoxy products thinner purposed for determining spraying viscosity of primers and base primers in case of motor and utility cars renovation.

Package: 1.0l

Product and additives: APP 2K Epoxy Verdunnung

Main ingredients: aromatic hydrocarbons mixture.

Colour: transparent, clear liquid

Specific gravity: 0.884 g/cm³ (DIN 53217)

Application: Use with APP 2K Grund EP and other epoxy products purposed for car body repairs.

Use: Follow the thinned product recipe.

Keep in a closed container.

Protect against humidity.

Storage: Store in closed, original containers, in dry and well ventilated spaces at temperature from 5°C to + 30°C. Protect against freezing.

Industrial Safety: Product for professional use only.
See: labels on containers and MSDS.
User must follow locally and regionally applicable industrial safety regulations.

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.

Auto Plast Produkt S.A 62-300 Września ul.Przemysłowa 10 Phone +48 61 437 00 00.