

# SPECIFICATIONS

Prepared on:  
March 22, 2005



Updated on:  
December 21, 2007

Page 1 of 2

## Product name: APP W900 Silikonentferner

A specially designed remover for cleaning and degreasing non-insulated metal surfaces, old lacquer coats, primers, fillers and filling coats, before applying the finishing coating.

Container: 1.0 l; 5.0 l; 30 l.

Product and additives: APP W900 Silikonentferner.

Colour: Transparent, colourless.

Usage: The product is intended for removing impurities including silicone, teflon, oils and greases from the surfaces to be lacquered.

### Base

Proper base types: Non-insulated metal surfaces, old lacquer coats, primers, fillers and filling coats.

### Application



Before carrying out a repair or reapplying a coat, it is necessary to clean and degrease the surface of the vehicle body, which is to be repaired or lacquered.

Soak a cleaning cloth in the remover and apply the liquid onto the surface being degreased. Immediately after applying, wipe the surface dry with another clean piece of an absorbant cleaning cloth.

#### Caution!

Frequent and regular replacement of the cleaning cloth is necessary. If needed, keep repeating this operation until impurities are completely removed.

### Applying:

The product is to be applied with a paintbrush, brush, cotton or cellulose cleaning cloth, sponge, or by spraying.

It is recommended to employ hand-operated atomizers resistant to removers in order to reduce the amount of remover being used.

### Drying:



As soon as the surface is degreased, the remover which is left over evaporates, thus lowering the temperature of the element. In extreme conditions, this may result in the condensation of moisture contained in the air.

It is recommended to wait until the remover and moisture have evaporated, and the temperature of the surface being washed returns to the ambient temperature level.

The above information complies with current knowledge on our products and their possible applications. This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect the final result of work.

**Auto Plast Produkt Sp. z o.o. [Ltd.] 62-300 Wrzeźnia, ul. Przemysłowa 10, Poland  
tel. + 48(prf)61 437 00 00**

# SPECIFICATIONS

Prepared on:  
March 22, 2005



Updated on:  
December 21, 2007


Page 2 of 2

## Product name: APP W900 Silikonentferner

### Equipment cleaning:

Nitrocellulose solvent.

### Storage:



Store in original, closed containers in a dry and well-ventilated room.  
Protect against freezing.

### Industrial safety regulations:



For professional use only.  
See: information on product labels and/or in Hazardous Material Safety Data Sheet.  
Users should observe all industrial safety regulations applicable in their countries.

### VOC:

Permissible VOC content [g/l] in a ready-to-use product.  
850 g/l for APP W900 Silikonentferner  
Maximum VOC content [g/l] in a ready-to-use product.  
750 g/l for APP W900 Silikonentferner

The above information complies with current knowledge on our products and their possible applications.  
This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect the final result of work.

**Auto Plast Produkt Sp. z o.o. [Ltd.] 62-300 Września, ul. Przemysłowa 10, Poland  
tel. + 48(prf)61 437 00 00**