

TECHNICAL INFORMATION

Date of Preparation:
03.01.2011



Date of Updating
03.01.2011

Page 1 of 2

Product Name: APP 2K HS Löser Spray

A solvent for eliminating dry spray and fuse new coats with existing coats, used for local repair and grading with HS class paints made in accordance with the LZO/VOC standard. It can be used with older generations of traditional paints.

Package: A 400ml aerosol with flat rotating nozzle
Product and additives: APP 2K HS Löser Spray

Basic components: A special solvent mix used for work with paints with low thinner content
Colour: Transparent, insipid

Application: A special product, used for SPOT/SMART repairs with two-component HS class acrylic surface paints with LZO/VOC<420g/l.t


Application
Procedure: Mix the contents thoroughly by shaking the container for 2-3 minutes.

Immediately after surface spraying is finished, on the dry spray area or the zone of transition of the new HS coat into the old one apply a thin layer of the grading thinner APP 2K HS Löser Spray. Spray from 20-25cm. After 10-15 seconds, dry spray is fused into the base or elimination of a sharp paint contact edge.

Warning:

This is a delayed action product. Do not use on paints with thermoplastic base.

Storage:



Store in closed original packages in dry and well ventilated spaces.
Protect against freezing and temperatures above 50°C

The above information is in accordance with currently possessed knowledge on our products and application hereof. The information does not guarantee any specific properties and fitness for particular use. Adhere strictly to warning and remarks provided on labels of products and Material Safety Data Sheets. We are not responsible for any final results of the work resulted from factors beyond our control.

Auto Plast Product S.A. 62-300 Września ul. Przemysłowa 10 Phone: +48(prefix) 61 437 00 00

TECHNICAL INFORMATION

Date of Preparation:
03.01.2011



Date of Updating
03.01.2011

Page 2 of 2

Product Name: APP 2K HS Löser Spray

Health and Safety:



Product for professional use only.
Before use consult: labels on the product's packages or Material Safety Data Sheet.
User shall adhere to locally applicable industrial safety regulations.

LVO/VOC:

Permissible LZO g/l value in ready to use product.
840 g/l for APP 2K HS Löser Spray
Maximum LZO g/l content in ready to use product.
792 g/l for APP 2K HS Löser Spray

The above information is in accordance with currently possessed knowledge on our products and application hereof. The information does not guarantee any specific properties and fitness for particular use. Adhere strictly to warning and remarks provided on labels of products and Material Safety Data Sheets. We are not responsible for any final results of the work resulted from factors beyond our control.

Auto Plast Product S.A. 62-300 Września ul. Przemysłowa 10 Phone: +48(prefix) 61 437 00 00