

# SPECIFICATIONS

Prepared on:  
March 22, 2005



Updated on:  
March 22, 2005

Page 1 of 1

## Product name: APP Anti-Silikon

An additive for top coat lacquers and primers, which neutralises the effects of silicone soiling on lacquered surfaces.

Container: 0.25 l, 1.0 l.  
Product and additives: APP Anti-Silikon.  
Basic components: Anti-silicone agent and a composition of solvents.  
Colour: Transparent, colourless.  
Usage: In case indications of soiling occur, in order to continue work.  
Caution:  
It is not recommended to use anti-silicone agents for preventive purposes.

### Base

Proper base types: Non-insulated metal surfaces, old lacquer coats, primers, fillers and filling coats.

### Application

Mixing ratio(s): Depending on the degree of silicone soiling, add from 2 to max. 5% of APP Anti-Silikon to the paint, which is ready for spraying. Stir well.


### Drying:



The paint drying time doesn't change as a result of adding APP Anti-Silikon.

Equipment cleaning: Nitrocellulose solvent.

### Storage:



Store in original, closed containers in a dry and well-ventilated room. Protect against freezing.

### Industrial safety regulations:



For professional use only.  
See: information on product labels and/or in Hazardous Material Safety Data Sheet.  
Users should observe all industrial safety regulations applicable in their countries.

The above information complies with current knowledge on our products and their possible applications. This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect the final result of work.