

# TECHNICAL INFORMATION

Development date:  
20.07.2009.



Updated: 20.07.2009.

Page 1 of 2

## Product name: APP 80°C PLUS Masking Tape- yellow.

APP 80°C PLUS self-adhesive spray painting masking tape on an impregnated, slightly wrinkled paper medium with natural rubber and resin-based glue. It ensures excellent adhesion to the masked surface, simple and clean removal, and a precise cut-off line of the painted surface.

### Technical data:

Total tape thickness	95 $\mu$	$\pm 15$
Grip / adhesion	4 N/25mm	$\pm 1$
Tensile strain before breaking	9%	$\pm 2$
Load before breaking	60N/mm <sup>2</sup>	$\pm 10$
Resistance to long-term high temperature	80°C.	
Color	yellow	
Tape length per roll	45m	

Intended use: Intended for use in car and industrial painting. Resistant to organic solvents and increased temperatures.

Surface: All surfaces to which the self-adhesive masking tapes are applied must first be de-dusted and de-greased.

Use The self-adhesive masking tape should be used in a temperature range of 15-25°C. If the storage temperature is different, then the tape must be brought to the recommended temperature prior to use. The optimal peeling temperature range is 20-30°C.

#### Caution!

Certain factors, such as sun rays (especially ultraviolet), ozone, salt water, or chemicals may have an adverse effect on the usage of self-adhesive tapes.

Application: When taping, the tension cannot be too high, as the tape's elastic properties will force it to return to its original length, losing its adhesive properties.

The above information conforms with the current state of knowledge concerning our products and the possibility of their application. This does not guarantee specific properties or suitability for use in particular conditions. Please follow the notes and warnings contained on product labels and in the safety data sheet. We do not assume any liability, if the end result of work was influenced by factors beyond our control.

# TECHNICAL INFORMATION

Development date:  
20.07.2009.



Updated: 20.07.2009.

Page 2 of 2

**Product name: APP 80°C PLUS Masking Tape- yellow.**

## Storage:



Store in original, closed packaging, in a dry and well ventilated place. Do not store tapes near sources of heat, in high moisture conditions, especially in so called salty mist. It is recommended to not exceed a humidity of 65%.

## OHS Regulations:



For professional use only.  
See: text contained on product labels or the product safety data sheet.  
The user must follow OHS regulations applicable in the given country.

The above information conforms with the current state of knowledge concerning our products and the possibility of their application. This does not guarantee specific properties or suitability for use in particular conditions. Please follow the notes and warnings contained on product labels and in the safety data sheet. We do not assume any liability, if the end result of work was influenced by factors beyond our control.