

TECHNICAL INFORMATION

Date drafted: 12.02.2024



Date updated: 12.02.2024

Page 1 of 2

Product Name: APP P Mask Standard Masking Paper. APP No.: 070411, 070421, 070431.

APP P Mask Standard is a double-sided smooth masking paper with a basis weight of 45 g/m², produced without the addition of recycled materials. Designed and manufactured as a specialised masking paper for the needs of automotive refinishing and industrial painting.

Sales Unit. A roll wound on a core with a 75 mm diameter hole.

Width of roll [cm]	Length of roll [m]	APP No.
30	300	070411
60	300	070421
90	300	070431

Product and accessories. APP P Mask Standard – masking paper.
NTools ADG75 – adapter for ø75 mm core (APP No. 070460).
APP Expert, APP Plus, APP Standard, APP Red Tape, and APP White Tape – automotive adhesive masking tapes.

Basic ingredients. Recycled-material-free pure cellulose with a high level of refinement, ensuring a naturally sealed sheet for the highest protection against leakage.
Contains no harmful chemical substances.

Advantages.

- Dust-free.
- Has a dense, non-porous structure.
- Masking possible with any side.
- Flexible, conforms well to the shape of the bodywork – does not crack on bends and folds.
- Long time until paint dust penetrates the masking.

Colour	brown.
Grammage	45 g/m ² (ISO536)
Thickness	65 µm (ISO534)
Density	690 kg/m ³ (ISO534)
Tensile Index MD	118 Nm/g (ISO 1924-3)
Tensile Index CD	59 Nm/g (ISO 1924-3)
Average Tensile Index.	89 Nm/g (ISO 1924-3)
Tensile Strength MD	5.3 kN/m (ISO 1924-3)
Tensile Strength CD	2.7 kN/m (ISO 1924-3)

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.

TECHNICAL INFORMATION

Date drafted: 12.02.2024




Date updated: 12.02.2024

Page 2 of 2

Product Name: APP P Mask Standard Masking Paper.
APP No.: 070411, 070421, 070431.

Average Tensile Strength	4.0 kN/m (ISO 1924-3)
Average Tensile Strength MD/CD	2.0 (ISO 1924-3)
Elongation at Break MD	1.5% (ISO 1924-3)
Elongation at Break CD	2.8% (ISO 1924-3)
Tear Index MD	8 mNm ² /g (ISO1974)
Tear Index CD	9 mNm ² /g (ISO1974)
Tear Strength MD	360 mN (ISO1974)
Tear Strength CD	405 mN (ISO1974)
Air Resistance (Gurley)	100.0 s/100 ml (ISO 5636-5)
Cobb Water Absorptiveness, top-side	23 g/m ² (60s) (ISO535)
Cobb Water Absorptiveness, wire-side	24 g/m ² (60s) (ISO535)
Humidity	7.9% (ISO287)
Bendtsen Roughness, top-side	800 ml/min (ISO 8791-2)
Bendtsen Roughness, wire-side	200 ml/min (ISO 8791-2)

Storage



Store in closed original packaging in a dry and well-ventilated room. Protect from direct sunlight. Protect from rodents.

OHS regulations



See text on product labels or SDS.
The user must comply with the OHS regulations in force in the country concerned.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.