

## TECHNICAL INFORMATION

Date drafted:  
26/10/2022



Date updated:  
26/10/2022

Page 1 of 3

**Product name: APP for AD CUT coarse-grained polishing paste.  
APP No.: 081220, 081222.**

A polishing paste with an innovative formulation to effectively remove very deep scratches from the paint surface. It is designed to work with Dual Action rotary and eccentric polishers. The technology used ensures low dusting of the paste during work and a significant reduction in surface time. It can be used for all types of paintwork. Leaves an aesthetically pleasing and smooth finish. Does not contain silicone, wax or fillers. It has a pleasant banana fragrance. Best results are obtained using APP 2CUT polishing sponges or APP 2HEAVY CUT polishing furs.

Packaging	081220 - 100 ml, 081222 - 500 ml.
Product and accessories	APP for AD CUT.
Basic ingredients	a mixture of aluminium oxide abrasive grain, hydrocarbons and additives.
Colour	white.
Density at 20°C	1.08 g/cm <sup>3</sup> .
pH	8
Shear force	Extreme - 5 out of 5.
Gloss level	High, 3 out of 5.
<u>Application</u>	The paste is designed for quick removal of: <ul style="list-style-type: none"><li>• very deep scratches from P1200-P1500 sandpaper,</li><li>• “orange peels”,</li><li>• residues from inclusions and stains,</li><li>• for machine and manual work.</li></ul>

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.

## TECHNICAL INFORMATION

Date drafted:  
26/10/2022



Date updated:  
26/10/2022

Page 2 of 3

**Product name: APP for AD CUT coarse-grained polishing paste.  
APP No.: 081220, 081222.**

### Application

For application on:

- factory coatings in the automotive industry,
- scratch-resistant, HS and UHS renovation paints during refinishing,
- UV-cured coatings,
- old oxidised paintwork during renovation,
- Dual Action rotary and eccentric polishers.

Note!

Use only on hardened substrates.

### Process

If necessary, sand the surface manually with APP P1200-APP P2500 waterproof abrasive paper or by machine with APP P1200-APP P2500. Eliminate spot damages and inclusions with APP P1500-APP P2500 abrasive pads.

Remove any sanding residue before polishing.

Mix the suspension by shaking before use.

Apply the paste onto clean and degreased paint surface or onto the surface of a hard APP 2CUT polishing sponge (APP No.: 080130, 080131, 080132) or APP 2HEAVY CUT fur (APP No.: 080146, 080147). When a clear gloss is achieved, stop work and inspect the surface to determine if further treatment with a new batch of paste is needed.

Remove paste residue with APP 2CLEAN MF microfibre cloth (APP No. 080653).

Speed for rotary polisher 1500-2000 rpm.

Vibration frequency for the eccentric polisher 2000-10 000 1/min.

After polishing, it is recommended to check the surface by washing it off with the APP Finish Test polishing quality assessment product (APP No. 210910).

Note!

When working, the working surface of the sponge or fur used should be cleaned regularly.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.

## TECHNICAL INFORMATION

Date drafted:  
26/10/2022




Date updated:  
26/10/2022

Page 3 of 3

**Product name: APP for AD CUT coarse-grained polishing paste.  
APP No.: 081220, 081222.**

### Storage



Store in closed original packaging in a dry and well-ventilated room.  
Protect from frost and sun.

### OHS regulations



For professional use only.  
See text on product labels or SDS.  
The user must comply with the OHS regulations in force in the country concerned.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.

**APP Sp. z o.o. 62-300 Września ul. Przemysłowa 10, tel. + 48 61 437 00 00.**