

TECHNICAL INFORMATION

Date drafted: 15.11.2022



Date updated: 15.11.2022

Page 1 of 2

Product name: APP P03 Heavy Duty Compound Abrasive Polishing Paste. APP No.: 081301, 081304, 081307.

A silicone-free, coarse-grained polishing emulsion consisting of synthetic abrasive grain and non-aromatic hydrocarbons dissolved in water. Thanks to the use of mutually compatible non-stick ingredients, the paste guarantees very high abrasion intensity. Removes scratches and tarnishes, makes the surface glossy, and prepares the lacquer surface for finishing works with APP P10 Leveling Compound paste. It is intended for machine and manual work. Best results are obtained by using hard and medium-hard APP sponges or polishing furs.

Packaging	081301 - 600 g, 081304 - 1200 g, 081307 - 6000 g.
Product and accessories	APP P03.
Basic ingredients	A mixture of synthetic abrasive grain, hydrocarbons and additives dissolved in water.
Colour	Light blue.
Density at 20°C	1.24 g/ml.
pH	9.0.

Application: The paste is designed for:

- machine and manual work,
- the removal of scratches up to P2500,
- for the removal of localised defects on the paint surface,
- removing residues of APP P01 paste.

Application For application on:

- polished surfaces as the second stage after APP P01 Intensive Compound,
- rotary polishers,
- factory paintwork,
- MS and HS refinish paints when carrying out paint repairs,
- old, oxidised paintwork during renovation,
- furniture paintwork during finishing work.

Note!

Use only on hardened substrates.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.

TECHNICAL INFORMATION

Date drafted: 15.11.2022



Date updated: 15.11.2022

Page 2 of 2

Product name: APP P03 Heavy Duty Compound Abrasive Polishing Paste. APP No.: 081301, 081304, 081307.

Process

If necessary, sand the surface manually with APP P1500-APP P3000 waterproof abrasive paper or APP P1500-APP P2500 by machine.

Eliminate spot damages and inclusions with APP P1500-APP P2500 abrasive pads.

Remove any sanding residue before polishing.

Mix the suspension by shaking before use.

Apply the paste to a clean and degreased lacquer surface or to the surface of an APP hard polishing sponge or fur. During polishing, the abrasive particles become finer and, over time, their abrasive effect decreases, while increasing the gloss effect. When a clear gloss is achieved, stop work and inspect the surface to determine if further treatment with a new batch of paste is needed. Remove any paste residue with a microfibre cloth, e.g. APP MF Cloth (APP No. 080649).


Speed for rotary polisher 1500-2000 rpm.

After polishing, it is recommended to check the surface by washing it off with APP Finish Test polishing quality assessment product (APP No. 210910) or with APP IPA isopropyl alcohol (APP No. 030670).

Note!

When working, the surface of the sponge or fur used should be cleaned regularly.

Storage:



Store in closed original packaging in a dry and well-ventilated room.

Protect from frost and sun.

OHS regulations:



For professional use only.

See text on product labels or SDS.

The user must comply with the OHS regulations in force in the country concerned.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.