

TECHNICAL INFORMATION

Preparation Date:
11.06.2015



Revision Date:
11.06.2015

Page 1 from 2

Product name: All Purpose Polishing Paste APP QUARTZ Q802, APP No. 081371

All Purpose Paste is an emulsion for machine or manual polishing. It removes car body scratches, refreshes a surface and imparts high gloss. It is free of silicone, waxes and aggressive solvents. For best effects use of **QUARTZ Q804** (080010) and **QUARTZ Q805** (080011) Polishing Pad is recommended.

Package:	1.0kg
Product and additives:	APP QUARTZ Q802.
Basic components:	Mixture of abrasive grit, aluminium oxide, hydrocarbons and additives.
Colour:	White.
Density at 20°C:	1.15g/mL

Use

Impart high gloss and quickly removes:

- Deep scratches in case of P1500,
- “Peel appearance”,
- Holograms,
- Inclusion and run,

Application

Purposed for:

- Top coats in automotive industry,
- Scratch-resistant top coats, HS and UHS system during top coats repairs,
- UV hardened top coats,
- Repair of aged oxidized coats,
- Finish work related to furniture top coats,
- Powder paints and gel coats.

Caution!

Apply on hardened substrate only.

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.

TECHNICAL INFORMATION

Preparation Date:
11.06.2015



Revision Date:
11.06.2015

Page 2 from 2

Product name: All Purpose Polishing Paste APP QUARTZ Q802, APP No. 081371

Process

If necessary a surface shall undergo manual sanding with water resistant sandpaper APP P1500-APP P2500 or machine sanding with APP P1200-APP P3000.

Any spot damages and inclusions shall be repaired with APP P1500 – APP P2500 Flexipads.

Before polishing clean the surface and remove any deposits resulted from sanding. Before use shake the container well.

Apply paste on clean and degreased top coat or sponge (buffing pad). During work abrasive grit subjects to grinding down what decreases sanding efficiency but at the same time increases gloss.

If high gloss is obtained interrupt the work and check the surface in respect of any further treatment or paste reapplication.

Remove any paste remains with QUARTZ Q806 Microfiber Cloth.

Polisher rotational speed: 1500-2000 rpm.

Eccentric polisher vibration frequency: 2000-10000¹/min.


Upon polishing completion it is recommended to check the surface by wiping dry with APP Finish Test (210910).

When polishing dark coloured surfaces, provide finishing treatment with APP QUARTZ Q802 All Purpose Paste (081371).

Caution!

During work always clean sponge surface or buffing pad on regular basis.

Storage:



Store in closed, original containers, in dry and well ventilated spaces.

Protect against sunshine and freezing.

Occupational safety:



Product for professional use only.

See: package label and MSDS.

User shall follow locally and regionally applicable industrial safety regulations.

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.