

TECHNICAL INFORMATION

Preparation Date:
27.06.2011



Updating Date:
27.06.2011

Page 1 from 2

Product Name: APP WB30 Rust Remover

Powerful rust remover that creates lubricating film. Includes MoS₂ Molybdenum Disulfide. Molybdenum Disulfide coat on surfaces subjected to wear and tear due to friction ensures effective protection both at low and high temperatures. Silicone free.

Package:	400ml –aerosol
Product and additives:	APP WB30
Main ingredients:	mineral oils mixture
Colour:	grey

Application:

- Solves any problems regarding disconnection of old and rusty screw joints during maintenance and repairs
- Loosens rusted, baked joints as: screws, hinges, levers, bolts, pins, etc.
- Cleans and maintains gears, breaking system, chains and pull rods in good working order

Properties:

- Dissolves rust and loosens any baked joints
- Ensures solid protection against corrosion according to DIN 50017
- Lubricates automatically sliding surfaces,
- Ensures coat that separates metal surfaces,
- Penetrates deep inside thanks to capillary action and crawling properties.
- Makes moving parts easy to move and stops squeaks.
- Removes humidity in ignition systems, wiring and improves conductivity,
- Prevents rust generation on surfaces previously treated,
- Economical in use thanks to possibility of precise point-wise application.

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.

Auto Plast Produkt S.A 62-300 Września ul.Przemysłowa 10 Phone +48 61 437 00 00.

TECHNICAL INFORMATION

Preparation Date:
27.06.2011



Updating Date:
27.06.2011

Page 2 from 2

Product Name: APP WB30 Rust Remover

Application:

Process:



Mix contents by shaking the container for 2-3 minutes.
Apply a thin layer of WB30 in a point wise manner at distance 10-20 cm and wait till penetration follows.
If necessary repeat this action.

Storage:



Store in closed, original containers in dry and well ventilated spaces. Protect against freezing and temperature over 50°C.

Industrial Safety:



Product for professional use only.
See: labels on containers and MSDS.
User must follow locally and regionally applicable industrial safety regulations.

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.

Auto Plast Produkt S.A 62-300 Września ul.Przemysłowa 10 Phone +48 61 437 00 00.