

TECHNICAL INFORMATION

Preparation Date:
06.02.2012



Updating Date:
06.02.2012

Page 1 from 2

**Product name: Vaseline Aerosol APP W11.
APP No.: 212031.**

Universal lubricant of neutral pH value. Resistant to weak acids and bases and weather conditions. Operating temperature from -30°C up to +160°C.

Package: 400ml Aerosol.

Product and additives: APP W11.

Colour: transparent.

Use temperature: from +5°C up to +30°C.

Use:

- Lubricant for industries and trades
- Protects against wear and tear of cooperating mechanical parts
- Elimination of noise, squeal and creaking of side elements e.g. slide guides
- Protection of rotating elements against jamming
- Lubricating battery poles (also in terms of insulation and maintenance)
- For use in food industry

Properties:

- Eliminates bothersome noise, squeal and creaking that follow during friction resulted from cooperation of parts and elements
- Keeps water away
- Facilitates movement of elements on side guides
- Protects against corrosion and oxidation
- Resistant to weather conditions
- Resistant to small concentrations of acids, salts, bases

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.

TECHNICAL INFORMATION

Preparation Date:
06.02.2012



Updating Date:
06.02.2012

Page 2 from 2

**Product name: Vaseline Aerosol APP W11.
APP No.: 212031.**

Application

Process:



Remove remains of other lubricants and mechanical contamination with APP BR01 brake remover.


Mix well by shaking the container for 2-3 minutes.

Apply this coat of APP W11 maintaining distance 10 -20 cm.

Repeat, if necessary.

Excellent lubricating properties are ensured after evaporation of solvent, namely after around 1 minute.

Storage:



Store in closed, original containers in dry and well ventilated spaces.

Protect against freezing and temperature over 50°C.

Industrial Safety:



Product for professional use only.

See: labels on containers and MSDS.

User must follow locally and regionally applicable industrial safety regulations.

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.