

TECHNICAL INFORMATION

Preparation Date:
07.02.2012



Updating Date:
07.02.2012

Page 1 from 2

**Product name: Ceramic Grease Aerosol APP SC1200°C.
APP No. : 212032.**

Resistant to high temperatures ceramic lubricant designed for use under heavy loaded mechanical and thermal elements. Prevents corrosion and sticking of lubricated elements. Operating temperature from -40°C up to +1200°C.

Package: 400ml Aerosol.

Product and additives: APP SC1200°C.

Colour: white.

Use temperature: from +5°C up to +30°C.

Use:

- Lubricant for industries and trades
- Prevents sticking of elements exposed to high temperature
- Eliminates bothersome brake squealing without disruption for ABS sensors operation
- During assembly of brake pads
- During assembly of oxygen sensor
- Protects joints exposed to high temperature e.g. in exhaust systems and industrial furnaces

Properties:

- Very high thermal stability
- Prevents sticking of lubricated elements.
- Eliminates bothersome noise, squeal and creaking that follow during friction resulted from cooperation of parts and elements in high temperatures
- Resistant to cold and hot water
- Protects against electrolytic corrosion and oxidation
- Resistant to small concentrations of acids, salts, bases
- Dirt repelling

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.

TECHNICAL INFORMATION

Preparation Date:
07.02.2012



Updating Date:
07.02.2012

Page 2 from 2

**Product name: Ceramic Grease Aerosol APP SC1200°C.
APP No. : 212032.**

Application

Process:



Remove remains of other lubricants and mechanical contamination with APP BR01 brake remover.

Mix well by shaking the container for 2-3 minutes.

Apply this coat of APP SC1200°C maintaining distance 10 -20 cm.


Repeat, if necessary.

Excellent lubricating properties are ensured after evaporation of solvent, namely after around 1 minute.

Caution!

Do not spray over brake discs.

Storage:



Store in closed, original containers in dry and well ventilated spaces.

Protect against freezing and temperature over 50°C.

Industrial Safety:



Product for professional use only.

See: labels on containers and MSDS.

User must follow locally and regionally applicable industrial safety regulations.

The above information is based on currently available data and knowledge on the product and its use. The information does not purport to be a description of product in terms of its quality, suitability for use in some conditions, nor does it guarantee any particular features. User shall follow instructions provided on labels and MSDS. Producer is not responsible for consequences and work effects that were influenced with factors beyond his control.