

SPECIFICATIONS

Prepared on:
July 18, 2007



Updated on:
July 18, 2007


Page 1 of 3

Product name: F-RUST Remover

Preparation for the removal of volatile rust (mechanical dust) from the car body.

<u>Container:</u>	1.0 l; 10 l
<u>Basic components:</u>	oxalic acid, polyetoxylated isotridecanol
<u>pH:</u>	1.5
<u>Colour:</u>	Colourless
<u>Density:</u>	1.03 g/cm ³ (at the temperature of 20 °C)
<u>Smell:</u>	Characteristic

Usage:



A preparation designed for removing volatile rust traces from the car body and windows. Volatile rust (mechanical dust) most often accumulates on mudguards and bumpers of cars equipped with a disk braking system. Moreover, it occurs on new cars, transported by railway with electric traction. After some time, a brown coating occurs around the dust particles, which are embedded or, as a rule, hot-fused. This deteriorates the aesthetic appearance of the surface and makes maintenance of the lacquer coat considerably harder.

The above information complies with the current knowledge on our products and their possible applications. This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect the final result of work.

**Auto Plast Produkt Sp. z o.o. [Ltd.] 62-300 Września, ul. Przemysłowa 10, Poland
tel. + 48(prf)61 437 00 00**

SPECIFICATIONS

Prepared on:
July 18, 2007




Updated on:
July 18, 2007

Page 2 of 3

Product name: F-RUST Remover

Directions for use:



Apply a thin layer of the agent onto the cleaned surface using a sprayer or sponge. After approximately 1 minute wipe the surface with a brush or washing sponge, and rinse with plenty of water under pressure. The product may be used undiluted or diluted with water in a proportion max. 1:2. Repeat the procedure if necessary.


Constraints:

Never allow the cleaned surface to dry with the preparation on it, and never exceed the maximum allowed reaction time - 5 minutes.

Equipment cleaning:

Water.

Storage:



Store in original, closed containers in a dry and well-ventilated room. Protect against freezing.

Industrial safety regulations:



For professional use only.
See: information on product labels and/or in Hazardous Material Safety Data Sheet.
Users should observe all industrial safety regulations applicable in their countries.

The above information complies with the current knowledge on our products and their possible applications. This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect the final result of work.

**Auto Plast Produkt Sp. z o.o. [Ltd.] 62-300 Września, ul. Przemysłowa 10, Poland
tel. + 48(prf)61 437 00 00**

SPECIFICATIONS

Prepared on:
July 18, 2007



Updated on:
July 18, 2007

Page 3 of 3

Product name: F-RUST Remover

Hazards:



See Material Safety Data Sheet

- the product is harmful
- the product is harmful in contact with the skin and if swallowed
- the product is irritating
- the product is irritating to eyes

R36 Irritating to eyes.

R21/22 Harmful in contact with skin and if swallowed.

S2 Keep out of the reach of children.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39 Wear suitable gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

The above information complies with the current knowledge on our products and their possible applications. This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect the final result of work.

**Auto Plast Produkt Sp. z o.o. [Ltd.] 62-300 Września, ul. Przemysłowa 10, Poland
tel. + 48(prf)61 437 00 00**