TECHNICAL INFORMATION

Date of preparation:
18 July 2007

Date updated:
13 September 2024

Product name: APP GM Care
Silicone-based product for the care of tyres and exterior plastics

Packaging: 1.0 L, 5.0 L.

Colour: blue

Density: -

Odour: Product-specific

Application:





tyres and external components made of unpainted plastics, seals in doors, boot lids and engine covers, side mouldings and bumpers. Facilitates the fitting of rubber hoses and cable harnesses. When used regularly, it maintains the elasticity of seals, reduces friction when opening and closing doors, and prevents seals from freezing in cold weather.

Directions for use:





Apply the product evenly to previously cleaned surfaces using a sponge or microfibre cloth. Leave to evaporate for approximately 10 minutes. Depending on the thickness of the applied layer, it leaves the surface with a matt finish (thin layer) or a gloss finish (thicker layer).

Restrictions: Do not apply to surfaces that should not be slippery (steering wheel, pedals, rubber mats).


The above information is based on our current knowledge of our products and their possible applications. It does not guarantee specific properties or suitability for use under particular conditions. Please follow the instructions and warnings on the product labels and contained in the safety data sheet. We accept no liability if the final result of the work was influenced by factors beyond our control.

TECHNICAL INFORMATION

Product name: APP GM Care
Silicone-based product for the care of tyres and exterior plastics

Cleaning of equipment: in organic solvents.

Storage: store in sealed original containers in a dry and well-ventilated room.



Protect from freezing.

Health and safety regulations: for professional use only.
See: the text on the product labels or in the safety data sheet.
The user must comply with the health and safety regulations in force in their country.



The above information is based on our current knowledge of our products and their possible applications. It does not guarantee specific properties or suitability for use under particular conditions. Please follow the instructions and warnings on the product labels and contained in the safety data sheet. We accept no liability if the final result of the work was influenced by factors beyond our control.