

SPECIFICATIONS

Prepared on:
July 18, 2007




Updated on:
July 18, 2007

Page 1 of 2

Product name: GM Care

A preparation for the maintenance of tyres and plastic elements.

<u>Container:</u>	5.0 l
<u>Basic components:</u>	Aliphatic hydrocarbons
<u>pH:</u>	-
<u>Colour:</u>	Pink
<u>Density:</u>	-
<u>Smell:</u>	Specialised in the product
<u>Usage:</u>	Tyres and external car elements made of non-lacquered plastics, door and trunk lid seals, garnish strips and bumpers. The preparation makes it easier to fasten rubber hoses and cable bunches. When used regularly, it ensures the elasticity of seals/gaskets, reduces door opening and closing friction, and limits the freezing of seals in wintertime.



Directions for use:



Spread the preparation evenly over previously cleaned surfaces using a sponge or microfibre cloth. Leave for 10 minutes until it evaporates. Depending on the thickness of the applied layer, the product leaves a mat surface (thin layer), or makes it glossy (thicker layer).

The above information complies with the current knowledge on our products and their possible applications. This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect the final result of work.

**Auto Plast Produkt Sp. z o.o. [Ltd.] 62-300 Września, ul. Przemysłowa 10, Poland
tel. + 48(prf)61 437 00 00**

SPECIFICATIONS

Prepared on:
July 18, 2007



Updated on:
July 18, 2007


Page 2 of 2

Product name: GM Care

Constraints: Do not apply onto surfaces, which should not be slippery (steering wheel, pedals, rubber mats).

Equipment cleaning: Inorganic solvents.

Storage:



Store in original, closed containers in a dry and well-ventilated room. Protect against freezing.

Industrial safety regulations:



For professional use only.
See: information on product labels and/or in Hazardous Material Safety Data Sheet.
Users should observe all industrial safety regulations applicable in their countries.

Hazards:

See Material Safety Data Sheet



R10 Flammable.
R65 Harmful: May cause lung damage if swallowed.
R66 Repeated exposure may cause dry and cracked skin.
R67 Vapours may cause drowsiness and dizziness.
S2 Keep out of the reach of children.
S16 Keep away from sources of ignition - do not smoke.
S23 Do not breathe in vapour and sprayed liquid.
S24 Avoid contact with skin.
S43 In case of fire use sand, earth, dry powder or foam. Never use water.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

The above information complies with the current knowledge on our products and their possible applications. This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect final result of work.

Auto Plast Produkt Sp. z o.o. [Ltd.] 62-300 Września, ul. Przemysłowa 10, Poland
tel. + 48(prf)61 437 00 00