

# TECHNICAL INFORMATION

Elaboration date: 27.07.2023



Update date: 27.07.2023

Page 1 of 2

**Product name: Leather primer,  
APP for AD Leather Primer — priming preparation for leathers.  
APP No.: 220967.**

Adhesion enhancer, improving adhesion of base coats to leather. Especially recommended for greasy and hydrophobic leathers. It evens out leather surfaces before lacquering. Does not harden leather surfaces. It does not have a negative impact on the water resistance of leathers.

Packaging: 200 ml

Product and accessories: APP for AD Leather Primer can be used as a primer for APP for AD Leather Color.

Key ingredients: Polyurethane resin.

Colour: Transparent to yellow

Application: As an adhesive coat, particularly on oily and hydrophobic leathers. Applied by spraying a thin layer, it smooths out surface irregularities. Thicker layers are not recommended due to the weakening of adhesion.

Properties: Improves the adhesion of lacquers to leather. It does not harden the leather itself. It levels the unevenness of the leather surface. Does not reduce the water resistance of leathers.

Benefits: Increases the adhesion of lacquers to leather surfaces. It imparts a subtle evenness to leather. Allows colouring of leathers with a difficult adhesion surface (greasy and strongly water-repellent). Can be used as an additive (5–10%) to APP for AD Leather Color to increase adhesion.

Usage

Mixing ratio: Ready-to-use agent.

Surface preparation: Before priming, the surface must be clean, degreased and dry.

Application method: With a small spray gun (0.8–1.0 nozzle) at low pressure (up to approx. 2 bar) or with an airbrush or a brush. Best applied in one thin layer. A thicker layer or more layers can cause weakened

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Observe the notes and warnings on the product labels and in the safety data sheet. We do not accept any responsibility if the final result of the work is influenced by factors beyond our control.

# TECHNICAL INFORMATION

Elaboration date: 27.07.2023



Update date: 27.07.2023

Page 2 of 2


**Product name: Leather primer,  
APP for AD Leather Primer — priming preparation for leathers.  
APP No.: 220967.**

adhesion.

Curing: Drying time: 5 minutes at 20°C. The process can be gently accelerated by blowing dry, warm air.

Equipment cleaning: Running lukewarm water.

## Storage



Store in closed original packaging in a dry and well-ventilated room and at a temperature of +5°C to +30°C. Protect from direct sunlight.

## Health and safety regulations



See text on product labels or in the material safety data sheet. Users must comply with health and safety regulations in force in respective countries.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Observe the notes and warnings on the product labels and in the safety data sheet. We do not accept any responsibility if the final result of the work is influenced by factors beyond our control.