

TECHNICAL INFORMATION

Preparation date: 10/10/2024



Revision date: 10/10/2024

Page 1 of 2

**Product name: Impregnating preparation for fabrics and convertible tops,
APP for AD Fabric Coat.
APP No: 223030.**

APP for AD Fabric Coat is a safe and highly effective impregnating preparation for fabrics and convertible tops. Penetrates deep into the structure of the material. Its hydrophobic properties prevent the material from becoming soaked. Protects the impregnated material from dirt and UV radiation. Slows down the ageing process of the protected material.

Packaging:	500 ml
Colour:	Transparent
<u>Intended use:</u>	Impregnation and periodic maintenance of convertible tops and fabrics.
<u>Properties:</u>	The preparation creates a thin film around the fibres of the materials, reducing the possibility of water and dirt penetration.
<u>Benefits:</u>	Forms a layer on the surface that impedes water penetration. Reduces the uptake of dirt on the surface. Protects against the harmful effects of UV radiation. Prolongs the life and improves durability of the protected material.
<u>Application</u>	
Mixing ratio	Ready-to-use product.
Efficiency	10 to 100 ml of the preparation per 1 sq. m., depending on the absorbency of the treated material surface.
Surface preparation	The surface must be properly cleaned, washed and rinsed and thoroughly dried before application.
Directions for use	Shake well before use. Spray directly onto the treated surface. Cover the material generously and evenly with the preparation. Moisture (dew) film should be visible on the surface. Rub in / massage in the product to increase the treated material penetration depth. Leave it to dry. The correct application and drying temperature is between 18 and 25 degrees Celsius. At temperatures above 25 degrees, apply within smaller areas. Do not apply at temperatures below 10 degrees Celsius.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. The notes and warnings on the product labels and on the safety data sheet should be adhered to. We do not bear any responsibility if the final result of the work was influenced by factors beyond our control.

TECHNICAL INFORMATION

Preparation date: 10/10/2024



Revision date: 10/10/2024


Page 2 of 2

**Product name: Impregnating preparation for fabrics and convertible tops,
APP for AD Fabric Coat.
APP No: 223030.**

Drying The impregnated surface can be used 60 minutes after applying the product. The correct drying temperature is between 18 and 25 degrees Celsius with relative humidity below 45%.

Equipment cleaning Lukewarm, running water.

Storage



Store in closed original packaging in a dry and well-ventilated room and at a temperature of +5°C to +30°C. Protect from direct sunlight.

OHS regulations



See the text on product labels or in the MSDS.
Comply with the OHS regulations in force in the country concerned.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. The notes and warnings on the product labels and on the safety data sheet should be adhered to. We do not bear any responsibility if the final result of the work was influenced by factors beyond our control.