

TECHNICAL INFORMATION

Date drafted: 19.09.2023r.



Date updated: 19.09.2023r.

Page 1 of 2

Product name: white dust-absorbing cloth. APP Tack Cloth white. APP No.: 250505.

Dust-absorbing cloth designed to clean surfaces of dust or dried base coat dust during touch-up painting and in many industrial applications before spray painting.

Packaging. 50cm x 75cm cloths individually packed in plastic bags. The cardboard dispenser, which is a bulk package, contains 10 unit packs.

Basic ingredients. A 100% polyester gauze with an open structure impregnated throughout with a synthetic binder.

Colour. White.

Specific weight. 40.64 g/m² ± 5% (DIN EN ISO 9073-1)

Tear Strength (MD). >30 N/m (EN13934-1)

Tear Strength (CD). >20 N/m (EN13934-1)

Elongation at Break (MD) <10 % (EN 13934-1)

Elongation at Break (CD) <15 % (EN 13934-1)

Application

- Designed to clean the surface of dust and dried base coat dust during touch-up painting.
- In many industrial applications prior to priming and spray painting.
- Designed to remove dust after dry sanding cataphoresis, primers and undercoats.
- For removing dust after long-term storage.

Advantages

- The cloth does not leave adhesive on the surface to be cleaned.
- Its open structure allows for better dust adhesion providing greater dust capacity.
- Minimal adhesive transfer to the hand.
- Mechanically durable polyester fibres.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.

TECHNICAL INFORMATION

Date drafted: 19.09.2023r.



Date updated: 19.09.2023r.

Page 2 of 2

**Product name: white dust-absorbing cloth.
APP Tack Cloth white. APP No.: 250505.**

Substrate

Surface dusted off with compressed air and degreased with APP W900, APP W911, APP WB910 or APP WK900 lacquer remover. Dry basecoat surface.


Application

After removing the cloth from its packaging, fold it into a soft and comfortable swab. Gently wipe the surface without excessive force. When the used surface of the cloth gets dirty with dust, fold it to use a new, clean surface. Repeat this procedure until the cloth is completely soiled. Once completely contaminated, the dust-absorbing cloth is not suitable for reuse because it will lose its ability to absorb dust.

Note!

- The use of excessive force can cause the cloth to leave residues such as binder or fibre pieces on the surface to be cleaned.
- For optimum performance, we recommend conditioning the cloths in the workplace at +18°C to +25°C for 2 hours before use.

Storage



Store in closed original packaging in a dry and well-ventilated room and at a temperature of +5°C to +45°C. Protect from freezing.

OHS regulations



See text on product labels or SDS.

The user must comply with the OHS regulations in force in the country concerned.

The above information is in line with the current state of knowledge of our products and their possible applications. This does not guarantee specific properties or suitability for use under specific conditions. Follow the notes and warnings on the product labels and on the safety data sheet. We assume no liability if the final result of the work was influenced by factors beyond our control.