



- **Two-component matte clear coat**
APP 2K HS Acryl Klarlack Matt 2:1
APP Nr 020180

The APP Acryl Klarlack Matt is a versatile varnish dedicated for patch repairs as well as for repairs on complete car parts as a clear topcoat with a lacklustre finish in multilayer restoration techniques on vehicle bodies.

It is possible to achieve the precise desired gloss level by mixing APP Acryl Klarlack Matt with high-gloss varnishes such as APP Classic or APP Spezial S.

The matte topcoat varnish APP Acryl Klarlack Matt is to be used only with hardeners for clear varnishes APP Classic or Spezial S, both the fast-drying as well as the standard type; mixing ration is 2:1.

Varnish thinner can be used if necessary: the recommended product is APP Acryl Verdünnung, used at a mixing ratio of up to 5%.

NB: the gloss level is affected by factors such as the amount of varnish thinner used, the total dry coat thickness and the number of layers.

The matte varnish can be used with conventional as well as waterborne basecoats. It is exceptionally resilient as well as weather-resistant. The light-fastness of the base varnish is guaranteed thanks to the addition of UV filters.



Related products



APP Nr	Packaging unit	Packaging size	Bulk packaging
020180	can	1 l	6 pcs.

The correct dosage of individual mixture components is of utmost importance in order for the desired gloss level to be obtained.

Gloss level	Gloss [%] (^ 60°)	APP 2K HS Acryl Klarlack Matt	Matting additive APP Modular 2K Acryl Line 50-95	APP 2K HS Acryl Klarlack Spezial S	APP 2K HS Spezial S Harter XLHN/ XLHS	APP 2K Acryl Verdünnung AVN/AVS	APP 2K HS Acryl Klarlack Classic	APP 2K HS Classic Harter XLHN/XLHS	APP 2K Acryl Verdünnung AVN/AVS
Semi-gloss	50-75	80	0	20	50	0	20	50	0-5
Satin	30-50	90	0	10	50	0	10	50	0-5
Semi-matte	20-30	95	0	5	50	0	5	50	0-5
Matte	10-20	100	0	0	50	0	0	50	0-5
Super-matte	< 10	95	5	0	50	0	0	50	0-5