



• **APP WS 222/WSR 222**

Abrasive Pad

APP WS 222 is an abrasive pad that features with open 3D structure of resin saturated Nylon fibres and spray coated high quality abrasive.

Abrasive Pad APP WS 222 is a perfect substitute of traditional abrasives. It is easy and comfortable to use. Moreover it speeds up works related to preparation of surface (shading). Use along with **APP PM 07** Dulling Paste ensures very good work results. Abrasive pad is purposed for mechanical and manual preparation, as well as surface machining.

BENEFITS:

- Open 3D structure prevents clogging and extends service life of abrasive pad;
- Provides uniform sanding on whole surface;
- Does not deform the surface;
- For dry or wet sanding.
- High elasticity ensures comfort of work on any shape and hard to reach to places;





EN

Perforation enables to use the box as a display

Colour and quantity identification

Grain grade scale

Sheets and rolls protected with shrink film and clamp preventing unrolling.

RELATED PRODUCTS

APP PM 07
APP Nr 081210

NTools WM GLV
APP Nr 170112

USE OF ABRASIVE PAD

Coarse (Grit 240-280)

- Dulling of steel elements before priming;
- Dulling of old coats and paints;
- During preparation works when combining (soldering) copper pipes;
- Cleaning of aluminium, copper, steel, stainless steel.

Medium (Grit 320-360)

- Preparation of surface (dulling) before application of base coat.
- Preparation of plastics and Polyester laminated materials;
- Dulling of brand new elements (cataphoresis)
- During preparation works when combining (soldering) copper pipes.

Fine (Grit 600-800)

- Recommended for use along with dulling pasta when preparing the surface for shading;
- Dulling of base coat and top coats;
- Dulling of plastics and Polyester laminated materials;
- Preparation of surface before application of top coat;
- SMART repairs.

Micro (Grit 1000-1200)

- Recommended for use along with dulling pasta when preparing the surface for shading (some colours e.g. silver, golden);
- Preparation of transition between clear topcoat during works related to touch-up;
- Dulling of top coat;
- SMART repairs;
- Dulling of plastics;
- Cleaning of aluminium, copper, steel and stainless steel.




COMPARISON APP WS 222 against APP WS

- Efficiency improved by ca.20%

- Dense structure, improved mechanical resistance

- Improved flexibility ensures comfort of work on any shape and hard to reach places.

- Uniform surface and double-sided abrasive grit coating ensures consistent sanding on whole surface.



APP No.	Name	Format	Size	Type	Grit	Grit Typ	Thickness	Pack
06Z200	APP WS 222 - Abrasive Pad	Sheet	150 x 230 mm	Coarse	240-280	Aluminium oxide	8 mm	10 pcs.
06Z210	APP WS 222 - Abrasive Pad	Sheet	150 x 230 mm	Medium	320-360	Aluminium oxide	8 mm	10 pcs.
06Z220	APP WS 222 - Abrasive Pad	Sheet	150 x 230 mm	Fine	600-800	Silicon carbide	8 mm	10 pcs.
06Z230	APP WS 222 - Abrasive Pad	Sheet	150 x 230 mm	Micro	1000-1200	Aluminium oxide	8 mm	10 pcs.
06ZR200	APP WSR 222 - Abrasive Pad	Roll	100 mm x 10 m	Coarse	240-280	Aluminium oxide	8 mm	1 pc.
06ZR210	APP WSR 222 - Abrasive Pad	Roll	100 mm x 10 m	Medium	320-360	Aluminium oxide	8 mm	1 pc.
06ZR220	APP WSR 222 - Abrasive Pad	Roll	100 mm x 10 m	Fine	600-800	Silicon carbide	8 mm	1 pc.
06ZR230	APP WSR 222 - Abrasive Pad	Roll	100 mm x 10 m	Micro	1000-1200	Aluminium oxide	8 mm	1 pc.