

NTools ROS 02E / ROS 05E


Power Random Orbital Sander

APP No. 125002

APP No. 125005

High quality brushless electric random orbital sander for professional use provided with powerful engine with 2,5 mm, 5 mm stroke that ensures stable rotational speed also under significant load.

Low noise level and vibration as well as rotational speed control ensure optimum work results.



FEATURES:



Powerful engine **350W** that ensures maximum stability and control during operation.



Rotary –orbital operation with 5mm stroke for improved performance during grinding that ensures perfect finish.



Electronic speed control system with soft start ensures smooth operation, rotational speed within range 4000 to 10000 RPM.



Conformance with European Standards confirmed with CE mark.

APP Sp. z o.o.

ul. Przemysłowa 10, 62-300 Września
Biuro Obsługi Klienta: tel. +48 61 437 00 20, bok@app.com.pl

www.APP.com.pl

09.10.2020

Design:

NTools

1 Robust and ergonomic body

Small size and ergonomic body that ensures comfort of work with one hand also and perfectly balanced body decreases significantly vibration

2 Switch lever

Ergonomic lever switch on the top of body that ensures easy switching on and off

4 Silicone power cord

Flexible Silicone cord 5 m long that offers more freedom of movement during delivery of works.

3 Rotational speed control

7-level 4000-10000 RPM (electronic module with display)

5 Partly rubberized handle

Improved grip ensures comfort during work

6 All-purpose backing disk

Multi-hole backing disk dia 150 with Velcro ensures efficient and smooth work with abrasive disks provided with with universal hole pattern 15+1/16+1 (APP, Ntools, Quartz, Festool, 3M etc.)

7 Dust extraction system

fitted with NTools universal joint ADO 50 (600012ND) for spiral suction hoses with outer diameters $\varnothing 23$, $\varnothing 32$, $\varnothing 34$, $\varnothing 38$ and $\varnothing 50$ mm




1 5




2



3



4



6



7



Technical Data:



APP No. 125002 / APP No. 125005

ROS 02E / ROS 05E


Power Random Orbital Sander



Conformance with the following Directives:

*Machinery Directive 2006/42/EC,
Low Voltage Directive 2014/35/EC,
EMC Directive 2014/30/EC
ROHS Directive 2011/65/EC*

WIDE RANGE OF APPLICATIONS THANKS TO POWERFUL ENGINE AND 7 LEVEL ROTATIONAL SPEED CONTROL WITHIN RANGE:
FROM 4000 RPM (4 ITEM ON DISPLAY)
TO 10000 RPM (MARKED A ON DISPLAY)



PURPOSE:

- Sanding of top coat, filler, base coat, wood finish materials,
- Preparation of surface before application of top coat, base coat, impregnate
- Finish sanding and preparation before polishing

TECHNICAL DATA:

Power supply input	220-240 V ~50-60 Hz	Dust extraction	Yes
RPM	350W	Soft start	Yes
Rotational control	4000-10000 RPM	Power cord length	5 m
Stroke	YES (electronic panel with display)	Mass	1,4 kg
Backing disk	2,5 mm; 5 mm		
	Ø 150 mm, 8+8/6+1 otworów, gwint 5/16", rzep		

INDUSTRY

AUTOMOTIVE	FURNITURE	BOAT BUILDING	WOODWORKING AND METAL INDUSTRY
			

ADVANTAGES



Robust body

Light weight and robust plastic body provided with partly rubberized handle improves grip.



Soft start

Soft start ensures work comfort, improves control over the tool and reduces engine wear.



Low vibration

Precise balancing ensures low vibration.



Dust extraction system

Compatible with external dust extraction system.



Electronic speed control

7-level smooth rotational speed control in range from 4000 to 10000 RPM along with electronic module for stable rotation ensure smooth operation and high quality of surface.



All-purpose backing disk

All-purpose multi-hole backing disk with Velcro ensures efficient and reliable operation of abrasive disks provided with 8+6+1 holes (e.g. Quartz, HMF7) or 8+8+1 holes (e.g. Festool, Makita).

NTools ROS 02E / 05E

Power Sander

Each sander features with
UNIQUE SERIAL NUMBER
UNIQUE SERIAL NUMBER



Serial Number is also indicated in the Guarantee Card on the last page of User Manual and on the cardboard.



SET INCLUDES:

- Power Random Orbital Sander with backing disk Ø 150 mm,
- Dust extraction tube connector,
- Backing disk Allen key,
- User Manual.



CAUTION!

Power Random Orbital Sander NTools ROS 02E/05E offers the same performance as the following brushless sanders: Mirka DEROS 650CV, Festool ETS EC 150/5, Rupes SKORPIO E.



NTools

APP No.	Product Description	Power	Stroke	RPM	Qty
125002	NTools ROS 02E Power Random Orbital Sander	350 W	2,5 mm	4000-10000	1
125005	NTools ROS 05E Power Random Orbital Sander		5,0 mm		1

NTools SPM 150 15/17HU M

Backing Disk

SPM 150 15/17HU M



ø 150 mm [6"]
Holes (8+8/6+1)
Thread 5/16"

NTools nr
150575

CAUTION:
Edge of pad may
tear if run against
sharp edges. Do not
use if pad is torn.

Always wear
eye, face and
body protection

Max. speed 12 000 RPM

SET INCLUDES:

A spacer for adjustment of a gap between the disk and the disk brake.

All-purpose multi-hole Velcro backing disk NTools SPM 150 15/17HU M is compatible with abrasive disks provided with 8+6+1 holes and 8+8+1 holes. It is also compatible with abrasive disks provided with 8+6+1 (e.g. APP, NTools, QUARTZ) and 8+8+1 holes (e.g. Festool, Makita).

- Made from hard foam PU 10 mm thick, with 5/16" threaded rivetted screw is compatible with NTools ROS 02E/05E sander (original) and is substitute for NTools RS 150 as well as AS 150 and Mirka Deros.
- All-purpose, multi-hole compatible with Velcro abrasive disks dia. 150 mm and provided with 8+6+1 holes (e.g. Quartz, HMF7) or 8+8+1 holes (e.g. Festool, Makita).
- Thin, profession Velcro ensures adherence of abrasive disks, precise sanding and perfect surface finish.

**THIN VELCRO
FOR PROFESSIONAL
USE**

APP No.	Product Description	Diameter	Fixing	Holes	Thread	Qty
150575	NTools SPM 150 15/17HU M Backing Disk	150 mm	Velcro	8+8/6+1	5/16"	1

APP Sp. z o.o.

ul. Przemysłowa 10, 62-300 Września
Customer Service Department: Phone +48 61 437 00 20, bok@app.com.pl

www.APP.com.pl

09.10.2020