

PNEUMATIC SANDERS NTools RS 15025/RS15050/RS 15080 APP Nr 135025/135050/135080

They are designed for continuous operation in industry and trade. They combine high power, high efficiency of sanding with low weight. Sanders can satisfy the most demanding customer.

5.0 mm pitch is ideal for fine sanding,

APP Nr 135025

RS 15025

2.5 mm pitch is ideal for finishing. Small pitch combined with high RPM gives the best quality of surface finish sanding. Proposed sandpaper gradations from P320 to P3000.

APP Nr135080

RS 15080

8.0 mm pitch allows for a significant reduction in working hours. Aggressive movement of the disk is ideal for rough sanding and fast removal of material. The proposed gradation is from P60 to P180.

APP Nr 135050

RS 15050

so as to prepare the substrate for the painting work. The proposed gradation is from P180 to P400.

Set:

- WORKING DISKS DS 15050HM
- Oil PNT 30
- Wrench

APP Nr	135025 (RS 15025)	135050 (RS 15050)	135080 (RS 15080)
RPM	0 - 12000	0 - 12000	0 - 12000
AIR CONSUMPTION	450 l/min	450 l/min	450 l/min
POWER	0,28 hp / 209 W	0,28 hp / 209 W	0,28 hp / 209 W
PITCH	2.5 mm	5.0 mm	8.0 mm
SUCTION	YES	YES	YES
DISK MOUNTING	5/16"	5/16"	5/16"



ul. Przemysłowa 10, 62-300 Września

Biuro Obsługi Klienta: tel. 061/437 00 20, fax 061/437 00 21

