

NTools TR 1501517U

Backing Disk compatible with SWR 03E/05E



APP Sp. z o.o.

ul. Przemysłowa 10, 62-300 Września Customer Service Department: Phone +48 61 437 00 20, bok@app.com.pl

www.APP.com.pl







13.09.2019







Power Random Orbital Sander

APP No. 127003, 127005

High quality electric random orbital sander for professional use provided with powerful engine that ensures stable rotational speed also under significant load.

Compact and precisely balanced body ensures low noise level and vibration to provide comfort during work.



FEATURES:



Powerful engine **400W** seated on vertical shaft to ensure maximum stability and control during operation.



Rotary —orbital operation with 3mm or 5mm stroke of improved performance during grinding that ensures perfect finish.



Multi-function electronic system that ensures smooth start, rotational speed control and stable disk operation.



Conformance with European Standards confirmed with CF mark

APP Sp. z o.o. ul. Przemysłowa 10, 62-300 Września Customer Service Department: Phone +48 61 437 00 20 bok@app.com.pl



f in EN



Power Sander

Design:



1 Robust and ergonomic body

Perfectly balanced body that decreases vibration and enables work for extended time without operator fatigue.

2 Rotational speed 6-level control

Smooth rotational speed control within range of 4000-10000 RPM and electronic module maintain stable rotational speed also under load.

3 Backing disk brake

Ensures safe disk stop after work finish.

All-purpose backing disk

Multi-hole backing disk dia. Ø150 with Velcro ensures efficient and smooth work with abrasive disks provided with 8+6+1 or 8+8+1 holes

(Ntools, Quartz Festool, 3M etc.),



5 Partly rubberized handle

> Improved grip ensures comfort during work.

6 Silicone power cord Flexible 5m long cord.

7 Switch with lock Ensures continual

operation without pressing the trigger.

8 Dust extraction system

Connector dedicated for independent dust extraction system to ensure clean air and good vision during work.



APP Sp. z o.o.

ul. Przemysłowa 10, 62-300 Września Customer Service Department: Phone +48 61 437 00 20, bok@app.com.pl









Power Sander

Comparative Analysis:



Certified acc to.:

Machinery Directive 2006/42/EC. Low Voltage Directive LVD 2006/95/EC, EMC Directive 2014/30/EC,

and EN Standards:

EN 60745-1: 2009 + A11: 2010 EN 60745-2-4: 2009 + A11: 2011

NTools No. 127003 SWR 03E Power Random Orbital Sander

NTools No. 127005 SWR 05E Power Random Orbital Sander





PURPOSE

SANDING OF TOP COAT, FILLER, BASE COAT, WOOD FINISH MATERIALS, **GLASS FIBRE AND GEL COAT**

PREPARATION OF SURFACE BEFORE APPLICATION OF TOP COAT, **BASE COAT, IMPREGNANT**

> **FINISH SANDING** AND PREPARATION BEFORE POLISHING

| Excellent work effects preparation |
|------------------------------------|
| before polishing |

Preparation of surface before painting

TECHNICAL DATA:

| Power supply | 220-240 V ~50-60 Hz | 220-240 V ~50-60 Hz | |
|--------------------|--|--|--|
| Power input | 400W | 400W | |
| RPM | 4000-10000 RPM | 4000-10000 RPM | |
| Rotational control | YES | YES | |
| Stroke | 3 mm | 5 mm | |
| Backing disk | Ø150 mm, 8+8/6+1 holes, M8 thread (key hex), Velcro | Ø150 mm, 8+8/6+1 holes, M8 thread (key hex), Velcro | |
| Dust extraction | YES | YES | |
| Soft start | YES | YES | |
| Power cord length | 5 m | 5 m | |
| Mass | 1,6 kg | 1,6 kg | |

| USE | | | | | | | |
|------------|-----------|--------------|-----------------------------------|------------------|--|--|--|
| AUTOMOTIVE | FURNITURE | BOATBUILDING | WOODWORKING AND METAL INDUSTRY | SANITARY TAPWARE | | | |
| | | | | 불급 | | | |

APP Sp. z o.o.

ul. Przemysłowa 10, 62-300 Września Customer Service Department: Phone +48 61 437 00 20, bok@app.com.pl

f ► Ø in EN





13.09.2019





Power Sander



ADVANTAGES



ROBUST AND ERGONOMIC BODY

Light weight and robust plastic body provided with partly rubberized handle improves grip.



SOFT START

Soft start ensures work comfort, improves control over the tool and reduces engine wear.



LOW **VIBRATION**

Precise balancing ensure low vibration



DUST EXTRACTION SYSTEM

Compatible with external dust extraction system.



ELECTRONIC SPEED CONTROL

6-level smooth rotational speed control in range from 4000 to 10000 RPM along with electronic module for stable rotation ensure smooth operation and high quality of surface



ALL-PURPOSE BACKING DISKS

All-purpose multi-hole backing disk with Velcro ensures efficient and reliable operation of abrasive disks provided with 8+8+1 and 8+6+1 holes (NTools, Quartz, Festool, 3M, etc.)



CAUTION!

NTools SWR 03E and NTools SWR 05E Power Random Orbital Sander is a counterpart of Rupes ER 03TE and Rupes ER 05TE sander as well as Festool ETS 150/3 EQ and Festool 150/5 EQ sander.



| APP No. | Product Name | Power | Stroke | Qty |
|---------|--|-------|--------|-----|
| 127003 | Power Random Orbital Sander NTools SWR 03E | 400W | 3mm | 1 |
| 127005 | Power Random Orbital Sander NTools SWR 05E | 400W | 5mm | 1 |

APP Sp. z o.o.

Customer Service Department: Phone +48 61 437 00 20, bok@app.com.pl









13.09.2019

