

Date of issue: 2015-11-30 APP Fiber 140 ml, 420ml, 1200 ml

Page 1 z 7

# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product Identifier

Trade name: APP Fiber 140ml, 420ml, 1200ml

Trade code: 010210, 010211, 010212

# 1.2. Relevant identified uses of the substance/mixture and uses advised against

Filler.

# 1.3. Details of the supplier of the safety data sheet

Company: APP Sp. z o. o.

ul. Przemysłowa 10, 62 – 300 Września

Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: app@app.com.pl

Strona WEB: www.app.com.pl

Safety Data Sheet e-mail: Tomasz Golda, t.golda@app.com.pl

#### 1.4. Emergency telephone number:

+48 (61) 437 00 00

**Date of issue:** 2015-11-30

#### **SECTION 2. HAZARDS IDENTIFICATION**

# 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02



GHS07



GHS08

**Danger** 

FlamLiq3: H226 Flammable liquid and vapour. SkinIrrit2: H315 Causes skin irritation.

EyeIrrit2: H319 Causes serious eye irritation

Repr2: H361d Suspected of damaging the unborn child.

STOT RE2: H372 Causes damage to organs through prolonged or repeated exposure through prolonged or

repeated exposure - hear apparatus.

2.2. Label elements

Labelling according Regulation (EC) No 1272/2008

Styrene

Signal word:



Date of issue: 2015-11-30 APP Fiber 140 ml, 420ml, 1200 ml

Page 2 z 7

Danger

# Pictogram:



GHS02



GHS07



GHS08

## **Hazard statement(s)**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure through prolonged or repeated exposure - hear apparatus.

# **Precautionary statement(s)**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container according to local/regional/national/international regulations.

# 2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

UN: 3269

VOC (2004/42/EC, IIc: 250) <249 g/l

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:



Date of issue: 2015-11-30 APP Fiber 140 ml, 420ml, 1200 ml

Page 3 z 7

Name	Conc.	CAS No	Index No	EC No	Classification:
<b>Styrene</b> REACH Reg No 01-2119457861-32	12,5-<20 %	100-42-5	601-026-00-0	202-851-5	R10 Xn: R63; R20; R48/20; Xi: R36/38 GHS02; GHS07; GHS08 Wng Flam.Liq.3: H226 STOT RE1: H372 Repr2: H361d AcuteTox4: H332 SkinIrrit2: H315 EyeIrrit2: H319

Full text of R-Phrases and H-Phrases can be found under heading 16

#### **SECTION 4. FIRST AID MEASURES**

#### 4.1. Description of first aid measures

#### In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. In case of irritation, consult a doctor

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

#### In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

#### In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

#### 4.2. Most important symptoms and effects, both acute and delayed:

Suspected of damaging the unborn child.

Causes damage to organs through prolonged or repeated exposure through prolonged or repeated exposure - hear apparatus.

# 4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

#### **Treatment:**

None

# **SECTION 5. FIRE-FIGHTING MEASURES**

# 5.1. Extinguishing media

#### Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

#### Extinguishing media which must not be used for safety reasons:

Water jet.

## 5.2. Special hazards arising from the substance or mixture

Flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

# 5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.



Date of issue: 2015-11-30 APP Fiber 140 ml, 420ml, 1200 ml

Page 4 z 7

See protective measures under point  $\overline{7}$  and  $\overline{8}$ .

# 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

# 6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

#### 6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

## **SECTION 7. HANDLING AND STORAGE**

# 7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

# 7.3. Specific end use(s)

None.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1. Control parameters

N.A.

# 8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

Nitrile gloves.

Respiratory protection:

Respiratory protection.

Thermal Hazards:

None

Environmental exposure controls:

None

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties

Appearance and colour: liquid, colour according to the label

Odour: characteristic Odour threshold: N.D.

pH: N.A.

Melting point / freezing point: N.D.

Initial boiling point and boiling range: 145°C



Date of issue: 2015-11-30 APP Fiber 140 ml, 420ml, 1200 ml

Page 5 z 7

Upper/lower flammability or explosive limits: 1.2-8.9%

Vapour density: N.D. Flash point: 31°C Evaporation rate: N.A.

Vapour pressure: 6 hPa (20°C) Density: 2160 kg/m³ (15°C) Solubility in water: insoluble

Solubility in organic solvents: soluble in aromatic solvents

Lipid solubility: N.A.

Partition coefficient (n-octanol/water): N.A.

Ignition temperature: N.D.

Auto-ignition temperature: 480°C Decomposition temperature: N.A.

Viscosity dyn.: N.D.

Viscosity kin.: 90 s (DIN 5321/4)

Explosive properties: can form an explisive mixture in air

Oxidizing properties: not oxidizing

**9.2. Other information** VOC: <249 g/l

## SECTION 10. STABILITY AND REACTIVITY

#### 10.1. Reactivity

Mixture is not reactive.

#### 10.2. Chemical stability

Stable under normal conditions of handling and storage.

## 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

- solar radiation
- sparks
- flame
- heat

# 10.5. Incompatible materials

- strong acids
- oxides and reductors

# 10.6. Hazardous decomposition products

None.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### 11.1. Information on toxicological effects

Causes skin irritation.

Causes serious eye irritation

Suspected of damaging the unborn child.

Causes damage to organs through prolonged or repeated exposure through prolonged or repeated exposure - hear apparatus.

a) acute toxicity: no hazard

b) skin corrosion/irritation: skin irritation.

c) serious eye damage/irritation: Causes serious eye irritation

d) respiratory or skin sensitization: No hazard

e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard

g) reproductive toxicity: no hazard h) STOT-single exposure: no hazard

i) STOT-repeated exposure: Causes damage to organs through prolonged or repeated exposure through prolonged or

repeated exposure - hear apparatus. **j) aspiration hazard:** NO hazard

Styrene

 LD50 (rat, ingestion)
 2650 mg/kg

 LC50 (rat, inhalation):
 11,8 mg/m3/4 h

 LD50 (rabbit, skin):
 2000 mg/kg

# **SECTION 12. ECOLOGICAL INFORMATION**



Date of issue: 2015-11-30 APP Fiber 140 ml, 420ml, 1200 ml

Page 6 z 7

#### 12.1. Toxicity

Mixture is not classified as hazardous.

12.2. Persistence and degradability

No data

12.3. Bioaccumulative potential

No data.

12.4. Mobility in soil

No data

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

## 13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

#### **SECTION 14. TRANSPORT INFORMATION**

#### 14.1. UN number

3269

#### 14.2. UN proper shipping name

Polyester resin kit.

## 14.3. Transport hazard class(es)

3

## 14.4. Packing Group

Ш

#### 14.5. Environmental hazards

Nο

#### 14.6. Special Precautions for User

During handling wear personal protection equipment (see Section 8)

Avoid heat and flame.

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

N.A.

## **SECTION 15. REGULATORY INFORMATION**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

#### Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

# 15.2. Chemical Safety Assessment

No

## **SECTION 16. OTHER INFORMATION**

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H332 Harmful if inhaled

H315 Causes skin irritation.

H319 Causes serious eye irritation

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure through prolonged or repeated exposure - hear apparatus.

R10 Flammable



Date of issue: 2015-11-30 APP Fiber 140 ml, 420ml, 1200 ml

Page 7 z 7

R20Harmful by inhalation.

R36/38 Irritating to eyes and skin

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

R63 Possible risk of harm to the unborn child

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.