



Date of issue: 2016-09-11

**2K KLARLACK FD Spray** 

Page 1 z 8

### SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

**1.1. Product Identifier** 

Trade name: 2K KLARLACK FD Spray Trade code: 020120

1.2. Relevant identified uses of the substance/mixture and uses advised against Two-component lacquer.

1.3. Details of the supplier of the safety data sheet **Company:** 

APP Sp. z o. o. ul. Przemysłowa 10, 62 - 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: app@app.com.pl Strona WEB: www.app.com.pl

Safety Data Sheet e-mail: Tomasz Golda, t.golda@app.com.pl

1.4. Emergency telephone number: +48 (61) 437 00 00

Date of issue: 2016-09-11

# SECTION 2. HAZARDS IDENTIFICATION

# 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Dgr H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H317 May cause an allergic skin reaction H319 Causes serious eye irritation H336 May cause drowsiness or dizziness EUH204 Contains isocyanates. May produce an allergic reaction. **2.2. Label elements** Labelling according Regulation (EC) No 1272/2008 Contains: Acetone Buthyl acetate Poly(hexamethylene diisocyanate) 4-metylopentan-2-on Signal word: Danger **Pictogram:** 



H222



Date of issue: 2016-09-11

### 2K KLARLACK FD Spray

H229 Pressurised container: May burst if heated.

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

EUH204 Contains isocyanates. May produce an allergic reaction.

# **Precautionary statement(s)**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open fl ame or other ignition source.
- P251 Do not pierce or burn, even after use.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50  $^{\circ}C/122^{\circ}F$ .

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+ P352 IF ON SKIN: Wash with plenty of water.
- P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor/.../if you feel unwell.

P333+ P313 If skin irritation or rash occurs: Get medical advice/attention.

 $P337 + P313 \ If \ eye \ irritation \ persists: \ Get \ medical \ advice/attention.$ 

P501 Dispose of contents/container to an authorised waste collection point.

# 2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

UN: 1950

VOC (2004/42/EC, IIe: 840) 666 g/l

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1. Substances

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Nazwa niebezpiecznej substancji	Zakres stężeń	Numer CAS	Numer indeksowy	Numer WE	Symbole niebezpieczeństwa
<b>Dimethyl ether</b> REACH Reg No: 01-2119472128-37	25-50%	115-10-6	603-019-00-8	204-065-8	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280
<b>Acetone</b> REACH Reg. No 01-2119471330-49	10-25%	67-64-1	606-001-00-8	200-662-2	GHS02; GHS07 Dgr Flam.Liq.2: H225 EyeIrrit2: H319 STOT SE3: H336 EUH066
<b>Buthyl acetate</b> REACH Reg. No 01-2119485493-29	10-25 %	123-86-4	607-025-00-1	204-658-1	GHS02; GHS04 Wng Flam.Liq.3: H226 STOT SE3: H336 EUH066
<b>Xylene</b> REACH Reg. No: 01-2119488216-32	5-<10%	1330-20-7	601-022-00-9	215-525-7	GHS02; GHS07 ; GHS08 Dgr FlamLiq3: H226 AcuteTox4: H302 AcuteTox4: H332 SkinIrrit2: H315 EyeIrrit2: H319 AspTox1: H304 STOT RE2: H373 STOT SE3: H335

	SATEFY DATA SHEET						
AUTO-PLAST PRODUKT	Date of issue: 2016-09-11			2K KLA	RLACK FD	Spray Page 3 z 8	
Poly(hexamethylene diisocyanate)	5-10 %	28182-81-	2	brak	500-060-2	GHS07; Wng AcuteTox4: H SkinSens1: H STOT SE3: H	317
5-metyloheksan-2-on	1-2,5%	110-12-3		606-026-00-4	203-737-8	GHS02; GHS07 Dgr FlamLiq3: H226 AcuteTox4: H332	
<b>4-metylopentan-2-on</b> REACH> Reg. No 01-2119473980-30	1-2,5%	108-10-1 606-004-00-4 203-550-1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		GHS02; GHS07 Dgr FlamLiq2: H225 AcuteTox4: H332 EyeIrrit2: H319 STOT SE3: H335			
<b>Ethylbenzene</b> REACH REg. No 01-2119489370-35	1-2,5 %	100-41-4		601-023-00-4	202-849-4	GHS02; GHS07 ; GHS08 Dgr Flam. Liq.2: H225 AspTox1: H304 STOT RE2: H373 Acute Tox.4: H332 SkinIrrit2: H315 EyeIrrit2: H319 STOT SE3: H335	
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha – unspecified; (Does not contain benzene; notes: H and P)	1-2,5%	64742-95-6		649-356-00-4	265-199-0	GHS02; GHS08;GHS09 Dgr Flam. Liq. 3, H226 Asp. Tox. 1: H304 AquaticChronic 2: H411 STOT SE 3; H335+H336	
Poly(isophorone diisocyanate)	<1 %	53880-05-0		-	-	GHS07 Dgr SkinSens.1: H317	
Pentano-2,4-dione	<1%	123-54-6		606-029-00-0	204-634-0	GHS02; GHS07 Dgr FlamLiq3: H226 AcuteTox4: H302	
1,2,4-trimethylbenzene	<1 %	95-63-6 601-043-00-3 202-436-9 Wn Skin Eye STO		GHS02; GHS Wng Flam.Liq.3: H AcuteTox4: H SkinIrrit2: H3 EyeIrrit2: H3 STOTSE3: H AquaticChron	1226 1332 315 19 335		

	SATEFY DATA SHEET						
AUTO-PLAST PRODUKT	Date of issue: 2016-09-11		2K KLA	Page 4 z 8			
<b>1,3,5-trimethylbenzene;</b> <b>mesitylene</b> REACH Reg. No: 01-2119463878-19	<1%	108-67-8	601-025-00-5	203-604-4	GHS02; GHS Wng Flam.Liq.3: H STOTSE3: H AquaticChroi	1226 335	

Full text of R-Phrases and H-Phrases can be found under heading 16

# SECTION 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

### In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

### In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious

person. Consult a doctor immediately and show him label or Safety Data Sheet.

### In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

### 4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. May cause drowsiness or dizziness. Contains isocyanates. May produce an allergic reaction.

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

**Treatment:** 

None

# SECTION 5. FIRE-FIGHTING MEASURES

# 5.1. Extinguishing media

#### Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

# 5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

# 5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

#### **6.2. Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up



#### Date of issue: 2016-09-11

#### 2K KLARLACK FD Spray

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

#### **6.4. Reference to other sections**

See Section 8 for information on personal protection equipment.

### SECTION 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

No data.

### 8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile :  $\geq 0.45$  mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

#### Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

Thermal Hazards:

None

Environmental exposure controls:

None

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance and colour: liquid, aerosol, color accordkig to the label Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range: -24°C Upper/lower flammability or explosive limits: 2.6-18.6 %



Date of issue: 2016-09-11

2K KLARLACK FD Spray

Page 6 z 8

Vapour density: N.D. Flash point: 0°C Evaporation rate: N.A. Vapour pressure: 5200 hPa Density:  $865 \text{ kg/m}^3 (20^{\circ}\text{C})$ Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: 235°C Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: N.D. Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC: 666 g/l

# SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity Mixture is not reactive. 10.2. Chemical stability Stable under normal conditions of handling and storage. 10.3. Possibility of hazardous reactions None. 10.4. Conditions to avoid - solar radiation - sparks - flame - heat **10.5. Incompatible materials** - strong oxidisers - strong acids 10.6. Hazardous decomposition products None.

# SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects
May cause an allergic skin reaction
Causes serious eye irritation
May cause drowsiness or dizziness
Contains isocyanates. May produce an allergic reaction.
a) acute toxicity: no hazard
b) skin corrosion/irritation: no hazard
c) serious eye damage/irritation: Causes serious eye irritation
d) respiratory or skin sensitization: May cause an allergic skin reaction. Contains isocyanates. May produce an allergic reaction.
e) germ cell mutagenicity: no hazard
f) carcinogenicity: no hazard
g) reproductive toxicity: no hazard
h) STOT-single exposure: may cause drowsiness or dizziness.
i) STOT-repeated exposure: no hazard

j) aspiration hazard: no hazard

# SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity
Mixture is not classified as hazarodus.
12.2. Persistence and degradability
No data.
12.3. Bioaccumulative potential
No data.



Date of issue: 2016-09-11

2K KLARLACK FD Spray

Page 7 z 8

12.4. Mobility in soil
No data
12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
12.6. Other adverse effects
None

### SECTION 13. DISPOSAL CONSIDERATIONS

### **13.1.** Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

#### SECTION 14. TRANSPORT INFORMATION

14.1. UN number
1950
14.2. UN proper shipping name
Aerosols, flammable
14.3. Transport hazard class(es)
2
14.4. Packing Group
No
14.5. Environmental hazards
No
14.6. Special Precautions for User
During handling wear personal protection equipment (see Section 8)
Avoid heat and flame.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
N.A.
Label: 2.1

# SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions : Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive) **15.2. Chemical Safety Assessment** 

No

#### SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:				
H220	Extremely flammable gas			
H222	Extremely flammable aerosol			
H225	Highly flammable liquid and vapour			
H280	Contains gas under pressure; may explode if heated			
H304	May be fatal if swallowed and enters airways			
H312	Harmful in contact with skin			
H315	Causes skin irritation			
H317	May cause an allergic skin reaction			
H319	Causes serious eye irritation			
H332	Harmful if inhaled			
H335	May cause respiratory irritation			
H336	May cause drowsiness or dizziness			
H400	Very toxic to aquatic life			



# Date of issue: 2016-09-11

# 2K KLARLACK FD Spray

H411 Toxic to aquatic life with long lasting effects

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.