



Date of issue: 2016-06-16

APP 2K-HS-Harter Normal/Fast

Page 1 z 8

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: **APP 2K-HS-Harter Normal/Fast** Trade code: **020518**, **020519**, **020520**, **020521**

1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Hardener

1.3. Details of the supplier of the safety data sheet

Company: APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: <u>www.app.com.pl</u>

Safety Data Sheet e-mail: Tomasz Golda, t.golda@app.com.pl

1.4. <u>Emergency telephone number:</u> +**48 (61) 437 00 00**

Date of issue: 2016-06-16

SECTION 2. HAZARDS IDENTIFICATION 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS07

Danger

H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction H319 Causes serious eve irritation H335 May cause respiratory irritation H336 May cause drowsiness or dizziness H412 Harmful to aquatic life with long lasting effects EUH204 Contains isocyanates. May produce an allergic reaction. EUH066 Repeated exposure may cause skin dryness or cracking. 2.2. Label elements Labelling according Regulation (EC) No 1272/2008 Contains: n-butyl acetate Poly(hexamethylene diisocyanate) Ethyl acetate Tosyl isocyanate Signal word: Danger **Pictogram:**



Date of issue: 2016-06-16

APP 2K-HS-Harter Normal/Fast





GHS07

Hazard statement(s)

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H412 Harmful to aquatic life with long lasting effects

EUH204 Contains isocyanates. May produce an allergic reaction.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P303+ P361+ P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006 UN: 1263

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
n-butyl acetate REACH Reg. No 01-2119485493-29	50-60 %	123-86-4	607-025-00-1	204-658-1	GHS02; GHS04 Wng Flam.Liq.3: H226 STOT SE3: H336 EUH066

	SATEFY DATA SHEET							
AUTO-PLAST PRODUKT	Date of issue: 2016-06-16		APP 2K-HS-H	larter Normal	Fast Page 3 z 8			
Poly(hexamethylene diisocyanate) REACH Reg. No 01-2119488934-20	10-<25 %	28182-81-2	2 brak	500-060-2	GHS07; Wng AcuteTox4: H332 SkinSens1: H317 STOT SE3: H335			
Ethyl acetate REACH Reg. No 01-2119475103-46	10-<25%	141-78-6	607-022-00-5	205-500-4	GHS02; GHS07 Dgr Flam. Liq. 2; H225 Eye Irrit. 2: H319 STOT SE 3: H336			
2-methoxy-1- methylethyl acetate REACH Reg. No: 01-2119475791-29- XXXX	2.5-<10%	108-65-6	607-195-00-7	203-603-9	GHS02 Wng FlamLiq3: H226			
2-Butoxyethyl acetate REACH Reg. No: 01-2119475112-47	≤5%	112-07-2	607-038-00-2	203-933-3	GHS07 Wng AcuteTox4: H312 AcuteTox4: H332			
Tosyl isocyanate	0,1-0,3 %	4083-64-1	615-012-00-7	223-810-8	GHS07; GHS Dgr RespSens1: I SkinIrrit2: H EyeIrrit2: H STOT SE3: I	1334 1315 319		
Dibutyltin dilaurate REACH Reg. No: 01-2119496068-27	0,25-0,3%	77-58-7	-	201-039-8	GHS06; GHS GHS08; GHS AcuteTox3: I Muta2: H341 Repr1B: H36 STOT RE1: I AquaticAcut AquaticChro AcuteTox4: I SkinIrrit2: H EyeIrrit2: H	509 Dgr H301 50 H372 e1: H400 nic1: H410 H312 [315		

Full text of R-Phrases and H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact: Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty



APP 2K-HS-Harter Normal/Fast

of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

Date of issue: 2016-06-16

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious

person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness

Contains isocyanates. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Flammable liquid. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable iner absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the

use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or



SATEFY DATA SHEET

Date of issue: 2016-06-16

APP 2K-HS-Harter Normal/Fast

Page 5 z 8

cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Store at temperature 5-32°C. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin. Eye protection: Wear face visor or goggles in circumstances where eye contact can accidentally occur. Protection for skin/hands: Nitrile gloves. Respiratory protection: Respiratory protection. Thermal Hazards: None Environmental exposure controls: None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, color according to the label Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range:77°C Upper/lower flammability or explosive limits: 1.2-11.5% (v/v) Vapour density: N.D. Flash point: 14°C Evaporation rate: N.A. Vapour pressure: N.D. Density: 964kg/m³ (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity: 13s (DIN 53211/4) Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC: 631.22 g/l

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity Mixture is not reactive.



SATEFY DATA SHEET

APP 2K-HS-Harter Normal/Fast

10.2. Chemical stability

Stable under normal conditions of handling and storage.

Date of issue: 2016-06-16

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

- solar radiation
- sparks
- flame
- heat

10.5. Incompatible materials

- nitrous gases
- hydrogen chloride
- prussic acid
- carbon oxides
- nitrogen oxides
- strong acids
- isocyanates may react with alcohols, amines, phenols, amides, thiols, metalorganic substances, surfactants
- isocyanates with moisture may polymerize
- may be corrosive to cupper, zinc, aluminum, plastic and rubber

10.6. Hazardous decomposition products

None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects May cause an allergic skin reaction Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness Contains isocyanates. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking. a) acute toxicity: no hazard b) skin corrosion/irritation: skin irritation. c) serious eye damage/irritation: Causes serious eye irritation d) respiratory or skin sensitization: May cause an allergic skin reaction, Contains isocyanates. May produce an allergic reaction. e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard g) reproductive toxicity: no hazard h) STOT-single exposure: May cause drowsiness or dizziness, May cause respiratory irritation i) STOT-repeated exposure: no hazard j) aspiration hazard: no hazard Repeated exposure may cause skin dryness or cracking. N-buthyl acetate: LD50 (rat, ingestion): 14000 mg/kg LD50 (rabbit, skin): >5000 mg/kg LC50 (rat, inhalation): 9660 mg/m³/4h ethyl acetate: LD50 (rat, ingestion): 6100 mg/kg LD50 (rabbit, skin): >20000 mg/kg

LC50 (rat, inhalation): 5856 mg/m³/4h

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects 12.2. Persistence and degradability No data. 12.3. Bioaccumulative potential No data. 12.4. Mobility in soil No data 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None 12.6. Other adverse effects



SATEFY DATA SHEET

Date of issue: 2016-06-16

APP 2K-HS-Harter Normal/Fast

None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number
1263
14.2. UN proper shipping name
Paint
14.3. Transport hazard class(es)
3

14.4. Packing Group
III

14.5. Environmental hazards
No

14.6. Special Precautions for User
During handling wear personal protection equipment (see Section 8)
Avoid heat and flame.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
N.A.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

SECTION 16. OTHER INFORMATION

- Full text of phrases referred to in Section 3:
- H225 Highly flammable liquid and vapour
- H226 Flammable liquid and vapour
- H301 Toxic if swallowed
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness

H341 Suspected of causing genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H360 May damage fertility or the unborn child (state specific effect if known)(state route of exposure if

it is conclusively proven that no other routes of exposure cause the hazard)

H372 Causes damage to organs through prolonged or repeated exposure (state all organs affected, if known) through prolonged or repeated exposure (stateroute of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

	D	F
AUTO-PLA	ST PRO	DUKT

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.