



Date of issue: 2015-12-04

APP -2K Epoksy Verdunnung

Page 1 z 7

# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: APP 2K Epoksy Verdunnung Trade code: 030146


1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Solvent.


1.3. Details of the supplier of the safety data sheet Company: APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: app@app.com.pl Strona WEB: www.app.com.pl

Safety Data Sheet e-mail: Tomasz Gołda, t.golda@app.com.pl

1.4. <u>Emergency telephone number:</u> +48 (61) 437 00 00

Date of issue: 2015-12-04





#### Hazard statement(s)

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H318 Causes serious eye damage
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H411 Toxic to aquatic life with long lasting effects

#### **Precautionary statement(s)**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
- P331 Do NOT induce vomiting.
- P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor/...
- P403+ P233 Store in a well-ventilated place.Keep container tightly closed.

P501 Dispose of contents/container according to local/regional/national/international regulations.

#### 2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

UN: 1993

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1. Substances

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
					R10 Xn:R20/21 Xi: R38
Reaction mass of ethylbenzene and m-xylene and p-xylene REACH Reg. No 01-2119488216-32	40-60%	1330-20-7	601-022-00-9	215-525-7	GHS02; GHS07 Wng FlamLiq3: H226 AcuteTox4: H312 AcuteTox4: H332 SkinIrrit2: H315

		SATEFY DATA SHEET							
AUTO-PLAST PRODUKT		Date of issue: 2015-12-04			APP -2k	dunnung	Page 3 z 7		
	Solvent naphtha (petroleum), light aromatic REACH Reg. No : 01-2119455851-35	30%	64742-95-6 108-65-6		649-356-00-4	256-199-0	R10         Xn: R65         Xi: R37         R66; R67         N: R51/53         GHS02; GHS07; GHS08;         GHS09       Dgr         Flam.Liq.3: H226         Asp.Tox.1: H304         AquaticChronic2:H411         STOT SE3: H335         STOT SE3: H336         EUH066         R10         GHS02         Wng         FlamLiq3: H226		
	<b>2-methoxy-1-methylethyl</b> acetate REACH Reg. No: 01-2119475791-29-XXXX	<20%			607-195-00-7	203-603-9			
	Cyclohexanone	<10%	108-94-1		606-010-00-7	203-631-1	R10 Xn: R20 GHS02 Wng FlamLiq3: H220 AcuteTox4: H33		
	<b>Butan-1-ol;</b> REACH Reg. No 01-2119484630-38	<5%	71-36-3		603-004-00-6	200-751-6	R10 Xn; R22 Xi; R37/38; R41 R67 GHS02; GHS05 Dgr Flam. L Acute Tox. 4: H SE 3: H335 Skin H315 Eye Dam. STOT SE 3: H33	; GHS07 iq. 3: H226 302 STOT i Irrit. 2: 1: H318	

Full text of R-Phrases and H-Phrases can be found under heading 16

#### SECTION 4. FIRST AID MEASURES

#### 4.1. Description of first aid measures

#### In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

#### In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

#### In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet. **4.2. Most important symptoms and effects, both acute and delayed:** 



Date of issue: 2015-12-04

APP -2K Epoksy Verdunnung

Page 4 z 7

May be fatal if swallowed and enters airways. Causes serious eye damage. May cause drowsiness or dizziness **4.3. Indication of any immediate medical attention and special treatment needed** 

In case if ingestion consult a doctor.

Treatment:

None

# SECTION 5. FIRE-FIGHTING MEASURES

## 5.1. Extinguishing media

### Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

## 5.2. Special hazards arising from the substance or mixture:

Flammable liquid. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

#### 5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

#### **6.2.** Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

# 6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

## 6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

# SECTION 7. HANDLING AND STORAGE

## 7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

# 7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on



APP -2K Epoksy Verdunnung

solid, hydrocarbons-proof floor. 7.3. Specific end use(s) None.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

N.A.

#### 8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Date of issue: 2015-12-04

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile :  $\geq 0.45$  mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

Thermal Hazards:

None

Environmental exposure controls: None

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, colourless Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range: N.D. Upper/lower flammability or explosive limits: N.D. Vapour density: N.D. Flash point: 30°C Evaporation rate: N.A. Vapour pressure: N.D. Density:830-930 kg/m<sup>3</sup> (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: N.D. Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: N.D. Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC: 880 g/l

#### SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity
Mixture is not reactive.
10.2. Chemical stability
Stable under normal conditions of handling and storage.
10.3. Possibility of hazardous reactions
None.
10.4. Conditions to avoid
- solar radiation



APP -2K Epoksy Verdunnung

Page 6 z 7

- sparks

- flame

- heat

10.5. Incompatible materials

- strong oxidisers

- strong acids

**10.6. Hazardous decomposition products** 

None.

# SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye damage May cause respiratory irritation May cause drowsiness or dizziness a) acute toxicity: no hazard b) skin corrosion/irritation: Causes skin irritation c) serious eye damage/irritation: Causes serious eye damage d) respiratory or skin sensitization: no hazard e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard g) reproductive toxicity: no hazard h) STOT-single exposure: May cause drowsiness or dizziness i) STOT-repeated exposure: no hazard j) aspiration hazard: May be fatal if swallowed and enters airways

Date of issue: 2015-12-04

# SECTION 12. ECOLOGICAL INFORMATION

#### 12.1. Toxicity

Toxic to aquatic life with long lasting effects
12.2. Persistence and degradability
Expected to be biodegradable. High volatility and fast evaporation. Mixture is not soluble in water. Mixture undergoes photolysis in air.
12.3. Bioaccumulative potential
No data.
12.4. Mobility in soil
No data
12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
12.6. Other adverse effects
None

#### SECTION 13. DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

# SECTION 14. TRANSPORT INFORMATION

14.1. UN number
1993
14.2. UN proper shipping name
Flammable liquids, n.o.s.
14.3. Transport hazard class(es)
3
14.4. Packing Group
III
14.5. Environmental hazards
Yes
14.6. Special Precautions for User
During handling wear personal protection equipment (see Section 8)



Date of issue: 2015-12-04

APP -2K Epoksy Verdunnung

# Avoid heat and flame.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** N.A.

## SECTION 15. REGULATORY INFORMATION

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

## Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive)

# 15.2. Chemical Safety Assessment

No

# SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:					
R10	Flammable				
R11	Highly flammable				
R20	Harmful by inhalation				
R21	Harmful in contact with skin				
R36	Irritating to eyes				
R37	Irritating to respiratory system				
R38	Irritating to skin				
R39	Danger of very serious irreversible effects				
R43	May cause sensitisation by skin contact				
R65	Harmful: may cause lung damage if swallowed				
R66	Repeated exposure may cause skin dryness or cracking				
R67	Vapours may cause drowsiness and dizziness				
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment				
H225	Highly flammable liquid and vapour				
H226	Flammable liquid and vapour				
H304	May be fatal if swallowed and enters airways				
H312	Harmful in contact with skin				
H315	Causes skin irritation				
H317	May cause an allergic skin reaction				
H319	Causes serious eye irritation				
H332	Harmful if inhaled				
H335	May cause respiratory irritation				
H336	May cause drowsiness or dizziness				
H411	Toxic to aquatic life with long lasting effects				

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.