SATEFY DATA SHEET



Date of issue: 2016-05-25

APP PS 50 Spray

Page 1 z 7

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. <u>Product Identifier</u>

Trade name: APP PS 50 Spray Trade code: 212017

1.2. <u>Relevant identified uses of the substance/mixture and uses advised against</u> Window Cleaning Professional Foam

1.3. <u>Details of the supplier of the safety data sheet</u> APP Sp. z o. o. ul. Przemysłowa 10, 62 – 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: <u>app@app.com.pl</u> Strona WEB: <u>www.app.com.pl</u>


Safety Data Sheet e-mail: Tomasz Gołda, t.golda@app.com.pl

1.4. <u>Emergency telephone number:</u> +48 (61) 437 00 00

Date of issue: 2016-05-25

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS02

APP Sp. z o.o. POLAND 62-300 Września ul. Przemysłowa 10, tel. +48(prf)61 437 00 00.





GHS07

Hazard statement(s)

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H319 Causes serious eye irritation

Precautionary statement(s)

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use
- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- P261 Avoid breathing spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves.
- P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container according to local/regional/national/international regulations.P501

2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006

UN: 1950

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Name	Conc.	CAS No	Index No	EC No	Classification:
Propane REACH Reg. No 01-2119486944-21	2.5-10 %	74-98-6	601-003-00-5	200-827-9	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280
Izobutane REACH Reg. No 01-2119485395-27	2.5-10 %	75-28-5	601-004-00-0	200-857-2	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280
Propan-2-ol; REACH Reg. No 01-2119457558-25	10-<20%	67-63-0	603-117-00-0	200-661-7	GHS02;GHS07 Dgr FlamLiq2: H225 EyeIrrit2: H319 STOT SE3: H336

AUTO-PLAST PRODUKT		SATEFY DATA SHEET					
		Date of issue: 2016-05-25		APP PS 50 Spra		у	Page 3 z 7
	Ammonia REACH Reg. No 02-2119752451-43	0,-<1 %	1336-21-6	007-001-01-2	215-647-6	GHS05; GH3 Dgr SkinCorr1B3 AquaticAcut	H314
	N-Lauroylsarcosine sodium salt REACG Reg. No -	≤0,1%	137-16-6	-	205-281-5	GHS05; GHS06 Dgr AcuteTox2: H330 SkinIrrit2: H315 EyeDam1: H318	

Full text of R-Phrases and H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of

time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious

person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

APP AUTO-PLAST PRODUKT

Date of issue: 2016-05-25

APP PS 50 Spray

SATEFY DATA SHEET

Page 4 z 7

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

N.A.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile : ≥ 0.45 mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

<u>Thermal Hazards:</u> None <u>Environmental exposure controls:</u> None

SATEFY DATA	SHEET



Date of issue: 2016-05-25

APP PS 50 Spray

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, white Odour: characteristic Odour threshold: N.D. pH: N.A. Melting point / freezing point: N.D. Initial boiling point and boiling range: N.D. Upper/lower flammability or explosive limits: N.D. Vapour density: N.D. Flash point: <0°C Evaporation rate: N.A. Vapour pressure: 5 bar (20°C) Density: 903 kg/m³ (15°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: >200°C Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: N.D. Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity Mixture is not reactive. 10.2. Chemical stability Stable under normal conditions of handling and storage. 10.3. Possibility of hazardous reactions None 10.4. Conditions to avoid - solar radiation - sparks - flame - heat **10.5.** Incompatible materials - strong oxidisers - strong acids 10.6. Hazardous decomposition products None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects
Causes serious eye irritation
b) skin corrosion/irritation: no hazard
c) serious eye damage/irritation: Causes serious eye damage
d) respiratory or skin sensitization: no hazard
e) germ cell mutagenicity: no hazard
f) carcinogenicity: no hazard
g) reproductive toxicity: no hazard
h) STOT-single exposure: no hazard
i) STOT-repeated exposure: no hazard
j) aspiration hazard: no hazard

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity Mixture is not classified as hazardous.





Date of issue: 2016-05-25

APP PS 50 Spray

Page 6 z 7

12.2. Persistence and degradability Expected to be biodegradable.
12.3. Bioaccumulative potential No data.
12.4. Mobility in soil No data
12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
12.6. Other adverse effects None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number 1950 14.2. UN proper shipping name Aerosols, flammable 14.3. Transport hazard class(es) 3 14.4. Packing Group No 14.5. Environmental hazards No 14.6. Special Precautions for User During handling wear personal protection equipment (see Section 8) Avoid heat and flame. 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code N.A. Label: 2.1

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions : Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent

amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:		
H220	Extremely flammable gas	
H222	Extremely flammable aerosol	
H225	Highly flammable liquid and vapour	
H280	Contains gas under pressure; may explode if heated	
H300	Fatal if swallowed	
H314	Causes severe skin burns and eye damage	
H315	Causes skin irritation	
H318	Causes serious eye damage	
H319	Causes serious eye irritation	

AUTO-PL	PP-®
H336	Ma



APP PS 50 Spray

May cause drowsiness or dizziness Very toxic to aquatic life

Date of issue: 2016-05-25

H400 Very toxic to aquatic life The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.