



Date of issue: 2016-06-24

APP W 11

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

1.1. Product Identifier Trade name: APP W 11 Trade code: 212031

1.2. Relevant identified uses of the substance/mixture and uses advised against Petrolatum.

1.3. Details of the supplier of the safety data sheet

APP Sp. z o. o. **Company:** ul. Przemysłowa 10, 62 - 300 Września Tel. +48 (061) 437 00 00 Fax. +48 (061) 437 91 37 Mail: app@app.com.pl Strona WEB: www.app.com.pl

Safety Data Sheet e-mail: Tomasz Gołda, t.golda@app.com.pl

1.4. Emergency telephone number: +48 (61) 437 00 00

Date of issue: 2016-06-24

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Dgr

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

H412 Harmful to aquatic life with long lasting effects

EUH066 Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Labelling according Regulation (EC) No 1272/2008

Signal word: Contains:

Pentane Danger

Pictogram:



- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness
- H412 Harmful to aquatic life with long lasting effects



APP W 11

Page 2 z 7

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container in accordance with local regulations.

Date of issue: 2016-06-24

2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006 UN: 1950

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

Nazwa niebezpiecznej substancji	Zakres stężeń	Numer CAS	Numer indeksowy	Numer WE	Symbole niebezpieczeństwa
Propane REACH Reg. No 01-2119486944-21	12.5-20 %	74-98-6	601-003-00-5	200-827-9	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280
Butane REACH Reg. No 01-2119474691-32	10-12.5 %	106-97-8	601-004-00-0	203-448-7	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280
Izobutane REACH Reg. No 01-2119485395-27	5-10 %	75-28-5	601-004-00-0	200-857-2	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280
Pentane REACG Reg. No 01-2119459286-30	20-25 %	109-66-0	601-006-00-1	203-692-4	GHS02; GHS07; GHS08; GHS09 Dgr FlamLiq2: H225 Asp.Tox1:H304 STOT SE3:H336 AquaticChronic2: H411
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha;	10-12.5 %	64742-48-9	649-327-00-6	265-150-3	GHS08 Dgr Asp.Tox1: H304

	SATEFY DATA SHEET					
AUTO-PLAST PRODUKT	Date of issue: 2016-06-24		APP W 11			Page 3 z 7
Propan-2-ol; REACH Reg. No 01-2119457558-25	10-12.5%	67-63-0	603-117-00-0	200-661-7	GHS02;GHS0 Dgr FlamLiq2: H2 EyeIrrit2: H3 STOT SE3: H	225 19

Full text of R-Phrases and H-Phrases can be found under heading 16

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. . In case of irritation, consult a doctor

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

Treatment:

None

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of



Date of issue: 2016-06-24

APP W 11

Page 4 z 7

suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data.

8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Wear face visor or goggles in circumstances where eye contact can accidentally occur.

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves (nitrile : ≥ 0.45 mm, 240 min.). Protective clothing should be regularly inspected and maintained. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water. Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled. If operations are such that the excessive generation and inhalation of vapour may be anticipated, then suitable approved organic vapour and particulate respiratory equipment should be worn

Thermal Hazards:

None

Environmental exposure controls: None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance and colour: liquid, aerosol, yellow
Odour: characteristic
Odour threshold: N.D.
pH: N.A.
Melting point / freezing point: N.D.
Initial boiling point and boiling range: N.D.
Upper/lower flammability or explosive limits: 0.6-12.0 %
Vapour density: N.D.



Date of issue: 2016-06-24

APP W 11

Flash point: <0°C Evaporation rate: N.A. Vapour pressure: 3500 hPa (20°C) Density: 660 kg/m³ (20°C) Solubility in water: insoluble Solubility in organic solvents: soluble in aromatic solvents Lipid solubility: N.A. Partition coefficient (n-octanol/water): N.A. Ignition temperature: 240°C Auto-ignition temperature: N.A. Decomposition temperature: N.A. Viscosity dyn.: N.D. Viscosity kin.: N.D. Explosive properties: can form an explisive mixture in air Oxidizing properties: not oxidizing 9.2. Other information VOC: 561 g/l

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity Mixture is not reactive. 10.2. Chemical stability Stable under normal conditions of handling and storage. 10.3. Possibility of hazardous reactions None. 10.4. Conditions to avoid - solar radiation - sparks - flame - heat **10.5.** Incompatible materials - strong acids - strong oxidants 10.6. Hazardous decomposition products -carbon oxides - toxic gases and fumes

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects Causes serious eye irritation May cause drowsiness or dizziness Repeated exposure may cause skin dryness or cracking. a) acute toxicity: no hazard b) skin corrosion/irritation: no hazard c) serious eye damage/irritation: Causes serious eye irritation d) respiratory or skin sensitization: no hazard e) germ cell mutagenicity: no hazard f) carcinogenicity: no hazard g) reproductive toxicity: no hazard h) STOT-single exposure: May cause drowsiness or dizziness i) STOT-repeated exposure: no hazard i) aspiration hazard: no hazard Repeated exposure may cause skin dryness or cracking. **Pentane:** LD50 (rat, skin): >2500mg/kg LC50 (rat, inhalation): 100 mg/l/ 4h >5000 mg/kg LD50 (rabbit, skin):

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity Harmful to aquatic life with long lasting effects **Pentane:**



Date of issue: 2016-06-24

APP W 11

- crustacea EC50 (Daphnia magna): 9,7 mg/l/48h
- fish LC50 (Pimephales promelas): 18 mg/l/96h
12.2. Persistence and degradability
No data.
12.3. Bioaccumulative potential
No data.
12.4. Mobility in soil
No data
12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
12.6. Other adverse effects
None

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number 1950 14.2. UN proper shipping name Aerosols, flammable 14.3. Transport hazard class(es) 2 14.4. Packing Group No 14.5. Environmental hazards No 14.6. Special Precautions for User During handling wear personal protection equipment (see Section 8) Avoid heat and flame. 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code N.A. Label: 2.1

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Where applicable, refer to the following regulatory provisions : Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive) **15.2. Chemical Safety Assessment**

No

SECTION 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:				
H220	Extremely flammable gas			
H222	Extremely flammable aerosol			
H225	Highly flammable liquid and vapour			
H280	Contains gas under pressure; may explode if heated			
H304	May be fatal if swallowed and enters airways			
H319	Causes serious eye irritation			
H336	May cause drowsiness or dizziness			

AUTO-PLAST PRODUKT		SATEFY DATA SHEET				
		Date of issue: 2016-06-24	APP W 11	Page 7 z 7		
H411	Toxic to a	quatic life with long lasting effects				
H412		o aquatic life with long lasting effects				
EUH066	Repeated	d exposure may cause skin dryness or cracking.				

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.